


6.8×4.7 Circularity/ Single Turn /Trimming Potentiometer


-- 3329H--



... Install dimension



... Mutall dimension



Standard Resistance Table

Resistance (Ohms)	Resistance Code
10	100
20	200
50	500
100	101
200	201
500	501
1,000	102
2,000	202
5,000	502
10,000	103
20,000	203
25,000	253
50,000	503
100,000	104
200,000	204
250,000	254
500,000	504
1,000,000	105
2,000,000	205

Electrical Characteristics

Standard Resistance Range.....50Ω~2MΩ
 Resistance Tolerance.....±10%
 Absolute Minimum Resistance.....≤1%R或10Ω
 Contact Resistance Variation.....CRV≤3%
 Insulation Resistance.....R1≥1GΩ (100Vac)
 Withstand Voltage.....500Vac
 Effective Travel.....280°

Environmental Characteristics

Power Rating, 300 volts max
0.25W@70°C, 0W@125°C
 Temperature Range.....-55°C~125°C
 Temperature Coefficient.....±250ppm/°C
 Temperature Variation.....-55°C, 30min, +125°C
30min 5cycles
ΔR≤5%R, Δ(Uab/Uac)≤5%
 Vibration.....10~500Hz, 0.75mm, 6h
ΔR≤5%R, Δ(Uab/Uac)≤7.5%R
 Collision.....390m/s², 4000cycles, ΔR≤5%R
 Electrical Endurance at 70°C.....0.5W@70°C
1000h, ΔR≤10%R, CRV≤3% or 5Ω
 Rotational Life.....200cycles
ΔR≤10%R, CRV≤3% or 5Ω

How To Order

