

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

34062-0025

Status:

Active

Overview:

MX150™ Sealed Connector System

Description:

MX150™ Sealed Female Receptacle, Single Row, 2 Circuits, Keying Option A, with CPA, without Clip Slot, Black



Documents:

3D Model

Drawing (PDF)

Application Specification AS-34062-000 (PDF)

RoHS Certificate of Compliance (PDF)

General	
Product Family	Crimp Housings
Series	34062
Application	Power
More Detailed Tech Information	http://ewcap.uscarteams.org
Overview	MX150™ Sealed Connector System
Product Name	MX150™
UPC	883906212247

Physical	
Circuits (maximum)	2
Circuits Detail	2
Color - Resin	Black
Gender	Female
Glow-Wire Compliant	No
Keying to Mating Part	Yes
Lock to Mating Part	Yes
Material - Resin	Nylon
Net Weight	4.400/g
Number of Rows	2
Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface	5.00mm
Pitch - Termination Interface	5.00mm
Polarized to Mating Part	Yes
Stackable	No
Temperature Range - Operating	-40°C to +125°C

Electrical	
Current - Maximum per Contact	21A

Material Info

Reference - Drawing Numbers	
Application Specification	AS-34062-000
Sales Drawing	SD-34062-002

EU RoHS

ELV and RoHS

Compliant

REACH SVHC

Contains SVHC: No

Low-Halogen Status

Low-Halogen

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

34062Series

Mates With

34675 MX150™ Cable-Sealed Male Connector

Use With

34083 Tin (Sn) Cable Seal Female Terminal, 34081 Silver (Ag) and Gold (Au) Cable Seal Female Terminal

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION