Digital Viscotesters

Battery operated viscosity meter, one button operation, choice of High or Low range model

With Direct readings on large digital display

Features:

- Measuring range:
  Model 345055 Low range - 1.5 to 330mPa-s (1.5 to 330cP)
  Model 345060 High range - 0.3 to 4000dPa-s (30 to 400,000cP)
- Accurate to 5% of reading
- One button turns the motor on and selects the rotor
- Use as handheld or with optional lab stand with base
- Sample temperature to 300°F (150°C)
- Fast, accurate determination of fluid viscosity
- Popular for fluids with viscosity ranging from castor oil or honey to tar
- Ideal for adhesives, paint, oils and fats, inks, pulp, rubber, foods, petroleum products, and cosmetics
- Dimensions: 7x6.7x3.5" (177.8x165.1x88.9mm)
  Weight: 1.72lbs (0.78kg)
- Complete with three interchangeable rotors, one sample cup, case, stand, and four AA batteries



Optional lab stand with base clip.



Complete Kit includes rotors, cups, holder for lab stand, and case.

Ordering Information:

345055 .....Digital Viscotester (Low range 1.5 to 330cP)
345060 .....Digital Viscotester (High range 30 to 400,000cP)
345104 .....Lab Stand with base clamp

Specifications subject to change without notice.
Copyright © 2007 Extech Instruments Corporation. All rights reserved including the right of reproduction in whole or in part in any form.

10/13/08 - R1