

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

34566-1503

Status:

Active

Overview:

MX123™ Sealed Connection System

Description:

2.54mm Pitch, MX123™ Female Receptacle Housing, Keying Option C, Wire Dress Option 9, 73 Circuits, Blue TPA



Documents:

3D Model

Drawing (PDF)

Product Specification PS-34566-0000 (PDF)

Application Specification AS-34566-001 (PDF)

RoHS Certificate of Compliance (PDF)

General	
Product Family	Crimp Housings
Series	34566
Application	Power, Wire-to-Board
Comments	See Sales Drawing for number of Open Circuits
Overview	MX123™ Sealed Connection System
Product Name	MX123
UPC	800756780061
Physical	
Circuits (maximum)	73
Circuits Detail	73
Color - Resin	Blue
Gender	Female
Glow-Wire Compliant	No
Keying to Mating Part	Yes
Lock to Mating Part	Yes
Material - Resin	Nylon
Net Weight	50.423/g
Number of Rows	4
Packaging Type	Tray
Panel Mount	No
Pitch - Mating Interface	2.54mm
Pitch - Termination Interface	2.54mm
Polarized to Mating Part	Yes
Stackable	No
Temperature Range - Operating	-40°C to +125°C
Electrical	
Current - Maximum per Contact	11A, 25A
Material Info	
Reference - Drawing Numbers	
Application Specification	AS-34566-001
Product Specification	PS-34566-0000

EU RoHS

ELV and RoHS

Compliant

REACH SVHC

Contains SVHC: No

Low-Halogen Status

Low-Halogen

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

34566Series

Mates With

MX123™ Header [31386](#) , [31387](#)

Use With

MX64 Female Terminals [33467](#)

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION