molex
one company > a world of innovation

This document was generated on 09/16/2014

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 34708-2007
Status: Active
Overview: Stac64™ Single, Multi-Pocket and Hybrid Header System
Description: Stac64™ 2 Bay Right Angle Headers, 36 Circuits, Bay A 16 Circuit Signal Header, Polarization C, Brown; Bay B 20 Circuit Signal Header, Polarization C, Tray

Documents:

- 3D Model
- Drawing (PDF)
- Product Specification PS-31372-100 (PDF)
- Product Specification PS-34729-020 (PDF)
- Application Specification AS-34729-020 (PDF)
- RoHS Certificate of Compliance (PDF)
- Product Literature (PDF)

General

Product Family	PCB Headers
Series	34708
Application	Power, Wire-to-Board
Comments	Bay A 16 Circuits Stac64™ Right Angle Signal Header, Polarization C. Bay B 20 Circuits Stac64™ Right Angle Signal Header, Polarization C
Overview	Stac64™ Single, Multi-Pocket and Hybrid Header System
Product Literature Order No	987650-4561
Product Name	Stac64™
UPC	887191467702

Physical

Breakaway	No
Circuits (Loaded)	36
Circuits (maximum)	36
Color - Resin	Brown
Durability (mating cycles max)	10
First Mate / Last Break	No
Glow-Wire Compliant	No
Guide to Mating Part	No
Keying to Mating Part	None
Lock to Mating Part	Yes
Material - Metal	Copper Alloy
Material - Plating Mating	Nickel
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Net Weight	16.117/g
Number of Rows	2
Orientation	Right Angle
PC Tail Length	3.36mm
PCB Locator	Yes
PCB Retention	None
PCB Thickness - Recommended	1.57mm
Packaging Type	Tray
Pitch - Mating Interface	2.54mm
Pitch - Termination Interface	2.54mm
Polarized to Mating Part	Yes
Polarized to PCB	Yes
Shrouded	Yes
Stackable	No
Surface Mount Compatible (SMC)	N/A
Temperature Range - Operating	-40°C to +100°C

EU RoHS
ELV and RoHS Compliant
REACH SVHC
Contains SVHC: No
Low-Halogen Status
Low-Halogen

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, click here

Please visit the Contact Us section for any non-product compliance questions.

Search Parts in this Series
34708Series

Mates With
31408 USCAR 2.54mm (.100”) Pitch Receptacle, 31372 5.25mm (.206") Pitch Hybrid Receptacle Assembly, 34729 2.54mm (.100") Pitch Stac64™ Right Angle Receptacle

Termination Interface: Style	Through Hole

Electrical

Current - Maximum per Contact	Contact Molex
Voltage - Maximum	500V

Material Info

Reference - Drawing Numbers

Application Specification	AS-34729-020
Product Specification	PS-31372-100, PS-34729-020
Sales Drawing	SD-34708-200

This document was generated on 09/16/2014

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION