Bulletin I2715 rev. I 03/03

International
IOR Rectifier

MB SERIES

SINGLE PHASE BRIDGE **Power Modules**

25 A
35 A

Features

- Universal, 3 way terminals: push-on, wrap around or solder
- High thermal conductivity package, electrically insulated case
- Center hole fixing
- Excellent power/volume ratio
- UL E 62320 approved
- Nickel plated terminals solderable as per MIL-STD-202 Method 208; solder: Sn/Pb (60/40); solder temperature: 235-260°C max. time: 8-10 secs

Description

A range of extremely compact, encapsulated single phase bridge rectifiers offering efficient and reliable operation. They are intended for use in general purpose and instrumentation applications.

Major Ratings and Characteristics

Parameters		26MB-A	36MB-A	Units
I_O		25	35	A
	@ T_C	65	60	°C
I_{FSM}	@ 50Hz	400	475	A
	@ 60Hz	420	500	A
I^2t	@ 50Hz	790	1130	A^2s
	@ 60Hz	725	1030	A^2s
V_{RRM} range		200 to 1200		V
T_J		-55 to 150		°C

ELECTRICAL SPECIFICATIONS

Voltage Ratings

Type number	Voltage Code	V_{RRM} , maximum repetitive peak reverse voltage V	V_{RSM} , maximum non-repetitive peak rev. voltage V	I_{RRM} max. @ T_J max.
26MB..A 36MB..A	20	200	275	2
	40	400	500	
	60	600	725	
	80	800	900	
	100	1000	1100	
	120	1200	1300	

Forward Conduction

Parameters		26MB-A	36MB-A	Units	Conditions		
I_O	Maximum DC output current	25	35	A	Resistive or inductive load		
		20	28	A	Capacitive load		
	@ Case temperature	65	60	°C			
I_{FSM}	Maximum peak, one-cycle non-repetitive forward current	400	475	A	t = 10ms	No voltage reapplied	Initial $T_J = T_J$ max.
		420	500		t = 8.3ms		
		335	400		t = 10ms	100% V_{RRM} reapplied	
		350	420		t = 8.3ms		
I^2t	Maximum I^2t for fusing	790	1130	A^2s	t = 10ms	No voltage reapplied	
		725	1030		t = 8.3ms		
		560	800		t = 10ms	100% V_{RRM} reapplied	
		512	730		t = 8.3ms		
$I^2\sqrt{t}$	Maximum $I^2\sqrt{t}$ for fusing	5.6	11.3	$KA^2\sqrt{s}$	I^2t for time $t_x = I^2\sqrt{t} \times \sqrt{t_x}$; $0.1 \le t_x \le 10ms$, V_{RRM} = 0V		
$V_{F(TO)1}$	Low-level of threshold voltage	0.76	0.79	V	$(16.7\% \times \pi \times I_{F(AV)} < I < \pi \times I_{F(AV)})$, @ T_J max.		
$V_{F(TO)2}$	High-level of threshold voltage	0.92	0.96		$(I > \pi \times I_{F(AV)})$, @ T_J max.		
r_{t1}	Low-level forward slope resistance	6.8	5.8	mΩ	$(16.7\% \times \pi \times I_{F(AV)} < I < \pi \times I_{F(AV)})$, @ T_J max.		
r_{t2}	High-level forward slope resistance	5.0	4.5		$(I > \pi \times I_{F(AV)})$, @ T_J max.		
V_{FM}	Maximum forward voltage drop	1.11	1.14	V	T_J = 25 °C, I_{FM} = 40A_{PK} (26MB) T_J = 25 °C, I_{FM} = 55A_{PK} (36MB)		tp = 400µs
I_{RRM}	Max. DC reverse current	10	10	µA	T_J = 25 °C, per diode at V_{RRM}		
V_{INS}	RMS isolation voltage base plate	2700	2700	V	f = 50 Hz, t = 1s		

Thermal and Mechanical Specifications

	Parameters	26MB-A	36MB-A	Units	Conditions
T_j	Junction temperature range	-55 to 150 °C			
T_{stg}	Storage temperature range	-55 to 150 °C			
R_{thJC}	Max. thermal resistance junction to case	1.7	1.2	K/W	Per bridge
R_{thCS}	Max. thermal resistance, case to heatsink	0.2		K/W	Mounting surface , smooth, flat and greased
wt	Approximate weight	20		g	
T	Mounting Torque ± 10%	2.0		Nm	Bridge to heatsink

Ordering Information Table

Device Code



1 - Current rating code:
- 26 = 25A (Avg)
- 36 = 35A (Avg)

2 - Circuit configuration:
MB = Single phase european coding

3 - Voltage code: MB series = code x 10 = V_{RRM}

4 - Diode bridge rectifier:
A = 26MB, 36MB Series

Outline Table



Suggested plugging force:
200 N max; axially applied to faston terminals



Not To Scale

All dimensions in millimetres (inches)



Fig. 1 - Current Ratings Characteristics



Fig. 2 - Forward Voltage Drop Characteristics

Maximum Allowable Ambient Te



Fig. 3 - Total Power Loss Characteristics



Fig. 4 - Maximum Non-Repetitive Surge Current



Fig. 5 - Maximum Non-Repetitive Surge Current



Fig. 6 - Current Ratings Characteristics



Fig. 7 - Forward Voltage Drop Characteristics

Maximum Allowable Ambient Te



Fig. 3 - Total Power Loss Characteristics



Fig. 9 - Maximum Non-Repetitive Surge Current



Fig. 10 - Maximum Non-Repetitive Surge Current

Data and specifications subject to change without notice.
This product has been designed and qualified for Industrial and Consumer Level.
Qualification Standards can be found on IR's Web site.

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7309
Visit us at www.irf.com for sales contact information. 03/03