ADELS contact

Pluggable PCB Connectors

GSK 864/ 3

Female Header, Pin Spacing: 5.08 mm, 3 pole, Voltage Rating: 250 V, Current Rating: 8 A, Cross-Section: 1.5 mm², Connection Type: Screw

Order Info

Reference Number (ref. no.)	373403
Applications	Lighting, Electrical Appliances, Electronics
PU	250
EAN	4028012110445

Type

Type	Female Header
Number of poles	3 pole
Clamping Units per Pole	1
Colour	blue
Cross-Section	1.5 mm²
Connection Type	Screw
Protection Against Incorrect Plugging	yes

Technical Data

Voltage Rating	250 V
Current Rating	8 A
Insulating Material	PBT
Contact Material	Brass
Core Cross-Section min.	0.5 mm²
Core Cross-Section max.	1.5 mm²
Flammability Rating	V-0
max. Ambient Temperature Operation	60 °C
Type of Conductor Solid	yes
Type of Conductor Flexible	yes
Type of Conductor Stranded	yes
Stripping Length	6.0-6.5 mm
Assembly Contact Screw	0.6x3.5 / ↻ 0.5 Nm
Pin Spacing	5.08 mm
Approbation EN61984	GSK760_GST760_GSK_864_GSK864_EN61984_20060227_2011051
Approbation UL	GSK760_GSK860_GSK864_GSK865_UL_E63492_1-11_Description_w
Approbation CSA	GSK_GST_Printklemmen_Serie_20160404_CSA_70070893_Certificat