HT Series

UL Recognized
CSA Certified
VDE Approved



HT Series

- Designed to provide significant attenuation of RFI noise in the frequency range from 10kHz to 30MHz
- Size and cost-effective

Specifications

Maximum leakage current each Line to Ground:
@ 120 VAC 60 Hz: 2 µA
@250 VAC 50 Hz: 5 µA

Hipot rating (one minute):
Line to Ground: 2250 VDC
Line to Line: 1450 VDC

Rated Voltage (max): 250 VAC

Operating Frequency: 50/60 Hz

Rated Current: 3 to 15A

Operating Ambient Temperature Range (at rated current I_r): -10°C to +40°C
In an ambient temperature (T_a) higher than +40°C the maximum operating current (I_o) is calculated as follows: $I_o = I_r \sqrt{(85-Ta)/45}$

Ordering Information

6 E HT 7 M

- **Suffix**
  - M – Metric inserts *(style 7 only)*
  - Omit for standard or none
- **Input / Output Style**
  - 1 – .250 [6.3] spade terminals
  - 3 – Wire leads
  - 6 – Threaded bolt
  - 7 – IEC inlet* *(line side)*
    .250 [6.3] spade terminals *(load side)*
- **HT Series**
- **Leakage current designation**
  - E – Low leakage *(<0.5 mA)*
- **Current Rating**
  - 3, 6, 10 or 15A

*IEC 60320-1 C14 inlet mates with C13 connector

Available Part Numbers

3EHT1	6EHT7
3EHT3	6EHT7M
3EHT7	10EHT1
3EHT7M	10EHT3
6EHT1	15EHT1
6EHT3	15EHT6

Accessories

GA400: NEMA 5-15P to IEC 60320-1 C-13 line cord



Dimensions are in inches and millimeters unless otherwise specified. Values in italics are metric equivalents. Dimensions are shown for reference purposes only. Specifications subject to change.

For email, phone or live chat, please go to
te.com/help
corcom.com

HT Series

Electrical Schematics

3 & 6EHT



10EHT



15EHT



Case Styles

HT1 (3, 6, 10A)



Typical Dimensions:

Line/Load Terminals (4):	.250 [*6.3*] with .07 [*1.8*] Dia. hole
Ground Terminal (1):	.250 [*6.3*] with .07 x .16 [*1.8 x 3.8*] slot
Mounting Holes (2):	.188 [*4.78*] Dia.

HT1 (15A)



Typical Dimensions:

Line/Load Terminals (4):	.250 [*6.3*] with .07 [*1.8*] Dia. hole
Ground Terminal (1):	.250 [*6.3*] with .07 x .16 [*1.8 x 3.8*] slot
Mounting Slots (4):	.203 x .156 [*5.16 x 3.96*] Dia.

HT3



Typical Dimensions:

6A Wire Leads (5):	4.0 [*101.6*] Min., 18AWG
10A Wire Leads (5):	6.0 [152.4] Min., 18AWG
Mounting Holes (2):	.188 [4.78] Dia.

HT6



Typical Dimensions:

Terminals (5):	8-32, Torque 18 lbf-in. [*2.03* N-m] max. ± 2 [*.22*]
Mounting Slots (4):	.203 x .156 [*5.16 x 3.96*] Dia.

HT7 & HT7M



Typical Dimensions:

Load Terminals (2):	.250 [*6.3*] with .07 [*1.8*] Dia. hole
Ground Terminal (1):	.250 [*6.3*] with .07 x .16 [*1.8 x 3.8*] slot
Line Inlet (1):	IEC 60320-1 C14
HT7 Tapped Inserts (2):	6-32 x 1/4
HT7M Tapped Inserts (2):	M3 x .5

Dimensions are in inches and millimeters unless otherwise specified. Values in italics are metric equivalents. Dimensions are shown for reference purposes only. Specifications subject to change.

For email, phone or live chat, please go to
te.com/help
corcom.com

HT Series

Recommended Panel Cutout



Tolerance ± .005 [0.13]

Case Dimensions

Part No.	A (max)	B (max)	C (max)	D ± .015 / ± .38	E (max)
3EHT1, 6EHT1	**3.56** *90.4*	**2.15** *54.6*	**1.81** *46.0*	**2.938** *74.63*	**3.38** *85.9*
3EHT3, 6EHT3	**2.55** *64.8*	**2.15** *54.6*	**1.81** *46.0*	**2.938** *74.63*	**3.38** *85.9*
3EHT7 / 7M, 6EHT7 / 7M	**3.52** *89.4*	**2.25** *57.2*	**1.78** *45.2*	**1.575** *40.01*	**0.63*** *16.0**
10EHT1	**4.69** *119.1*	**2.27** *57.7*	**1.8** *45.7*	**4.063** *103.2*	**4.47** *113.5*
10EHT3	**3.69** *93.7*	**2.27** *57.7*	**1.8** *45.7*	**4.063** *103.2*	**4.47** *113.5*
15EHT1	**5.45** *138.4*	**3.12** *79.2*	**2.18** *55.4*	**3.5** *88.9*	**3.96** *100.6*
15EHT6	**5.95** *151.1*	**3.12** *79.2*	**2.18** *55.4*	**3.5** *88.9*	**3.96** *100.6*

*±0.02 [0.5]

Performance Data

Typical Insertion Loss

Measured in closed 50 Ohm system

Common Mode / Asymmetrical (L-G)
Differential Mode / Symmetrical (L-L)

3EHT



6EHT



10EHT



15EHT



Minimum Insertion Loss

Common Mode / Asymmetrical (Line to Ground)

Current Rating	Frequency – MHz .02	.02	.05	.08	.15	.5	1	2	5	10	20	30
3A	22	32	36	-	49	46	40	30	22	12	12	12
6A	16	23	32	41	46	41	33	26	15	9	6	2
10A	9	15	24	30	36	42	34	22	11	12	8	8
15A	4	9	18	22	27	41	34	22	12	12	5	2

Differential Mode / Symmetrical (Line to Line)

Current Rating	Frequency – MHz .02	.02	.05	.08	.15	.5	1	2	5	10	20	30
3A	3	1	30	-	61	70	65	65	48	40	32	32
6A	4	1	14	45	51	70	70	65	55	47	37	37
10A	7	8	17	32	52	70	70	70	65	55	40	35
15A	12	16	15	10	51	70	70	70	70	70	65	55

Dimensions are in inches and millimeters unless otherwise specified. Values in italics are metric equivalents. Dimensions are shown for reference purposes only. Specifications subject to change.

For email, phone or live chat, please go to **te.com/help** **corcom.com**