

|                      |                                                                                              |
|----------------------|----------------------------------------------------------------------------------------------|
| <b>Sales Region</b>  | Worldwide (except Japan)                                                                     |
| <b>Series</b>        | ALE                                                                                          |
| <b>Model</b>         | ALE-Rack mount                                                                               |
| <b>Status</b>        |  Production |
| <b>Option</b>        | Positive polarity                                                                            |
| <b>Option Lineup</b> | <a href="#">Please refer to here.</a>                                                        |
| <b>Accessories</b>   | <a href="#">Please refer to the catalog</a>                                                  |



| Electrical Characteristics       |               |
|----------------------------------|---------------|
| Input                            | 3-phase       |
| Input Voltage Range[AC]          | 180 to 264VAC |
| Input Frequency Range            | 47 to 63Hz    |
| Rated Output Voltage[DC]         | 15000Vdc      |
| Output Voltage Range[DC]         | 0 to 15000V   |
| Average Capacitor Charging Power | 4000J/sec     |
| Peak Capacitor Charging Power    | 5000J/sec     |
| Charge Current                   | 667mA         |
| Continuous DC Current            | 260mA         |
| Continuous DC Power              | 4kW           |
| Polarity                         | Positive      |
| Power Factor                     | 0.85          |
| Efficiency                       | 85% Typ.      |

| Package Type & Size |                           |
|---------------------|---------------------------|
| Package / Mounting  | Rack mount                |
| Width(W)            | 482mm Nom. (18.98in Nom.) |
| Height(H)           | 178mm Nom. (7.01in Nom.)  |
| Depth(D)            | 432mm Nom. (17.01in Nom.) |
| Weight              | 30kg Typ. (66.1lbs Typ.)  |

| Other                      |                                                                                                                                     |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Operating Temp. Range      | -20 to 45°C                                                                                                                         |
| Storage Temp. Range        | -40 to 85°C                                                                                                                         |
| Cooling                    | Forced air                                                                                                                          |
| Safety Standard(Certified) |                                                                                                                                     |
| Safety Standard(Conformed) |                                                                                                                                     |
| Remarks                    | This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions. |

! Images are for reference only and show exemplary products.  
! This PDF document was created based on the data listed on the TDK Corporation website.  
! All specifications are subject to change without notice.