


**4066****CMOS IC****QUAD BILATERAL SWITCH****DESCRIPTION**

The UTC **4066** is a quad bilateral switch intended for the transmission or multiplexing of analog or digital signals.

FEATURES

- * Wide supply voltage range: 3V ~ 15V.
- * High noise immunity : 0.45V_{DD} (typ.)
- * Wide range of digital and $\pm 7.5V_{PEAK}$ analog switching
- * "ON" resistance for 15V operation : 80 Ω
- * Matched "ON" resistance : $\Delta R_{ON}=5\Omega$ (typ.) over 15V signal input
- * "ON" resistance flat over peak-to-peak signal range
- * High "ON" / "OFF" : 65 dB (typ.)
- * output voltage ratio @ $f_{IS}=10kHz$, $R_L=10k\Omega$
- * High degree linearity: 0.1% distortion (typ.).
@ $f_{IS}=1kHz$, $V_{IS}=5V_{p-p}$.
 $V_{DD}-V_{SS}=10V$, $R_L=10k\Omega$
- * Extremely low "OFF" : 0.1nA (typ.)
- * switch leakage @ $V_{DD}-V_{SS}=10V$, $T_A=25^\circ C$
- * Extremely high control input impedance : $10^{12}\Omega$ (typ.)
- * Low crosstalk : -50dB (typ.)
- * between switches @ $f_{IS}=0.9MHz$, $R_L=1k\Omega$
- * Frequency response, switch "ON" : 40MHz (typ.)

**ORDERING INFORMATION**


Ordering Number		Package	Packing
Lead Free	Halogen Free		
4066L-D14-T	4066G-D14-T	DIP-14	Tube
-	4066G-S14-R	SOP-14	Tape Reel
-	4066G-P14-R	TSSOP-14	Tape Reel

4066L-D14-T (1)Packing Type (2)Package Type (3)Green Package	(1) R: Tape Reel, T: Tube (2) D14: DIP-14, P14: TSSOP-14, S14: SOP-14 (3) L: Lead Free, G: Halogen Free and Lead Free
--	--


MARKING

DIP-14	SOP-14 / TSSOP-14
UTC □□□□ 4066 □ □□ → Date Code → L: Lead Free → G: Halogen Free → Lot Code	UTC □□□□ 4066 G □□ → Date Code → Lot Code

■ PIN CONFIGURATION



■ SCHEMATIC DIAGRAM



■ **ABSOLUTE MAXIMUM RATINGS** ($V_{SS}=0V$, unless otherwise specified))

PARAMETER		SYMBOL	RATINGS	UNIT
Supply Voltage		V_{DD}	-0.5 ~ +18	V
Input Voltage		V_{IN}	-0.5 ~ $V_{CC}+0.5$	V
Power Dissipation	DIP-14	P_D	700	mW
	SOP-14/TSSOP-14		500	
Junction Temperature		T_J	+125	°C
Storage Temperature		T_{STG}	-40 ~ +150	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.
Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ **RECOMMENDED OPERATING CONDITIONS** ($V_{SS}=0V$, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Supply Voltage		V_{DD}	3 ~ 15	V
Input Voltage		V_{IN}	0 ~ V_{DD}	V
Operating Temperature Range		T_{OPR}	-40 ~ +85	°C

■ **DC ELECTRICAL CHARACTERISTICS** ($V_{SS}=0V$, unless otherwise specified)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNIT
Quiescent Device Current	I _{DD}	V _{DD} =5V			0.01	1.0	μA
		V _{DD} =10V			0.01	2.0	
		V _{DD} =15V			0.01	4.0	
SIGNAL INPUTS AND OUTPUTS							
Input or Output Leakage Switch “OFF”	I _{IS}	V _C =0			±0.1	±50	nA
“ON” Resistance	R _{ON}	R _L =10kΩ~ (V _{DD} -V _{SS} /2) V _C =V _{DD} , V _{SS} ~ V _{DD}	V _{DD} =5V		270	1050	Ω
			V _{DD} =10V		120	400	
			V _{DD} =15V		80	240	
Δ“ON” Resistance Between Any 2 of 4 Switches	ΔR _{ON}	R _L =10kΩ~ (V _{DD} -V _{SS} /2) V _C =V _{DD} , V _{IS} =V _{SS} ~V _{DD}	V _{DD} =10V		10		Ω
			V _{DD} =15V		5		
CONTROL INPUTS							
Low Level Input Voltage	V _{ILC}	V _{IS} =V _{SS} and V _{DD} V _{OS} =V _{DD} and V _{SS} I _{IS} =±10μA	V _{DD} =5V		2.25	1.5	V
			V _{DD} =10V		4.5	3.0	
			V _{DD} =15V		6.75	4.0	
HIGH Level Input Voltage	V _{IHC}	V _{DD} =5V		3.5	2.75		V
		V _{DD} =10V (Note)		7.0	5.5		
		V _{DD} =15V		11.0	8.25		
Input Current	I _{IN}	V _{DD} -V _{SS} =15V, V _{DD} ≥V _{IS} ≥V _{SS} , V _{DD} ≥V _C ≥V _{SS}			±10 ⁻⁵	±0.3	μA

Note: Conditions for V_{IHC} : (a) $V_{IS}=V_{DD}$, I_{OS} =standard B series I_{OH} . (b) $V_{IS}=0V$, I_{OL} =standard B series I_{OL} .

■ **AC ELECTRICAL CHARACTERISTICS** (AC Parameters are guaranteed by DC correlated testing)

($T_A=25^\circ\text{C}$, $t_R=t_F=20\text{ ns}$ and $V_{SS}=0\text{V}$ unless otherwise)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNIT
Propagation Delay Time Signal Input to Signal Output	T_{PHL}, T_{PLH}	$V_C=V_{DD}$, $C_L=50\text{pF}$ (Figure1) $R_L=200\text{k}$	$V_{DD}=5\text{V}$ $V_{DD}=10\text{V}$ $V_{DD}=15\text{V}$	25 15 10	55 35 25	ns
Propagation Delay Time Control Input to Signal Output High Impedance to Logical Level	t_{PZH}, t_{PLZ}	$R_L=1.0\text{k}\Omega$, $C_L=50\text{pF}$ (Fig. 2, 3)	$V_{DD}=5\text{V}$ $V_{DD}=10\text{V}$ $V_{DD}=15\text{V}$		125 60 50	ns
Propagation Delay Time Control Input to Signal Output Logical Level to High Impedance		$R_L=1.0\text{k}\Omega$, $C_L=50\text{pF}$ (Fig. 2, 3)	$V_{DD}=5\text{V}$ $V_{DD}=10\text{V}$ $V_{DD}=15\text{V}$		125 60 50	ns
Sine Wave Distortion	t_{PHZ}, t_{PLZ}	$V_C=V_{DD}=5\text{V}$, $V_{SS}=-5\text{V}$ $R_L=10\text{k}\Omega$, $V_{IS}=5\text{V}_{P-P}$, $f=1\text{kHz}$, (Fig. 4)		0.1		%
Frequency Response -Switch "ON" (Frequency at -3dB)		$V_C=V_{DD}=5\text{V}$, $V_{SS}=-5\text{V}$ $R_L=1\text{k}\Omega$, $V_{IS}=5\text{V}_{P-P}$ $20\text{ Log}_{10} V_{OS}/V_{IS}$ (1kHz)-dB (Fig. 4)		40		MHz
Feedthrough - Switch "OFF" (Frequency at -50 dB)		$V_{DD}=5.0\text{V}$, $V_{CC}=V_{SS}=-5.0\text{V}$, $R_L=1\text{k}\Omega$, $V_{IS}=5.0\text{V}_{P-P}$, $20\text{Log}_{10} V_{OS}/V_{IS}=-50\text{dB}$, (Fig. 4)		1.25		MHz
Crosstalk Between Any Two Switches(Frequency at -50dB)		$V_{DD}=V_C(A)=5.0\text{V}$; $V_{SS}=V_C(B)=5.0\text{V}$, $R_L=1\text{k}\Omega$, $V_{IS}(A)=5.0\text{V}_{P-P}$, $20\text{Log}_{10} V_{OS}(B)/V_{IS}(A)=-50\text{dB}$ (Fig. 5)		0.9		MHz
Crosstalk; Control Input to Signal Output		$V_{DD}=10\text{V}$, $R_L=10\text{k}\Omega$, $R_{IN}=1.0\text{k}\Omega$, $V_{CC}=10\text{V}$ Square Wave, $C_L=50\text{pF}$ (Fig. 6)		150		mV_{p-p}
Maximum Control Input		$R_L=1.0\text{k}\Omega$, $C_L=50\text{pF}$ (Fig. 7) $V_{OS}(f)=1/2V_{OS}$ (1.0kHz)	$V_{DD}=5.0\text{V}$ $V_{DD}=10\text{V}$ $V_{DD}=15\text{V}$	6.0 8.0 8.5		MHz
Signal Input Capacitance	C_{IS}			8.0		pF
Signal Output Capacitance	C_{OS}	$V_{DD}=10\text{V}$		8.0		pF
Feedthrough Capacitance	C_{IOS}	$V_C=0\text{V}$		0.5		pF
Control Input Capacitance	C_{IN}			5.0	7.5	pF

■ SPECIAL CONSIDERATIONS

In applications where separate power sources are used to drive V_{DD} and the signal input, the V_{DD} current capability should exceed V_{DD}/R_L (R_L =effective external load of the UTC 4066 bilateral switches). This provision avoids any permanent current flow or clamp action of the V_{DD} supply when power is applied or removed from UTC 4066.

In certain applications, the external load-resistor current may include both V_{DD} and Signal-line components. To avoid drawing V_{DD} current when switch current flows into terminals 1,4,8 or 11, the voltage drop across the bidirectional switch must not exceed 0.6V at $T_A \leq 25^\circ\text{C}$, or 0.4V at $T_A > 25^\circ\text{C}$ (calculated from R_{ON} values shown).

NO V_{DD} current will flow through R_L if the switch current flows into terminals 2, 3, 9 or 10.

■ AC TEST CIRCUITS AND SWITCHING TIME WAVEFORMS




Fig.1 t_{PHL} , t_{PLH} Propagation Delay Time Signal Input to Signal Output





Fig. 2 t_{PZH} , t_{PHZ} Propagation Delay Time Control to Signal Output







Fig. 3 t_{PZL} , t_{PLZ} Propagation Delay Time Control to Signal Output



$V_C = V_{DD}$ for distortion and frequency response tests
 $V_C = V_{SS}$ for feedthrough test




Fig. 4 Sine Wave Distortion, Frequency Response and Feedthrough

■ AC TEST CIRCUITS AND SWITCHING TIME WAVEFORMS(Cont.)




Fig. 5 Crosstalk Between Any Two Switches




Fig. 6 Crosstalk: Control Input to Signal Output






Fig. 7 Maximum Control Input Frequency

■ TYPICAL PERFORMANCE CHARACTERISTICS


"ON" Resistance vs Signal Voltage for $T_A=25^\circ\text{C}$




"ON" Resistance as a Function of temperature for $V_{DD}-V_{SS}=15\text{V}$



"ON" Resistance as a Function of Temperature for $V_{DD}-V_{SS}=10\text{V}$



"ON" Resistance as a Function of Temperature for $V_{DD}-V_{SS}=15\text{V}$



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.