Power Supply Cord with Special Connector and Plug, Straight

new



Description
Power Cord,
- Protection class II, Pin temperature 70 °C, Cable

References
General Product Information

Weblinks
Approvals, RoHS, CHINA-RoHS, Mating Connectors, e-Store, Distributor-Stock-Check, Accessories

Technical Data

Dielectric Strength	> 2 kVDC between L-N > 2 kVAC between L/N-PE (1 min/50 Hz)
Allowable Operation Temp.	-25 °C to 70 °C
Degree of Protection	from front side IP 20 acc. to IEC 60529
Protection Class	Suitable for appliances with protection class 2 acc. to IEC 61140
Terminal	moulded
Material: Housing	PVC, black or grey

Config. Code
Product Configurator

5026 - R - Type - D - Length

The characters are placeholders for the correspondingly keys of selections from the key tables.
Typ steht für die Dose bzw. 2. Seite, Länge ist die Leitungslänge in mm.

5026 - **R** - Type - D - Length = cord type

cord type	Configuration key
special cord	Z
Cord definition is detailed in general product information	XXX

5026 - R - **Type** - D - Length = Cord end 2

Cord end 2
zzzz

5026 - R - Type - **D** - Length = Color

Color	Configuration key
jet black; RAL9005	A

standard color: black

5026 - R - Type - D - **Length** = Cord length

Cord length
zzzz

Cord length in mm

The specifications, descriptions and illustrations indicated in this document are based on current information. All content is subject to modifications and amendments.