
Model 5069
Breakout: BNC (Female) To .025” (,63mm) Pin Receptacles CE



FEATURES:

- ✓ Converts BNC (male) cables / connectors to .025” (,63mm) receptacles for attachment to square or round pins on test boards, etc.
- ✓ BNC connector is molded directly to the wire for pull strength durability and dust and moisture resistance.
- ✓ Black wire is connected to BNC shell, red wire to BNC center contact.

MATERIALS:

BNC: Nickel Plated Brass, Center Contact: Gold Plated Beryllium Copper
Dielectric: PTFE
Wire: 22 AWG, PVC Insulated
Pin Receptacle: Body: Gold Plated Phosphor Bronze
Insulation: ABS, color matches color of wire

RATINGS:

Operating Voltage: Hands free testing in controlled voltage environments: 500 VRMS Max.
Operating Temperature: +131°F (+55°C) Max.

ORDERING INFORMATION: Model 5069*
* Custom lengths are available, contact Pomona Product Support at: 1-800-241-2060

All dimensions are in inches. Tolerances (except noted): .xx = ±.02” (,51 mm), .xxx = ± .005” (,127 mm).
All specifications are to the latest revisions. Specifications are subject to change without notice.
Registered trademarks are the property of their respective companies.

Sales: 800-490-2361 Fax: 888-403-3360 Technical Assistance: 800-241-2060
For “Where to Buy” information, visit the Pomona web site at www.pomonaelectronics.com

Rev: 100
D1094274