

SPECIFICATION SHEET**JFW MODEL 50BR-104****BENCH TOP ROTARY ATTENUATOR**

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	DC-2700 MHz
Impedance	50 Ohms nominal
Attenuation Range	0-80 dB in 1 dB steps
VSWR	1.5:1 maximum DC-1000 MHz 1.8:1 maximum 1000-2700 MHz
Attenuation Accuracy	± 0.5 dB (1 dB steps) ± 0.5 dB or 3% (10 dB steps)
Insertion Loss	1.7 dB maximum
RF Input Power	2 Watts average
Direction of Rotation	Attenuation increases in a Clockwise direction
Indexing	30 degrees with stops at minimum and maximum
RF Connector	BNC, N, SMA or TNC female
Operating Temperature Range	-20°C to +85°C
Lifetime	500,000 attenuation steps (each knob)
Physical Size	See outline drawing 092-5942

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	10/15/2008		TRS 10/15/2008	23479	11/26/2013	C	TRS 11/27/2013
20173	05/26/2011	A	TRS 05/26/2011	28157	10/05/2017	D	TRS 10/05/2017
21179	01/26/2012	B	TRS 01/26/2012				