

SPECIFICATION SHEET**JFW MODEL 50S-1463****1P2T REFLECTIVE SOLID STATE RF SWITCH**

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	10-1000 MHz
Configuration	1P2T Reflective
Impedance	50 Ohms nominal
VSWR	1.4:1 maximum
Insertion Loss	0.50 dB maximum 10-500 MHz 0.75 dB maximum 500-1000 MHz
Isolation	50 dB minimum 10-500 MHz 40 dB minimum 500-1000 MHz
Switching Speed	40 microseconds (50% TTL to 10% or 90% RF)
RF Input Power	30 Watts average Cold switch 30 Watts average Hot switch
Control (1 line)	TTL "Low" Common to J1 TTL "High" Common to J2
DC Supply	+15 Vdc @ 250 mA and +5 Vdc @ 40 mA
RF Connector	BNC, SMA, TNC or N female
Operating Temperature Range	-20°C to +70°C
Storage Temperature Range	-55°C to +85°C
Physical Size	See outline drawing 092-3022 (N) 092-5245 (SMA)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	01/30/2006		BAC 01/30/2006				
28062	08/30/2017	A	BAC 08/30/2017				