

**SPECIFICATION SHEET****JFW MODEL 50S-1773+XX****1P4T NORMALLY OPENED REFLECTIVE  
ELECTROMECHANICAL RF SWITCH**

JFW Industries, Inc.  
Phone: 317-887-1340  
sales@jfwindustries.com  
www.jfwindustries.com

|                    |                                                                                                                                                                                                                                                                                                   |
|--------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Frequency Range    | DC-40 GHz                                                                                                                                                                                                                                                                                         |
| Configuration      | 1P4T Normally Open Reflective                                                                                                                                                                                                                                                                     |
| Impedance          | 50 Ohms nominal                                                                                                                                                                                                                                                                                   |
| VSWR               | 1.3:1 maximum DC-6 GHz<br>1.4:1 maximum 6-12 GHz<br>1.5:1 maximum 12-18 GHz<br>1.7:1 maximum 18-26.5 GHz<br>2.0:1 maximum 26.5-40 GHz                                                                                                                                                             |
| Insertion Loss     | 0.3 dB maximum DC-6 GHz<br>0.4 dB maximum 6-12 GHz<br>0.5 dB maximum 12-18 GHz<br>0.7 dB maximum 18-26.5 GHz<br>1.0 dB maximum 26.5-40 GHz                                                                                                                                                        |
| Isolation          | 70 dB minimum DC-6 GHz<br>60 dB minimum 6-12 GHz<br>60 dB minimum 12-18 GHz<br>55 dB minimum 18-26.5 GHz<br>50 dB minimum 26.5-40 GHz                                                                                                                                                             |
| Switching Speed    | 20 milliseconds                                                                                                                                                                                                                                                                                   |
| RF Input Power     | 40 Watts average DC-6 GHz<br>30 Watts average 6-12 GHz<br>25 Watts average 12-18 GHz<br>15 Watts average 18-26.5 GHz<br>8 Watts average 26.5-40 GHz                                                                                                                                               |
| Control (4 lines)  | +XX is either +12, +15, +24 or +28:<br>-----<br>+12 Vdc @ 325 mA nominal (11-14 Vdc)<br>+15 Vdc @ 280 mA nominal (13-17 Vdc)<br>+24 Vdc @ 190 mA nominal (20-28 Vdc)<br>+28 Vdc @ 160 mA nominal (24-32 Vdc)<br>on control line corresponding to desired port<br>(Only one active port at a time) |
| Lifetime           | 1 million cycles minimum                                                                                                                                                                                                                                                                          |
| Weight             | 4 oz. Nominal                                                                                                                                                                                                                                                                                     |
| DC Connector       | Solder Terminals                                                                                                                                                                                                                                                                                  |
| RF Connector       | 2.9mm female                                                                                                                                                                                                                                                                                      |
| Temperature Ranges | -25°C to +65°C (operating)<br>-55°C to +85°C (storage)                                                                                                                                                                                                                                            |

**--CONTINUED--**

**SPECIFICATION SHEET**

**JFW MODEL 50S-1773+XX**

**1P4T NORMALLY OPENED REFLECTIVE  
ELECTROMECHANICAL RF SWITCH**

JFW Industries, Inc.  
Phone: 317-887-1340  
sales@jfwindustries.com  
www.jfwindustries.com

Physical Size

See outline drawing 092-8604



| ECR/ECN # | DATE       | REV | APPR / DATE    | ECR/ECN # | DATE | REV | APPR / DATE |
|-----------|------------|-----|----------------|-----------|------|-----|-------------|
|           | 04/04/2016 |     | TRS 04/04/2016 |           |      |     |             |