

SPECIFICATION SHEET**JFW MODEL 50T-376****TERMINATION**

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range DC-4000 MHz

Impedance 50 Ohms nominal

VSWR 1.10:1 maximum
1.04:1 typical

RF Input Power 2 Watts average

Peak Power 1000 Watts

RF Connector BNC, N, SMA, TNC or 4.1/9.5
(male or female)

Operating Temperature Range -20°C to +85°C

Outline Drawing Numbers

092-4072	(50T-376 SMA F)
092-4269	(50T-376 SMA M)
092-7065	(50T-376 N F)
092-4208	(50T-376 N M)
092-7064	(50T-376 TNC F)
092-4444	(50T-376 TNC M)
092-7066	(50T-376 BNC F)
092-6043	(50T-376 BNC M)
092-8688	(50T-376 4.1/9.5 M)
092-8689	(50T-376 4.1/9.5 F)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
4324	08/04/2003	A	CLV 08/04/2003	4542	03/30/2004	D	CLV 03/30/2004
4442	01/27/2004	B	SL 01/27/2004	20493	08/23/2011	E	TRS 08/24/2011
4470	02/11/2004	C	CLV 02/11/2004	26961	08/17/2016	F	TRS 08/17/2016