
engineered to light up your design
www.vcclite.com
1.800.522.5546

5310F Series T-1 LED Circuit Board Indicator

Description and Features



Features

- Blockmounting,heightandspacingalignmentsaves assemblycostandtime.
- Standoffspreventfluxentrapment.
- Press-inmountingpinsecuresassemblytoPCboard while soldering.

Housing: BlackNylon,UL94V-O

Alternate LEDs are available in this package as standard variations.

Refer to “Mounting Hole Pattern 4.pdf”

Electro-Optical Characteristics and Ratings

Part Number	Color	Typ. Intensity (mcd)	Rated Current (mA)	Continuous Forward Current Max. (mA)	Forward Voltage Typ. (V)	Forward Voltage Max. (V)	Reverse Break-down Voltage Min. (V)	Peak Wavelength (nm)	DIM A (inches)
5310F1	Red	10	10	30	2.0	3.0	5	650	.580
5310F3	Amber	7	10	30	2.2	3.0	5	603	.580
5310F5	Green	16	10	30	2.2	3.0	5	562	.580
5310F7	Yellow	6.3	10	30	2.1	3.0	5	585	.580
5312F1	Red	10	10	30	2.0	3.0	5	650	.810
5312F5	Green	7	10	30	2.2	3.0	5	562	.810
5312F7	Yellow	6.3	10	30	2.1	3.0	5	585	.810
5315F1	Red	10	10	30	2.0	3.0	5	650	.550
5315F5	Green	7	10	30	2.2	3.0	5	562	.550
5315F7	Yellow	6.3	10	30	2.1	3.0	5	585	.550

CML and Chicago Miniature Lamp are registered trademarks of Visual Communications Company, LLC.