586 Series
Single Chip BASED LED
T 1 3/4 MIDGET FLANGE



(Center Contact Negative)

FEATURES / BENEFITS

- RoHS Compliant
- High brightness with low current draw - uses up to 90% less energy than incandescent
- Long life - up to 100K hours
- No heat generated
- Mounts directly into industry-standard socket
- Resistant to shock and vibration
- AlInGaP and InGaN technology
- Super bright single chip design
- Colors include red, green, yellow, blue and white

Dialight's line of based LED lamps is designed to directly replace many popular subminiature and miniature incandescent lamps. The benefits of LED technology over incandescent are significant: They offer long life, are shock resistant, withstand vibration and provide energy conservation.

SPECIFICATIONS



Measurements are typical
Dimensions are inches [mm]

- Operating Voltages: 6, 14, and 28 VDC
- Operating temperature: -40ºC to +80ºC
- Storage temperature: -40ºC to +100ºC
- Replaces incandescent lamp numbers: 327, 328, 330, 345,349, 350, 376, 377, 380, 381, 382, 385, 387, and 7341*

* **See Dialight's Incandescent lamp/based LED cross reference for a complete listing.**

CONSIDERATIONS

- Since lens caps act as filters for the light emitted from the based LED, it is important to match the emitting color of the LED. If not matched properly, the overall light output may be substantially reduced. Dialight recommends using transparent lenses, which will optimize the light output.
- Although these lamps can be operated at a lower voltage, which will increase the life, the intensity will be reduced.
- Operation of the based LED at a higher voltage should not exceed 10% above the recommended voltage.
- Dialight does not recommend that based LED lamps be used in neon sockets.

Dialight reserves the right to make changes at any time in order to supply the best product possible.

A4703 UL REGISTERED FIRM ISO 9001
Dialight Corporation

RoHS COMPLIANT

Dialight Corporation
1501 Route 34 South • Farmingdale, NJ 07727 USA
Tel: (1) 732-919-3119 • Fax: (1) 732-751-5778 • www.dialight.com

586 Series
Single Chip BASED LED
T 1 3/4 MIDGET FLANGE

T 1 3/4 MIDGET FLANGE - POLARIZED

PART NUMBER	COLOR	PEAK WAVELENGTH (nm)	VOLTAGE (VDC)	CURRENT TYP.-(mA)	INTENSITY TYP.-(mcd)	RoHS COMPLIANT
586-1101-001F	Red	639	6	10	775	✔
586-1102-001F	Green	520	6	10	600	✔
586-1103-001F	Yellow	592	6	10	775	✔
586-1105-001F	Blue	467	6	10	210	✔
586-1106-001F	White	*	6	10	460	✔
586-1101-003F	Red	639	14	10	775	✔
586-1102-003F	Green	520	14	10	600	✔
586-1103-003F	Yellow	592	14	10	775	✔
586-1105-003F	Blue	467	14	10	210	✔
586-1106-003F	White	*	14	10	460	✔
586-1101-005F	Red	639	28	10	775	✔
586-1102-005F	Green	520	28	10	600	✔
586-1103-005F	Yellow	592	28	10	775	✔
586-1105-005F	Blue	467	28	10	210	✔
586-1106-005F	White	*	28	10	460	✔

*** Color coordinates: x = .320, y = .320**

Based LEDs *SELECTION*

With the technological advancements in Light Emitting Diodes (LEDs) brightness can now rival the incandescent lamp when used in similar packages. These advancements have created a new type of product called the based LED - an LED with the functionality of an incandescent bulb.

The following styles are currently available in red, green, yellow, blue and white:

- ▲ T 1 3/4 Midget Flange
- ▲ T 1 3/4 Bi-Pin
- ▲ T 1 3/4 Wedge (T5)
- ▲ T 2 Telephone Slide
- ▲ T 3 1/4 Miniature Bayonet (BA9S)
- ▲ T 3 1/4 Miniature Screw (E10)
- ▲ T 3 1/4 Wedge (T10)
- ▲ 15mm SC Bayonet (BA15S)

Dialight's line of based LEDs continues to grow.

Please visit our website for more information.

www.dialight.com

Dialight reserves the right to make changes at any time in order to supply the best product possible.

A4703 UL REGISTERED FIRM Dialight Corporation ISO 9001

RoHS COMPLIANT

Dialight Corporation
1501 Route 34 South • Farmingdale, NJ 07727 USA
Tel: (1) 732-919-3119 • Fax: (1) 732-751-5778 • www.dialight.com