



- ① CONTACTS ARE LATCHED INTO THE PRELOAD WINDOWS
- ② USE WITH #22-#26 AWG WIRE SIZE, .054/.030 INSULATION DIAMETER, .015 MAXIMUM INSULATION THICKNESS
- ③ THE DIMENSION APPLIES WITH THE FORWARD PRELOAD STOP IN CONTACT WITH THE HOUSING SURFACE
- ④ POINT OF MEASUREMENT FOR PLATING THICKNESS
- 5 FOR STRIP ASSEMBLIES SEE PART NUMBER 103946
- ⑥ MATERIAL- HOUSING: FLAME RETARDANT THERMOPLASTIC, COLOR: BLACK
PINS: PHOS. BRONZE
- ⑦ FINISH- PINS: .000030 GOLD IN THE CONTACT AREA,
.000050-.000100 BRIGHT TIN-LEAD ON THE TERMINATION AREA,
OVER .000050 NICKEL.
- ⑧ FINISH- PINS: .000030 GOLD IN THE CONTACT AREA,
.000050-.000100 MATTE TIN ON THE TERMINATION AREA,
OVER .000050 NICKEL.
- ⑨ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI