PCM 175/175 XG

Sample image

Order symbol: PCM 175/175 XG

Product nbr: 6016343

Description: Enclosure. PC


Remarks: Opaque cover

EAN: 6418074011831

El. number:

- Finland:
- Denmark:
- Sweden:

Including: Base with TPE gasket. screws for mounting plate/DIN-rail and cover with polyamide cover screws.



Dimensions:	**Height**	**Width**	**Depth**
mm:	180	180	175
inch:	7.09	7.09	6.89

Materials:

Material:	Polycarbonate
Base colour:	RAL 7035 -light grey
Cover colour:	RAL 7035 -light grey
Gasket material:	Polyurethane

Temperatures:

Temperature °C (short term)::	-40 … 120
Temperature °C (continuous):	-40 … 80
Temperature °F (short term):	-40 … 250

Accessories:

MIV 175	Back Panel (Galvanized steel). for enclosures: (148 x 148 x 1)
FP A 175/180	Front panel (Aluminum). for enclosures: (170 x 162 x 1)
HFP 180	Front panel hinge series
MIN 15	DIN-15 Mounting rail. for enclosures: (150 x 15 x 1)
MIV 15	DIN-35 Mounting rail. for enclosures: (150 x 35 x 1)
FP 22046	Mounting foot kit (4 pcs)

Rating:

Ingress protection (EN 60529):	IP66; IP67;
Impact Resistance (EN 62262):	IK08;
Electrical insulation:	Totally insulated

Temperature °F (continuous):	-40 … 175

Halogen free (DIN/VDE 0472, Part 815):	1
UV resistance:	UL 508
Flammability Rating:	UL 746C 5"
Glow Wire Test (IEC 695-2-1) °C:	960 °C
NEMA Class	

Certificates:

Certificate FI 40847

© Fibox Oy, Data subject to change without notice (printed: 01.09.2022)