Pomona®

Model 6253
50 Ohm Cable Assembly With Insulated Push-On BNC Connectors



FEATURES:

- Provides quick and easy connect/disconnect
- Reliable Push-On snap lock fit provides excellent connector retention
- Mates to all BNC female connectors
- Strain relief prolongs cable life
- Center pin is gold plated for low contact resistance
- BNC body is nickel plated for tarnish resistance
- BNC shell is insulated
- Excellent for hard to access back panels
- Easier push-on insertion method compared to push and twist bayonet BNC connectors

MATERIALS:

BNC Connector: Body – Brass, Nickel Plated
Center Pin – Brass, Gold Plated
Insulation – Thermoplastic, Color: Blue
Dielectric: PTFE
Strain Relief: PVC, Color: Black
Cable: RG58C/U – Cap pF/ft.: 30.8, O.D. 0.195" (4.95 mm), Color: Black

RATINGS:

Operating Temperature: +50°C (+122°F) Max
Operating Voltage: 500 VRMS
Cable and Connector Impedance: 50 Ohms Nom.

ORDERING INFORMATION: Model 6253-C-XX
XX = Cable length in inches, standard lengths: 36" (91.44 cm)
Additional lengths can be quoted upon request.

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (,127 mm).
All specifications are to the latest revisions. Specifications are subject to change without notice.
Registered trademarks are the property of their respective companies. Made in USA

Sales: 800-490-2361 Fax: 425-446-5844
Technical Support: technicalsupport@pomonatest.com

www.pomonaelectronics.com