

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
© COPYRIGHT By – ALL RIGHTS RESERVED.


LOC	DIST
CM	00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	AC	REVISED PER ECO-11-014381	110CT11	KH	SM







RECOMMENDED MOUNTING HOLE PATTERN
FOR 1.60 [.063] THICK P.C. BOARD 2

1. POST TO WITHSTAND 13 NEWTONS (3 LBS) MINIMUM AXIAL FORCE IN BOTH DIRECTIONS SHOWN WITHOUT DISLODGING.
2. TOLERANCES APPLY TO SOLDER SIDE OF BOARD.
3. MEASURED ~~A~~ –A–
4. PLASTIC FLASH PERMITTED IN THIS AREA.
5. PARTS COMPLY WITH AMP SOLDERABILITY SPEC. NO. 109–11–2.
6. ONE HOLE MAY BE UNDERSIZED 0.81–0.89 [.032–.035] DIA. FOR ASSEMBLY RETENTION DURING WAVE SOLDERING.
7. MATERIAL: HEADER–THERMOPLASTIC POLYESTER
   94V–0 (NATURAL)
   POST–COPPER ALLOY
   FINISH–USE PLATING NOTES 13 & 14 FOR –2 THRU –28
   AND NOTES 13 & 15 FOR –32 THRU –58
8. COORDINATE DIMENSION APPLIES FROM CENTER OF ACTUAL FEATURE.
9. PLASTIC BURRS CAUSED BY CUT–OFF TOOLING ARE PERMITTED WITHIN THE MAXIMUM TOLERANCE ENVELOPE.
10. POSTS TO BE MEASURED WHEN STRIP IS HELD FLAT.
11. POST MUST WITHSTAND TWO 90° BENDS AGAINST EXTRUSION WITHOUT BREAKING.
12. DIMENSION SHOULD BE 3.30 [.130] WHEN MATING WITH A MTA–100 CONNECTOR ASSEMBLY OR A CST–100 CONNECTOR ASSEMBLY.
13. PLATING: GOLD PLATE AREA, 0.00038 [.000015] GOLD OR 0.00008[.000003] MIN GOLD FLASH OVER 0.00030 [.000012] PALLADIUM NICKEL, PER TE CONNECTIVITY'S DISCRETION, ALL SIDES, OVER NICKEL UNDERPLATE, 0.00127 [.000050] MIN, ALL SIDES AND ENTIRE LENGTH OF POST.
14. PLATING: BRIGHT TIN/LEAD (93/7) PLATE AREA, 0.00381–0.00889 [.000150–.000350] THICK, ALL FOUR SIDES 3.56 [.140] MINIMUM.
15. PLATING: MATTE TIN PLATE AREA, 0.00381–0.00889 [.000150–.000350] THICK, ALL FOUR SIDES 3.56 [.140] MINIMUM.
16. OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

LEAD FREE				CONTAINS LEAD			
DIM (L)	NO.OF POSN	ASSEMBLY		DIM (L)	NO.OF POSN	ASSEMBLY	
71.12 [2.800]	28	5–641124–8		71.12 [2.800]	28	~~2–641124–8~~	16
68.58 [2.700]	27	5–641124–7		68.58 [2.700]	27	~~2–641124–7~~	16
66.04 [2.600]	26	5–641124–6		66.04 [2.600]	26	~~2–641124–6~~	16
63.50 [2.500]	25	5–641124–5		63.50 [2.500]	25	~~2–641124–5~~	16
60.96 [2.400]	24	5–641124–4		60.96 [2.400]	24	2–641124–4	
58.42 [2.300]	23	5–641124–3		58.42 [2.300]	23	~~2–641124–3~~	16
55.88 [2.200]	22	5–641124–2		55.88 [2.200]	22	~~2–641124–2~~	16
53.34 [2.100]	21	5–641124–1		53.34 [2.100]	21	~~2–641124–1~~	16
50.80 [2.000]	20	5–641124–0		50.80 [2.000]	20	2–641124–0	
48.26 [1.900]	19	4–641124–9		48.26 [1.900]	19	~~1–641124–9~~	16
45.72 [1.800]	18	4–641124–8		45.72 [1.800]	18	~~1–641124–8~~	16
43.18 [1.700]	17	4–641124–7		43.18 [1.700]	17	~~1–641124–7~~	16
40.64 [1.600]	16	4–641124–6		40.64 [1.600]	16	~~1–641124–6~~	16
38.10 [1.500]	15	4–641124–5		38.10 [1.500]	15	~~1–641124–5~~	16
35.56 [1.400]	14	4–641124–4		35.56 [1.400]	14	~~1–641124–4~~	16
33.02 [1.300]	13	4–641124–3		33.02 [1.300]	13	~~1–641124–3~~	16
30.48 [1.200]	12	4–641124–2		30.48 [1.200]	12	~~1–641124–2~~	16
27.94 [1.100]	11	4–641124–1		27.94 [1.100]	11	~~1–641124–1~~	16
25.40 [1.000]	10	4–641124–0		25.40 [1.000]	10	~~1–641124–0~~	16
22.86 [.900]	9	3–641124–9		22.86 [.900]	9	~~641124–9~~	16
20.32 [.800]	8	3–641124–8		20.32 [.800]	8	~~641124–8~~	16
17.78 [.700]	7	3–641124–7		17.78 [.700]	7	~~641124–7~~	16
15.24 [.600]	6	3–641124–6		15.24 [.600]	6	641124–6	
12.70 [.500]	5	3–641124–5		12.70 [.500]	5	641124–5	
10.16 [.400]	4	3–641124–4		10.16 [.400]	4	641124–4	
7.62 [.300]	3	3–641124–3		7.62 [.300]	3	~~641124–3~~	16
5.08 [.200]	2	3–641124–2		5.08 [.200]	2	~~641124–2~~	16

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ±
1 PLC ±
2 PLC ± 0.13 [.005]
3 PLC ±
4 PLC ±
ANGLES ±

MATERIAL 7 FINISH 7

METRIC

DWN	S. HOOVER	26–JAN–2005
CHK	D. BOSSI	26–JAN–2005
APVD	D. BOSSI	26–JAN–2005
PRODUCT SPEC		
APPLICATION SPEC		
WEIGHT		

TE Connectivity

NAME: MTA–100 HEADER ASSEMBLY, POLARIZED, NOTCHED, .025 SQUARE STRAIGHT POST, .000015 GOLD PLATED

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A1	00779	C–641124	

CUSTOMER DRAWING | SCALE 8:1 | SHEET 1 OF 1 | REV AC