
Pomona®

Model 6372, 6559, 6560, 6561 Male Mini-Connector "Do-It-Yourself"



FEATURES:

- Molded in contacts assure precision alignment
- Matching thermocouple alloys reduce EMF
- Channel design isolates wires for clear, strong signals
- Make your own extension cables

MATERIALS:

Insulator – Hytrel 4776.

MODEL NUMBER	CALIBRATION	COLOR
6372	K	Yellow
6559	J	Black
6560	E	Violet
6561	T	Blue

RATINGS:

Maximum Ambient Temperature - 400°F. (205°C.).
Maximum Wire Size – 20AWG (solid), 22 AWG (stranded)

ORDERING INFORMATION: Model 6372, 6559, 6560, 6561
Note: For low voltage environments do not exceed 30VAC/60VDC.

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (,51 mm), .xxx = ± .005" (,127 mm).
All specifications are to the latest revisions. Specifications are subject to change without notice.
Registered trademarks are the property of their respective companies. Made in USA

Sales:800-490-2361 Fax: 888-403-3360
Technical Assistance: 800-241-2060

Pomona*ACCESS* **90739** (800) 444-6785 or (425) 446-6010
More drawings available at www.pomonaelectronics.com

Pomona®

Model 6372, 6559, 6560, 6561 Male Mini-Connector "Do-It-Yourself"

ASSEMBLY INSTRUCTIONS

1. Using a flat tip screwdriver, remove lid from connector.

2. Cut back extension wire jacket (if applicable) 5/8", strip back individual wires ¼".

3. Remove the elastomer strain relief from the connector. Insert wires into the strain relief until flush with the extension wire outer jacket (5/8").

4. Loosen the two wire terminal screws (Approximately 3 ½ turns counter clockwise) using a small flat tip screwdriver.

5. Insert the stripped Red* wire under the (-) terminal screw, and the remaining wire under the (+) terminal screw. Tighten down the two terminal screws.

6. Install the lid and tighten down the lid screw.

*Color may vary outside of the USA.

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (,51 mm), .xxx = ± .005" (,127 mm).
All specifications are to the latest revisions. Specifications are subject to change without notice.
Registered trademarks are the property of their respective companies. Made in USA

Sales:800-490-2361 Fax: 888-403-3360
Technical Assistance: 800-241-2060