
Fax-on-Demand: 86-22-24207687 / 25-471-1126
Tel-on-Demand: 86-22-24207688 / 25-471-1136
Before ordering check with
factory for most current data

672-3866 / 672-3866A

RF & MICROWAVE TRANSISTORS
LOW POWER TRANSISTORS

Features

- Silicon NPN, To-39 packaged VHF/UHF Transistor
- Specified 400 MHz, 28Vdc Characteristics
  - Output Power = 1.0 Watt
  - Minimum Gain = 10 dB
  - Efficiency = 45%
- 800 MHz Current-Gain Bandwidth Product





1. Emitter
2. Base
3. Collector

TO-39

DESCRIPTION:

Silicon NPN transistor, designed for VHF and UHF equipment. Applications include amplifier; pre-driver, driver, and output stages. Also suitable for oscillator and frequency-multiplier functions.

ABSOLUTE MAXIMUM RATINGS (Tcase = 25°C)

Symbol	Parameter	Value	Unit
V_{CEO}	Collector-Emitter	30	Vdc
V_{CBO}	Collector-Base Voltage	55	Vdc
V_{EBO}	Emitter-Base Voltage	3.5	Vdc
I_C	Collector Current	400	mA

Thermal Data

P_D	Total Device Dissipation Derate above 25°C	5.0 28.6	Watts mW/ °C

Fax-on-Demand: 86-22-24207687 / 25-471-1126
Tel-on-Demand: 86-22-24207688 / 25-471-1136
Before ordering check with
factory for most current data

672-3866 / 672-3866A
RF & MICROWAVE TRANSISTORS
LOW POWER TRANSISTORS

ELECTRICAL SPECIFICATIONS (Tcase = 25°C)

STATIC

(off)

Symbol	Test Conditions	Value			
		Min.	Typ.	Max.	Unit
BVCER	Collector-Emitter Breakdown Voltage (IC = 5.0 mAdc, RBE = 10 ohms)	55	-	-	Vdc
BVCEO	Collector-Emitter Sustaining Voltage (IC=5.0 mAdc, IB=0)	30	-	-	Vdc
BVCBO	Collector-Base Breakdown Voltage (IE = 0, IC = 0.1 mAdc)	55	-	-	Vdc
BVEBO	Emitter-Base Breakdown Voltage (IE = 0.1 mAdc, IC = 0)	3.5	-	-	Vdc
ICEO	Collector Cutoff Current (VCE = 28 Vdc, IB = 0)	-	-	20	µA
ICEX	Collector Cutoff Current (VCE = 55 Vdc, VBE = 1.5 Vdc)	-	-	100	µA

(on)

HFE	DC Current Gain (IC = 360 mAdc, VCE = 5.0 Vdc) Both (IC = 50 mAdc, VCE = 5.0 Vdc) 672-3866 (IC = 50 mAdc, VCE = 5.0 Vdc) 672-3866A	 5.0 10 25	 - - -	 - 200 200	 - - -
VCE(sat)	Collector-Emitter Saturation Voltage (IC = 100 mAdc, IB = 20 mAdc)	-	-	1.0	Vdc

DYNAMIC

Symbol	Test Conditions		Value			
			Min.	Typ.	Max.	Unit
f_T	Current-Gain - Bandwidth Product (IC = 50 mAdc, VCE = 15 Vdc, f = 200 MHz)	2N3866 2N3866A	500 800	800 -	- -	MHz
COB	Output Capacitance (VCB = 30 Vdc, IE = 0, f = 1.0 MHz)		-	2.8	3.5	pF

FUNCTIONAL

Symbol	Test Conditions		Value			
			Min.	Typ.	Max.	Unit
G_{PE}	Power Gain	Test Circuit-Figure 1 Pin = 0.1 W, VCE = 28Vdc f = 400 MHz, TC = 25 C	10	-	-	dB
Pout	Output Power	Test Circuit-Figure 1 Pin = 0.1 W, VCE = 28Vdc f = 400 MHz, TC = 25 C	1.0	-	-	Watts
η_C	Collector Efficiency	Test Circuit-Figure 1 Pin = 0.1 W, VCE = 28Vdc f = 400 MHz, TC = 25 C	45	-	-	%




Figure 1 - 400 MHz RF AMPLIFIER CIRCUIT FOR G_{PE}, P_{OUT}, AND EFFICIENCY SPECIFICATIONS.

L_1: 2 TURNS No. 18 wire, ¼" ID, 1/8" long

L_s: 2 ¾TURNS No. 18 wire, ¼" ID, 3/16" long

Capacitor values in pF unless otherwise indicated.

Tuning capacitors are air variable

.

Fax-on-Demand: 86-22-24207687 / 25-471-1126
Tel-on-Demand: 86-22-24207688 / 25-471-1136
Before ordering check with
factory for most current data

672-3866 / 672-3866A

RF & MICROWAVE TRANSISTORS
LOW POWER TRANSISTORS

RF Low Power PA, LNA, and General Purpose Discrete Selector Guide


Package	Device	Type	GPE Freq (MHz)	Pout	GPE (dB)	Efficiency (%)	GPE VCC	BVCEO	IC max (mA)
SO-8	672-4427, R2	NPN	175	0.15	18	60	12	20	400
TO-39	672-4427	NPN	175	1	10	50	12	20	400
POWER MACRO	672-553	NPN	175	1.5	11.5	60	12.5	16	500
POWER MACRO	672-553T	NPN	175	1.5	11.5	50	12.5	16	500
TO-39	672-607	NPN	175	1.75	11.5	50	12.5	16	330
TO-39	672-6255	NPN	175	3	7.8	50	12.5	18	1000
TO-72	672-5179	NPN	200		20		6	12	50
MACRO X	672-559	NPN	512	0.5	10	65	7.5	16	150
MACRO X	672-559	NPN	512	0.5	13	60	12.5	16	150
TO-39	672-3866A	NPN	400	1	10	45	28	30	400
SO-8	672-3866, R1, R2	NPN	400	1	10	45	28	30	400
POWER MACRO	672-555	NPN	470	1.5	11	50	12.5	16	400
POWER MACRO	672-555T	NPN	470	1.5	11	50	12.5	16	400
MACRO X	672-559	NPN	870	0.5	6.5	70	7.5	16	150
MACRO X	672-559	NPN	870	0.5	9.5	65	12.5	16	150
SO-8	672-8372,R1,R2	NPN	870	0.75	8	55	12.5	16	200
POWER MACRO	672-557	NPN	870	1.5	8	55	12.5	16	400
POWER MACRO	672-557T	NPN	870	1.5	8	55	12.5	16	400

RF (Low Power PA / General Purpose) Selection


Package	Device	Type	Freq (MHz)	NF (dB)	NF IC (mA)	NF VCE	GNF (dB)	Gu Max (dB)	Ftau (MHz)	Ccb(pF)	BVCEO	IC max (mA)
TO-39	672-5109	NPN	200	3	10	15		12	1200	3.5	20	400
TO-39	672-5943C	NPN	200	3.4	30	15		11.4	1000		30	400
SO-8	672-5943, R1, R2	NPN	200	3.4	30	15		15	1300		30	400
TO-72	672-5179	NPN	200	4.5	10	6		17	900	1	15	50
TO-72	672-2857	NPN	300	5.5	50	6		13	1600	1	15	40
TO-39	672-517	NPN	300	7.5	50	15		5.5	4600	3	25	150
TO-72	672-904	NPN	450	1.5	5	6		11	4000	1	15	30
TO-72	672-6304	NPN	450	5	2	5		14	1400	1	15	50
MACRO T	672-R91	NPN	500	1.9	2	5	11	16.5	5000	1	12	3
MACRO T	672-R96	NPN	500	2	10	10		14.5	500	2.6	15	100
SO-8	672-5812, R1, R2	NPN	500	2	50	10	15.5	17.8	5000		15	200
MACRO X	672-581A	NPN	500	2	50	10	14	15	5000		15	200
Macro	672-90	NPN	500	2.4	2	10	15	18	5000	1	15	30
TO-72	672-90	NPN	500	2.5	2	5		20	1300		15	50
TO-72	672-914	NPN	500	2.5	5	10		15	4500		12	40
MACRO X	672-581	NPN	500	2.5	50	10	15	17.8	5000		16	200
TO-39	672-586	NPN	500	3	90	15	11	14.5	4500	2.2	17	200
MACRO X	672-951	NPN	1000	1.3	5	6	14	17	8000	0.45	10	100
MACRO X	672-571	NPN	1000	1.5	10	6	10		8000	1	10	70
MACRO T	672-91	NPN	1000	2.5	2	5	8	11	5000	1	12	35
MACRO T	672-90	NPN	1000	3	2	10	10	12.5	5000	1	15	30
TO-39	672-545	PNP						14	1400	2	70	400
TO-39	672-544	NPN						13.5	1500		70	400

RF (LNA / General Purpose) Selection Guide


Low Cost RF Plastic Package Options




Macro T



Macro X



Power




SO-8

Fax-on-Demand: 86-22-24207687 / 25-471-1126
Tel-on-Demand: 86-22-24207688 / 25-471-1136
Before ordering check with
factory for most current data

672-3866 / 672-3866A
RF & MICROWAVE TRANSISTORS
LOW POWER TRANSISTORS

PACKAGE STYLE M246



	MINIMUM INCHES/MM	MAXIMUM INCHES/MM		MINIMUM INCHES/MM	MAXIMUM INCHES/MM
A	.350/8,89	.370/9,40	J	.095/2,41	.105/2,67
B	.315/8,00	.335/8,51	K	.095/2,41	.105/2,67
C	.240/6,10	.260/6,60	L	.190/4,83	.210/5,33
D	.015/0,38	.045/1,14			
E	.500/12,70				
F	.016/0,41	.019/0,48			
G	.029/0,74	.040/1,02			
H	.028/0,71	.034/0,86			