






REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	B	REVISED PER ECR-16-003314	18JUL2016	BW	GJ



POS.	DIM.A	DIM.B
3*5	33.70	31.30
3*4	27.70	25.30
3*3	21.70	19.30



- 1 MATERIAL:
LEVEL A:PA6 GLASS FILLED,COMPLY WITH GLOW WIRE REQUIREMENTS FOR PARTS OF NON-METALLIC MATERIAL SUPPORTING A CURRENT-CARRYING CONNECTION DETAILED IN IEC 60335-1, SECTION 30 (GWT),UL 94V-0
LEVEL B:PBT GLASS FILLED,HOT WIRE IGNITION (HWI) VERSION ARE MOLDED IN A RESIN THAT COMPLIES WITH TE HOT WIRE IGNITION TEST 109-32026 AND ARE RECOMMENDED FOR USE WITH HWI HOUSINGS THAT ALSO COMPLY, UL 94V-0.

- 2 MATERIAL MARK:
LEVEL A: GWT,LEVEL B:HWT.







- 3 APPLICABLE CONTACT P/N
TAB CONTACT:1971238/1971780/82/84/86/88-*

- 4 MATING CONN. P/N
PLUG HSG: *-2232357- *
TPA DOUBLE ROW: *-1971778- *; TPA SINGLE ROW: *-1971777- *.

- 6 THIS PRODUCT HAS NOT COMPLETED VALIDATION TESTING.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN TOMMY WU 26MAR2013	TE Connectivity	
DIMENSIONS:		CHK HAPYE WU 26MAR2013		
mm	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD YUZHONG MAO 26MAR2013	NAME CAP HOUSING,FREE HANGING,TRIPLE ROW POWER TRIPLE LOCK	
	0 PLC	±	PRODUCT SPEC	
	1 PLC	±0.35	108-106118	
	2 PLC	±0.25	APPLICATION SPEC	
	3 PLC	±	114-106118	
	4 PLC	±	WEIGHT	
	ANGLES	±	100779	
MATERIAL		FINISH	Customer Drawing	
-	-	-	SCALE	
-	-	-	SHEET 1 OF 2	
			REV B	

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
-	-	SEE SHEET 1	-	-	-









3*5	LEVEL A	DARK GREY	KEY A	5-2232360-7
		BROWN	KEY B	6-2232360-7
		GREEN	KEY C	7-2232360-7
		ORANGE	KEY D	8-2232360-7
3*4	LEVEL A	BLACK	KEY A	1-2232360-5
		DARK GREY	KEY A	5-2232360-4
		BROWN	KEY B	6-2232360-4
		GREEN	KEY C	7-2232360-4
	LEVEL B	ORANGE	KEY D	8-2232360-4
BLACK		KEY A	1-2232360-4	
3*3	LEVEL A	DARK GREY	KEY A	5-2232360-3
		BROWN	KEY B	6-2232360-3
		GREEN	KEY C	7-2232360-3
		ORANGE	KEY D	8-2232360-3
POS.	MATERIAL	COLOR	KEY	P/N

3*3 POSITIONS

3*4 POSITIONS

3*5 POSITIONS



KEYING FOR 3*3 POS.

KEYING FOR 3*4 POS.

KEYING FOR 3*5 POS.

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN TOMMY.WU 26MAR2013
CHK HAPYE.WU 26MAR2013
APVD YUZHONG.MAO 26MAR2013

NAME CAP HOUSING,FREE HANGING,TRIPLE ROW POWER TRIPLE LOCK

DIMENSIONS: mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ±0.35
1 PLC ±0.25
2 PLC ±0.25
3 PLC ±0.25
4 PLC ±0.25
ANGLES ±0.5°
FINISH

MATERIAL

SIZE 100779

CAGE CODE

DRAWING NO. 2232360

RESTRICTED TO

Customer Drawing

SCALE

SHEET 2 OF 2

REV B