
SloanLED®
Leaders in LED Technology




VL Plus 2 Whites


Everyday standard face lit solutions

VL Plus 2 LED lighting system is based on proven SloanLED channel letter module design and performance. VL Plus 2 offers a variety of solutions and a wide selection of color temperatures.


- VL Plus 2 is 25% brighter than VL Plus
- **NEW** VL Plus 2 HB Short is 28% brighter than VL Plus 2 Short
- Short available in 5 shades of white
- Constant Current Technology (CCT)



VL Plus 2 Long
2 modules per foot



VL Plus 2 Short
2.5 modules per foot





VL Plus 2 Mini
4 modules per foot

Specifications

Part number	Long	6500 K	701269-6WLA2-MB
	Short	7200 K	701269-7WSA2-MB
		6500 K	701269-6WSA2-MB
		5000 K	701269-5WSA2-MB
		4000 K	701269-4WSA2-MB
		3000 K	701269-3WSA2-MB
	HB Short	6500 K	701269-6WHA1-MB
	Mini	6500 K	701269-6WMA2-MB
Dimensions L × W × H	Long	3.45 in × 0.49 in × 0.35 in	
	Short	2.35 in × 0.49 in × 0.35 in	
	Mini	1.33 in × 0.44 in × 0.35 in	
Viewing angle	120°		
LEDs per module	Long/Short	3	
	Mini	2	
Modules per foot	Long	2	
	Short	2.5	
	Mini	4	
Maximum coverage per row	**Can depth**	**Coverage**	
	5 in	5 in	
Operating temperature	-40° C to +70° C		
Protection class	IP66		
Power per module	Long/Short	0.54 W	
	Mini	0.42 W	
Efficacy	Long/Short	93 lm/W	
	HB Short	119 lm/W	
	Mini	60 lm/W	
Power capacity	Per SloanLED 60 W 12 VDC power supply:		
	Long/Short	100 modules	
	Mini	128 modules	

SloanLED®
Leaders in LED Technology





VL Plus 2 Whites

Everyday standard face lit solutions

Specifications *cont'd*

Fastening Peel-n-stick and mechanical

Packaging 5 trays per carton

Long	25 ft (50 modules) per tray
Short	30 ft (75 modules) per tray
Mini	25 ft (100 modules) per tray

Size	Color temperature	Part number	Lumens per module (nominal)
Long	6500 K	701269-6WLA2-MB	50
Short	7200 K	701269-7WSA2-MB	50
	6500 K	701269-6WSA2-MB	50
	5000 K	701269-5WSA2-MB	50
	4000 K	701269-4WSA2-MB	50
	3000 K	701269-3WSA2-MB	50
HB Short	6500 K	701269-6WHA1-MB	64
Mini	6500 K	701269-6WMA2-MB	25

5725 Olivas Park Drive • Ventura, California 93003 • 805.676.3200 Fax 805.676.3206 • SloanLED.com • info@SloanLED.com

SloanLED channel letter products are covered by US and foreign patents pending and covered by
one or more of the following US patents issued: 6,932,495, 7,160,140, 7,241,031, 7,520,771, 7,931,386 and European Patent No. 1756471

© 2015 SloanLED Rev C 2015-04-15