

Data sheet | Item number: 706-100/326-300

Connection cable; 26-pole; Pluggable connector per DIN 41651; open-ended; Length: 3 m; Conductor cross-section: 0.14 mm²

www.wago.com/706-100/326-300



Data Notes

Note	When using more than 10 wires, the maximum current per wire must be reduced to 0.7 A.
------	---

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Electrical data

Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	1 A

Connection data

Pole No.	26
Connection type (1)	System
Pole number 1	26
Pluggable connectors	Pluggable connector per DIN 41651; Female connector
Connection type 2	Open-ended
Cable type	LiYY
Wire cross-section	0.14 mm ²
Color code	per DIN VDE 47100

Physical data

Cable length	3 m
--------------	-----

Material data

Weight	286 g
--------	-------

Environmental requirements

Surrounding air temperature (operation)	-20 ... 50 °C
---	---------------

Commercial data

PU (SPU)	1 Stück
Packaging type	box
Country of origin	FR
GTIN	4050821825449
Customs tariff number	85444290900

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 706-100/326-300	URL	Download
--	-----	----------

Subject to changes. Please also observe the further product documentation!



Connection cable; 26-pole; Pluggable connector per DIN 41651; open-ended;
Length: 3 m; Conductor cross-section: 0.14 mm²

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.