ADELS contact

Circular Plug Terminal Blocks IP68
Circular Plug Connectors AC 179 kompakt

AC 179 SVH 3/ 4 SL



Distributor, 4 pole, Voltage Rating: 450 V, Current Rating: 17.5 A

Order Info

Reference Number (ref. no.)	743964K1
Applications	Lighting, Installation
PU	50

Type

Type	Distributor
Number of poles	4 pole
Clamping Units per Pole	1
Colour	black
Connection Type	Screw

Technical Data

Voltage Rating	450 V
Current Rating	17.5 A
Insulating Material	PA 6.6
Contact Material	Brass
Flammability Rating	V-2
max. Ambient Temperature Operation	85 °C
IP Code	IP68
Assembly Contact Screw	0.5x3.0 / ↻ 0.5 Nm
Assembly Strain Relief	↻ 2.5 Nm
Cable Diameter min.	7.0 mm
Cable Diameter max.	12.0 mm

Accessories

AC 179 RVK/ 4 M20	749564
DR 14 1x5,5x11	729007
DR 14 1x3,5	729008
DR 14 1x7,0	729001
DR 14 2x3,0	729003
DR 14 2x5,0	729004

DR 14 3x3,0	729005
DR 14 4x3,0	729006
DR 14 RH	729002
DR 14 GS	729010