

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0022503175

Status:

Active

Overview:

kk

Description:

2.54mm (.100") KK® IDT Double Cantilever Contact, 17 Circuits, Tin (Sn), Feed-Through, Friction Ramp and Polarizing Rib, Green ID Strip

Documents:


3D Model

Drawing (PDF)

Product Specification PSX-7690S (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification	
UL	E29179
General	
Product Family	IDT and Solder Connectors
Series	7720
Comments	Version H
Crimp Quality Equipment	Yes
Overview	kk
Product Name	KK®
Physical	
Circuits (Loaded)	17
Circuits (maximum)	17
Color - Resin	Natural
Durability (mating cycles max)	5
Flammability	94V-2
Gender	Female
Glow-Wire Compliant	No
Lock to Mating Part	None
Material - Metal	Brass
Material - Plating Mating	Tin
Material - Plating Termination	Tin
Material - Resin	Nylon
Number of Rows	1
Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface (in)	0.100 In
Pitch - Mating Interface (mm)	2.54 mm
Pitch - Term. Interface (in)	0.100 In
Pitch - Term. Interface (mm)	2.54 mm
Polarized to Mating Part	Yes
Stackable	No
Temperature Range - Operating	0°C to +50°C
Termination Interface: Style	IDT or Pierce
Wire Size AWG	24 Stranded, 26 Solid, 26 Stranded Topcoat
Electrical	
Current - Maximum per Contact	4A
Voltage - Maximum	250V
Solder Process Data	
Lead-free Process Capability	Wave Capable (TH only)
Material Info	
Old Part Number	7720SC17H



EU RoHS

ELV and RoHS

Compliant

REACH SVHC

Not Reviewed

Halogen-Free

Status

Halogen-Free

China RoHS

Need more information on product environmental compliance?

Email productcompliance@molex.com

For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

7720Series

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global


Description	Product #
Insertion Tool for 2.54mm (.100") Pitch KK® IDT Crimp Terminals	0638133504
IDT - Semi-automatic	0011200412
- Bench-Top Terminator	

Reference - Drawing Numbers

Packaging Specification	PK-7720-100
Product Specification	PSX-7690S
Sales Drawing	SDA-7720S-*N*

This document was generated on 05/18/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION



	10	9	8	7	6	5	4	3	2	1																																																																																																																																																
F	<table><tr><td>PART NO.</td><td>ENG. NO.</td><td>CCTS.</td><td>TERMINAL</td><td>I.D. STRIPE</td><td>PLTGT.</td></tr><tr><td>22-50-3025</td><td>A-7720S-C 2H</td><td>2</td><td>40125-H(P918)</td><td>GREEN</td><td rowspan="28">HOT TIN DIP (1-3MM)/.000040-.000120</td></tr><tr><td>↑ 3035</td><td>↑ C 3H</td><td>3</td><td>↑</td><td>↑</td></tr><tr><td>3045</td><td>C 4H</td><td>4</td><td></td><td></td></tr><tr><td>3055</td><td>C 5H</td><td>5</td><td></td><td></td></tr><tr><td>3065</td><td>C 6H</td><td>6</td><td></td><td></td></tr><tr><td>3075</td><td>C 7H</td><td>7</td><td></td><td></td></tr><tr><td>3085</td><td>C 8H</td><td>8</td><td></td><td></td></tr><tr><td>3095</td><td>C 9H</td><td>9</td><td></td><td></td></tr><tr><td>3105</td><td>C 10H</td><td>10</td><td></td><td></td></tr><tr><td>3115</td><td>C 11H</td><td>11</td><td></td><td></td></tr><tr><td>3125</td><td>C 12H</td><td>12</td><td></td><td></td></tr><tr><td>3135</td><td>C 13H</td><td>13</td><td></td><td></td></tr><tr><td>3145</td><td>C 14H</td><td>14</td><td></td><td></td></tr><tr><td>3155</td><td>C 15H</td><td>15</td><td></td><td></td></tr><tr><td>3165</td><td>C 16H</td><td>16</td><td></td><td></td></tr><tr><td>3175</td><td>C 17H</td><td>17</td><td></td><td></td></tr><tr><td>3185</td><td>C 18H</td><td>18</td><td></td><td></td></tr><tr><td>3195</td><td>C 19H</td><td>19</td><td></td><td></td></tr><tr><td>3205</td><td>C 20H</td><td>20</td><td></td><td></td></tr><tr><td>3215</td><td>C 21H</td><td>21</td><td></td><td></td></tr><tr><td>3225</td><td>C 22H</td><td>22</td><td></td><td></td></tr><tr><td>3235</td><td>C 23H</td><td>23</td><td></td><td></td></tr><tr><td>3245</td><td>C 24H</td><td>24</td><td></td><td></td></tr><tr><td>3255</td><td>C 25H</td><td>25</td><td></td><td></td></tr><tr><td>3265</td><td>C 26H</td><td>26</td><td></td><td></td></tr><tr><td>↓ 3275</td><td>↓ C 27H</td><td>27</td><td>↓</td><td>↓</td></tr><tr><td>22-50-3285</td><td>A-7720S-C 28H</td><td>28</td><td>40125-H(P918)</td><td>GREEN</td></tr></table>											PART NO.	ENG. NO.	CCTS.	TERMINAL	I.D. STRIPE	PLTGT.	22-50-3025	A-7720S-C 2H	2	40125-H(P918)	GREEN	HOT TIN DIP (1-3MM)/.000040-.000120	↑ 3035	↑ C 3H	3	↑	↑	3045	C 4H	4			3055	C 5H	5			3065	C 6H	6			3075	C 7H	7			3085	C 8H	8			3095	C 9H	9			3105	C 10H	10			3115	C 11H	11			3125	C 12H	12			3135	C 13H	13			3145	C 14H	14			3155	C 15H	15			3165	C 16H	16			3175	C 17H	17			3185	C 18H	18			3195	C 19H	19			3205	C 20H	20			3215	C 21H	21			3225	C 22H	22			3235	C 23H	23			3245	C 24H	24			3255	C 25H	25			3265	C 26H	26			↓ 3275	↓ C 27H	27	↓	↓	22-50-3285	A-7720S-C 28H	28	40125-H(P918)	GREEN	F
PART NO.	ENG. NO.	CCTS.	TERMINAL	I.D. STRIPE	PLTGT.																																																																																																																																																					
22-50-3025	A-7720S-C 2H	2	40125-H(P918)	GREEN	HOT TIN DIP (1-3MM)/.000040-.000120																																																																																																																																																					
↑ 3035	↑ C 3H	3	↑	↑																																																																																																																																																						
3045	C 4H	4																																																																																																																																																								
3055	C 5H	5																																																																																																																																																								
3065	C 6H	6																																																																																																																																																								
3075	C 7H	7																																																																																																																																																								
3085	C 8H	8																																																																																																																																																								
3095	C 9H	9																																																																																																																																																								
3105	C 10H	10																																																																																																																																																								
3115	C 11H	11																																																																																																																																																								
3125	C 12H	12																																																																																																																																																								
3135	C 13H	13																																																																																																																																																								
3145	C 14H	14																																																																																																																																																								
3155	C 15H	15																																																																																																																																																								
3165	C 16H	16																																																																																																																																																								
3175	C 17H	17																																																																																																																																																								
3185	C 18H	18																																																																																																																																																								
3195	C 19H	19																																																																																																																																																								
3205	C 20H	20																																																																																																																																																								
3215	C 21H	21																																																																																																																																																								
3225	C 22H	22																																																																																																																																																								
3235	C 23H	23																																																																																																																																																								
3245	C 24H	24																																																																																																																																																								
3255	C 25H	25																																																																																																																																																								
3265	C 26H	26																																																																																																																																																								
↓ 3275	↓ C 27H	27	↓	↓																																																																																																																																																						
22-50-3285	A-7720S-C 28H	28	40125-H(P918)	GREEN																																																																																																																																																						
E	NOTE: 1. 18 - 28 CIRCUITS ARE NON-STANDARD.											E																																																																																																																																														
D												D																																																																																																																																														
C												C																																																																																																																																														
B												B																																																																																																																																														
A	<table><tr><td rowspan="5">CORRECT PLATING EC NO: E2007-0125 DRWN: WASZK/EMI C7 2006/10/10 CHKD: D. MORIARTY 2006/10/11 APPR: DENNEHY 2006/10/11</td><td>REV</td><td>DESCRIPTION</td><td>QUALITY SYMBOLS ▽=0 ▽C=0</td><td>GENERAL TOLERANCES (UNLESS SPECIFIED) mm INCH 4 PLACES ± --- ± --- 3 PLACES ± --- ± --- 2 PLACES ± --- ± --- 1 PLACE ± --- ± --- ANGULAR ± ---°</td><td>DIMENSION STYLE MM ONLY DRAWN BY DATE CHECKED BY DATE APPROVED BY DATE J. DENNEHY MATERIAL NO.</td><td>SCALE ---</td><td>DESIGN UNITS METRIC</td><td>THIRD ANGLE PROJECTION</td><td colspan="2">INSULATION DISPLACEMENT CONNECTOR (2.54)/.100 CENTRES</td></tr><tr><td colspan="3"></td><td>DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS</td><td>SEE CHART</td><td colspan="2">DOCUMENT NO. SDA-7720S-*N*</td><td colspan="2">SHEET NO. 2 OF 4</td></tr><tr><td colspan="3"></td><td colspan="8">THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION</td></tr><tr><td colspan="3"></td><td colspan="8"></td></tr><tr><td colspan="3"></td><td colspan="8"></td></tr></table>											CORRECT PLATING EC NO: E2007-0125 DRWN: WASZK/EMI C7 2006/10/10 CHKD: D. MORIARTY 2006/10/11 APPR: DENNEHY 2006/10/11	REV	DESCRIPTION	QUALITY SYMBOLS ▽=0 ▽C=0	GENERAL TOLERANCES (UNLESS SPECIFIED) mm INCH 4 PLACES ± --- ± --- 3 PLACES ± --- ± --- 2 PLACES ± --- ± --- 1 PLACE ± --- ± --- ANGULAR ± ---°	DIMENSION STYLE MM ONLY DRAWN BY DATE CHECKED BY DATE APPROVED BY DATE J. DENNEHY MATERIAL NO.	SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	INSULATION DISPLACEMENT CONNECTOR (2.54)/.100 CENTRES					DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	SEE CHART	DOCUMENT NO. SDA-7720S-*N*		SHEET NO. 2 OF 4					THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																														A																																																																																									
CORRECT PLATING EC NO: E2007-0125 DRWN: WASZK/EMI C7 2006/10/10 CHKD: D. MORIARTY 2006/10/11 APPR: DENNEHY 2006/10/11	REV	DESCRIPTION	QUALITY SYMBOLS ▽=0 ▽C=0	GENERAL TOLERANCES (UNLESS SPECIFIED) mm INCH 4 PLACES ± --- ± --- 3 PLACES ± --- ± --- 2 PLACES ± --- ± --- 1 PLACE ± --- ± --- ANGULAR ± ---°	DIMENSION STYLE MM ONLY DRAWN BY DATE CHECKED BY DATE APPROVED BY DATE J. DENNEHY MATERIAL NO.	SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	INSULATION DISPLACEMENT CONNECTOR (2.54)/.100 CENTRES																																																																																																																																																	
				DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	SEE CHART	DOCUMENT NO. SDA-7720S-*N*		SHEET NO. 2 OF 4																																																																																																																																																		
				THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																																																																																																																																																						
ib_frame_A3_P_ME_T Rev. D 2004/04/02																																																																																																																																																										
	10	9	8	7	6	5	4	3	2	1																																																																																																																																																