SPECIFICATION

Device Name	:	IGBT Module
Type Name	:	7MBR50SB060-01
Spec. No.	:	MS6M 0551
Date	:	Jun. - 02 - 2000

This material and the information herein is the property of Fuji Electric Co.,Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co.,Ltd.

Fuji Electric Co.,Ltd.
Matsumoto Factory

	DATE	NAME	APPROVED
DRAWN	Jun. - 2 - '00	J. Kobayashi	
CHECKED	June - 2 - 00	S. Motta	T. Miyata

Fuji Electric Co.,Ltd.

DWG.NO. MS6M 0551 1/10

Revised Records

Date	Classi-fication	Ind.	Content	Applied date	Drawn	Checked	Approved
Jun.-2-'00	enactment	——	————	Issued date	——	S. Ueda	T. Miyaoka


the property of
produced, copied
or the use of any
purposes without
ic Co., Ltd.

Revised Records


Date	Classi-fication	Ind.	Content	Applied date	Drawn	Checked	Approved
Jun.-2-'00	enactment	—	————	Issued date	—	S. Myata	T. Miyaoka

This material and the information herein is the property of Fuji Electric Co.,Ltd. They shall be neither reproduced, copied lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd

1. Outline Drawing (Unit : mm)



2. Equivalent circuit



This material and the information herein is the property of Fuji Electric Co.Ltd They shall be neither reproduced copied lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co.,Ltd.

3. Absolute Maximum Ratings (at Tc= 25C unless otherwise specified)

Items			Symbols	Conditions	Maximum Ratings	Units
Inverter	Collector-Emitter voltage		VCES		600	V
	Gate-Emitter voltage		VGES		+-20	V
	Collector current		Ic	Continuous	50	A
			Icp	1ms	100	A
			-Ic		50	A
	Collector Power Dissipation		Pc	1 device	200	W
Brake	Collector-Emitter voltage		VCES		600	V
	Gate-Emitter voltage		VGES		+-20	V
	Collector current		Ic	Continuous	30	A
			Icp	1ms	60	A
	Collector Power Dissipation		Pc	1 device	120	W
	Repetitive peak reverse Voltage(Diode)		VRRM		600	V
Converter	Repetitive peak reverse Voltage		VRRM		800	V
	Average Output Current		Io	50Hz/60Hz sine wave	50	A
	Surge Current (Non-Repetitive)		IFSM	Tj=150C,10ms half sine wave	350	A
	I^2t (Non-Repetitive)		I^2t		613	A^2s
Junction temperature			Tj		150	C
Storage temperature			Tstg		-40~ +125	C
Isolation voltage	between terminal and copper base(*1)		Viso	AC : 1min.	2500	V
	between thermistor and others (*2)				2500	V
Mounting Screw Torque (*3)					3.5	Nm

(*1) All terminals should be connected together when isolation test will be done.

(*2) Terminal 8 and 9 should be connected together. Terminal 1 to 7 and 10 to 24 should be connected together and shorted to copper base.

(*3) Recommendable Value : 2.5~3.5 Nm (M5)

This material and the information herein is the property of Fuji Electric Co.,Ltd. They shall be neither reproduced, copied lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

4. Electrical characteristics (at Tj= 25C unless otherwise specified)

	Items	Symbols	Conditions		Characteristics min.	typ.	Max.	Units
Inverter	Zero gate voltage Collector current	ICES	VGE 0 V, VCE 600 V				1.0	mA
	Gate-Emitter leakage current	IGES	VCE 0 V, VGE +-20 V				200	nA
	Gate-Emitter threshold voltage	VGE(th)	VCE 20 V, Ic = 50 m		5.5	7.8	8.5	V
	Collector-Emitter saturation voltage	VCE(sat)	VGE 15 V, Ic = 50 A	chip		1.8		V
				terminal		1.95	2.4	
	Input capacitance	Cies	VGE 0 V, VCE 10 V f = 1 MHz			5000		pF
	Turn-on time	ton	Vcc= 300 V			0.45	1.2	us
		tr	Ic = 50 A			0.25	0.6	
		$tr_{(i)}$	VGE +-15 V			0.08		
	Turn-off time	toff	RG = 51 ohm			0.40	1.0	
		tf				0.05	0.35	
	Forward on voltage	VF	IF = 50 A	chip		1.75		V
				terminal		1.9	2.6	
	Reverse recovery time	trr	IF = 50 A				300	ns
Brake	Zero gate voltage Collector current	ICES	VGE 0 V, VCE 600 V				1.0	mA
	Gate-Emitter leakage current	IGES	VCE 0 V, VGE +-20 V				200	nA
	Collector-Emitter saturation voltage	VCE(sat)	VGE 15 V, Ic = 30 A	chip		1.8		V
				terminal		1.95	2.4	
	Turn-on time	ton	Vcc= 300 V			0.45	1.2	us
		tr	Ic = 30 A			0.25	0.6	
	Turn-off time	toff	VGE +-15 V			0.40	1.0	
		tf	RG = 82 ohm			0.05	0.35	
	Reverse current	IRRM	VR = 600 V				1.0	mA
Converter	Forward on voltage	VFM	IF = 50 A	chip		1.1		V
				terminal		1.2	1.5	
	Reverse current	IRRM	VR = 800 V				1.0	mA
Thermistor	Resistance	R	T = 25C			5000		ohm
			T =100C		465	495	520	
	B value	B	T = 25/50C		3305	3375	3450	K


5. Thermal resistance characteristics

Items	Symbols	Conditions	Characteristics min.	typ.	Max.	Units
Thermal resistance (1 device)	Rth(j-c)	Inverter IGBT			0.63	C/W
		Inverter FWD			1.33	
		Brake IGBT			1.04	
		Converter Diode			0.90	
Contact Thermal resistance	Rth(c-f)	with Thermal Compound (*)		0.05		C/W

* This is the value which is defined mounting on the additional cooling fin with thermal compound.

This material and the information herein is the property of Fuji Electric Co.Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party,nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

6. Indication on module




7. Applicable category

This specification is applied to Power Integrated Module named 7MBR50SB060-01.

8. Storage and transportation notes

- The module should be stored at a standard temperature of 5 to 35℃ and humidity of 45 to 75% .
- Store modules in a place with few temperature changes in order to avoid condensation on the module surface.
- Avoid exposure to corrosive gases and dust.
- Avoid excessive external force on the module.
- Store modules with unprocessed terminals.
- Do not drop or otherwise shock the modules when transporting.
- Please connect adequate fuse or protector of circuit between three-phase line and this product to prevent the equipment from causing secondary destruction.


9. Definitions of switching time




This material and the information herein is the property of Fuji Electric Co.Ltd They shall be neither reproduced, copied lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

This material and the information herein is the property of Fuji Electric Co Ltd They shall be neither reproduced, copied lent, or disclosed in any way whatsoever for the use of any third party,nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.


[Inverter]
Collector current vs. Collector-Emitter voltage
Tj= 25℃ (typ.)




[Inverter]
Collector current vs. Collector-Emitter voltage
Tj= 125℃ (typ.)




[Inverter]
Collector current vs. Collector-Emitter voltage
VGE=15V (typ.)




[Inverter]
Collector-Emitter voltage vs. Gate-Emitter voltage
Tj= 25℃ (typ.)



[Inverter]
Capacitance vs. Collector-Emitter voltage (typ.)
VGE=0V, f= 1MHz, Tj= 25℃




[Inverter]
Dynamic Gate charge (typ.)
Vcc=300V, Ic=50A, Tj= 25℃




This material and the information herein is the property of Fuji Electric Co.,Ltd. They shall be neither reproduced, copied lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.


[Inverter]
Switching time vs. Collector current (typ.)
Vcc=300V, VGE=± 15V, Rg=51Ω , Tj= 25℃




[Inverter]
Switching time vs. Collector current (typ.)
Vcc=300V, VGE=± 15V, Rg= 51Ω , Tj= 125℃




[Inverter]
Switching time vs. Gate resistance (typ.)
Vcc=300V, Ic=50A, VGE=± 15V, Tj= 25℃




[Inverter]
Switching loss vs. Collector current (typ.)
Vcc=300V, VGE=± 15V, Rg=51Ω




[Inverter]
Switching loss vs. Gate resistance (typ.)
Vcc=300V, Ic=50A, VGE=± 15V, Tj= 125℃




[Inverter]
Reverse bias safe operating area
+VGE=15V, -VGE≦ 15V, Rg≧ 51Ω , Tj≦ 125℃




[Inverter]
Forward current vs. Forward on voltage (typ.)




[Inverter]
Reverse recovery characteristics (typ.)
Vcc=300V, VGE=± 15V, Rg=51Ω




[Converter]
Forward current vs. Forward on voltage (typ.)



Transient thermal resistance




[Thermistor]
Temperature characteristic (typ.)




This material and the information herein is the property of Fuji Electric Co.Ltd They shall be neither reproduced, copied lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

This material and the information herein is the property of Fuji Electric Co.Ltd They shall be neither reproduced, copied lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co. Ltd


[Brake]
Collector current vs. Collector-Emitter voltage
Tj= 25℃ (typ.)




[Brake]
Collector current vs. Collector-Emitter voltage
Tj= 125℃ (typ.)




[Brake]
Collector current vs. Collector-Emitter voltage
VGE=15V (typ.)




[Brake]
Collector-Emitter voltage vs. Gate-Emitter voltage
Tj= 25℃ (typ.)



[Brake]
Capacitance vs. Collector-Emitter voltage (typ.)
VGE=0V, f= 1MHz, Tj= 25℃



[Brake]
Dynamic Gate charge (typ.)
Vcc=300V, Ic=30A, Tj= 25℃



Fuji Electric Co.,Ltd.	DWG.NO.	MS6M 0551	10/10

H04-004-03