

4		3		2		1																																																																																																																
THIS DRAWING IS UNPUBLISHED.		RELEASED FOR PUBLICATION		LOC		DIST		REVISIONS																																																																																																														
© COPYRIGHT - By -		ALL RIGHTS RESERVED.		G		14		P	LTR	DESCRIPTION	DATE	DWN	APVD																																																																																																									
									W2	REVISED PER ECO-11-004917	11MAR11	RK	HMR																																																																																																									
INSULATION BODY 7.52 MAX DIA [.296]IN CRIMP AREA 11.25 MAX DIA [.443] 19.69 MAX [.775] 0 22 4 22 0 AMP 4 AMP 1 FOR 9.53 [.375] MAX WIRE INSULATION DIA 2 SUPERSEDED BY 35653 3 MATERIAL: BODY; COPPER PER ASTM B152 INSULATION; NYLON COLOR; NATURAL 4 FINISH: BODY; TIN PL. PER ASTM B545 <table><tr><td></td><td></td><td></td></tr><tr><td>22-10 AWG SOLID OR STRANDED</td><td>22-10 AWG SOLID OR STRANDED</td><td>22-10 AWG SOLID OR STRANDED</td></tr></table><table><tr><td>25</td><td>LOOSE PC,BAG</td><td>8-35653-5</td></tr><tr><td>5</td><td>LOOSE PC,BLS</td><td>8-35653-4</td></tr><tr><td>100</td><td>LOOSE PC,BOX</td><td>8-35653-1</td></tr><tr><td>10000</td><td>SPECIAL PKG,</td><td>2-35653-2</td></tr><tr><td>1500</td><td>TAPE MOUNTED</td><td>2-35653-1</td></tr><tr><td>1000</td><td>LOOSE PIECE</td><td>35653</td></tr><tr><td>QTY</td><td>DESCRIPTION</td><td>PART NO</td></tr></table><table><tr><td colspan="2">AMP INCORPORATED CUSTOMER SERVICE SYSTEMS</td><td colspan="2">MAX RECOMMENDED OPERATING TEMPERATURE: 105° C MAX</td><td colspan="2">THIS DRAWING IS A CONTROLLED DOCUMENT.</td><td colspan="2">DWN G KRUPER 1/93</td><td colspan="4" rowspan="2"> TE Connectivity</td></tr><tr><td colspan="2">FOR ADDITIONAL PRODUCT INFORMATION OR COPIES OF DRAWINGS AND TECHNICAL DOCUMENTS</td><td colspan="2">PRODUCT INFORMATION CENTER 1-800-522-6752</td><td colspan="2">DIMENSIONS: INCHES</td><td colspan="2">TOLERANCES UNLESS OTHERWISE SPECIFIED:</td><td colspan="2">CHK R HERSEY 1/93</td></tr><tr><td colspan="2">FOR APPLICATION TOOLING INFORMATION</td><td colspan="2">TOOLING ASSISTANCE CENTER 1-800-722-1111</td><td colspan="2">VOLTAGE RATING: 300V MAX</td><td colspan="2" rowspan="2"></td><td colspan="2">APVD M ELLIS 1/93</td><td colspan="2" rowspan="2">NAME SPLICE, WIRE, CLOSED END</td></tr><tr><td colspan="2">FOR ORDER ENTRY</td><td colspan="2">1-800-526-5142</td><td colspan="2">CIRCULAR MIL AREA: 1.65-6.64mm² [3248-13100] SOLID OR STRANDED</td><td colspan="2">PRODUCT SPEC -</td></tr><tr><td colspan="2"></td><td colspan="2">THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INCORPORATED. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.</td><td colspan="2">MATERIAL</td><td colspan="2">FINISH</td><td colspan="2">APPLICATION SPEC -</td><td colspan="2">SIZE A3</td><td colspan="2">CAGE CODE 00779</td><td colspan="2">DRAWING NO C-35653</td><td colspan="2">RESTRICTED TO -</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"> 3 </td><td colspan="2"> 4 </td><td colspan="2">WEIGHT -</td><td colspan="2">CUSTOMER DRAWING</td><td colspan="2">SCALE 4:1</td><td colspan="2">SHEET 1 OF 1</td><td colspan="2">REV W2</td></tr></table> 1470-19 (3/11)																	22-10 AWG SOLID OR STRANDED	22-10 AWG SOLID OR STRANDED	22-10 AWG SOLID OR STRANDED	25	LOOSE PC,BAG	8-35653-5	5	LOOSE PC,BLS	8-35653-4	100	LOOSE PC,BOX	8-35653-1	10000	SPECIAL PKG,	2-35653-2	1500	TAPE MOUNTED	2-35653-1	1000	LOOSE PIECE	35653	QTY	DESCRIPTION	PART NO	AMP INCORPORATED CUSTOMER SERVICE SYSTEMS		MAX RECOMMENDED OPERATING TEMPERATURE: 105° C MAX		THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN G KRUPER 1/93		TE Connectivity				FOR ADDITIONAL PRODUCT INFORMATION OR COPIES OF DRAWINGS AND TECHNICAL DOCUMENTS		PRODUCT INFORMATION CENTER 1-800-522-6752		DIMENSIONS: INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED:		CHK R HERSEY 1/93		FOR APPLICATION TOOLING INFORMATION		TOOLING ASSISTANCE CENTER 1-800-722-1111		VOLTAGE RATING: 300V MAX				APVD M ELLIS 1/93		NAME SPLICE, WIRE, CLOSED END		FOR ORDER ENTRY		1-800-526-5142		CIRCULAR MIL AREA: 1.65-6.64mm² [3248-13100] SOLID OR STRANDED		PRODUCT SPEC -				THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INCORPORATED. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.		MATERIAL		FINISH		APPLICATION SPEC -		SIZE A3		CAGE CODE 00779		DRAWING NO C-35653		RESTRICTED TO -						3		4		WEIGHT -		CUSTOMER DRAWING		SCALE 4:1		SHEET 1 OF 1		REV W2	
22-10 AWG SOLID OR STRANDED	22-10 AWG SOLID OR STRANDED	22-10 AWG SOLID OR STRANDED																																																																																																																				
25	LOOSE PC,BAG	8-35653-5																																																																																																																				
5	LOOSE PC,BLS	8-35653-4																																																																																																																				
100	LOOSE PC,BOX	8-35653-1																																																																																																																				
10000	SPECIAL PKG,	2-35653-2																																																																																																																				
1500	TAPE MOUNTED	2-35653-1																																																																																																																				
1000	LOOSE PIECE	35653																																																																																																																				
QTY	DESCRIPTION	PART NO																																																																																																																				
AMP INCORPORATED CUSTOMER SERVICE SYSTEMS		MAX RECOMMENDED OPERATING TEMPERATURE: 105° C MAX		THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN G KRUPER 1/93		TE Connectivity																																																																																																														
FOR ADDITIONAL PRODUCT INFORMATION OR COPIES OF DRAWINGS AND TECHNICAL DOCUMENTS		PRODUCT INFORMATION CENTER 1-800-522-6752		DIMENSIONS: INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED:						CHK R HERSEY 1/93																																																																																																										
FOR APPLICATION TOOLING INFORMATION		TOOLING ASSISTANCE CENTER 1-800-722-1111		VOLTAGE RATING: 300V MAX				APVD M ELLIS 1/93		NAME SPLICE, WIRE, CLOSED END																																																																																																												
FOR ORDER ENTRY		1-800-526-5142		CIRCULAR MIL AREA: 1.65-6.64mm² [3248-13100] SOLID OR STRANDED				PRODUCT SPEC -																																																																																																														
		THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INCORPORATED. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.		MATERIAL		FINISH		APPLICATION SPEC -		SIZE A3		CAGE CODE 00779		DRAWING NO C-35653		RESTRICTED TO -																																																																																																						
				3		4		WEIGHT -		CUSTOMER DRAWING		SCALE 4:1		SHEET 1 OF 1		REV W2																																																																																																						