Fuse DTII 500V



See below:
Approvals and Compliances

Description

- Operation full range cable defensive fuses
- Over-load and short-circuit protection
- Colored characteristic detector in the middle
- Characteristic gG
- According to IEC 269

Technical Data

Rated Current In	2- 25 A
Rated Voltage	500 VAC
Breaking Capacity	50 kA
Rated Power Operating Frequency fe	50 Hz

Basic Design	
Insulator	Ceramics
Metal components	Brass

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals


Compliances

The product complies with following Guide Lines

Identification	Details	Initiator	Description
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

Time-Current-Curves

DT II - DT III



Current in Amperes

All Variants

Rated current	Color	Packaging unit	Order Number	E-No.	
[A]		Pcs			
2	rosé	25	0001.2021	800250209	
4	brown	25	0001.2022	800250409	
6	green	25	0001.2023	800250609	
10	red	25	0001.2024	800251009	
16	grey	25	0001.2025	800251509	
20	blue	25	0001.2026	800252009	
25	yellow	25	0001.2027	800252509	

Most Popular.

Availability for all products can be searched real-time:https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

04.01.2022

The specifications, descriptions and illustrations indicated in this document are based on current information. All content is subject to modifications and amendments. Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability and test each product selected for their own applications.