



Series 802 AquaMouse™ Submersible Shielded Overmolded Harsh Environment Cordsets

802-026, -027, -028, and -029 Ordering Information

Series 802 Cordsets with #16 Contacts

Sample Part Number								
802-026	-A	C	6	Z1	9-4	N	A	-48
Series	End A Connector	End B Connector	Wire Size	Shell Material / Finish	Insert Arr.	Protective Cover	Shell Key Pos.	Length
802-028 Style 1 Polyurethane Cable Jacket, Thermoset Polyurethane Overmold, 2500 PSI Rated 802-026 Style 2 Polyurethane Cable Jacket, Polyamide Overmold, 1 Meter Immersion	-A Plug, with Male Pin Contacts -B Plug, with Female Socket Contacts -C Receptacle, with Male Pin Contacts -D Receptacle, with Female Socket Contacts	A Plug, with Male Pin Contacts B Plug, with Female Socket Contacts C Receptacle, with Male Pin Contacts D Receptacle, with Female Socket Contacts N No Connector (Single-Ended)	6 #16 AWG 8 #18 AWG	Z1 Stainless Steel Shell / Passivated ZM Stainless Steel Shell / Electroless Nickel Plated AB Marine Bronze Shell Unplated	See page E-2 for insert arr. Consult Factory for Combo Arr.	P Metal Protective Covers Included N No Covers Supplied	A Normal B Pos. B C Pos. C D Pos. D See page E-2	Overall Length In Inches 12 Inch Min.

E

Series 802 Cordsets with #12 Contacts

Sample Part Number								
802-027	-A	C	0	M	10-2	N	A	-48
Series	End A Connector	End B Connector	Wire Size	Shell Material / Finish	Insert Arr.	Protective Cover	Shell Key Pos.	Length
802-029 Style 1 Polyurethane Cable Jacket, Thermoset Polyurethane Overmold, 2500 PSI Rated 802-027 Style 2 Polyurethane Cable Jacket, Polyamide Overmold, 1 Meter Immersion	-A Plug, with Male Pin Contacts -B Plug, with Female Socket Contacts -C Receptacle, with Male Pin Contacts -D Receptacle, with Female Socket Contacts	A Plug, with Male Pin Contacts B Plug, with Female Socket Contacts C Receptacle, with Male Pin Contacts D Receptacle, with Female Socket Contacts N No Connector (Single-Ended)	2 #12 AWG 4 #14 AWG	Z1 Stainless Steel Shell / Passivated ZM Stainless Steel Shell / Electroless Nickel Plated AB Marine Bronze Shell Unplated	See page E-2 for insert arr. Consult Factory for Combo Arr.	P Metal Protective Covers Included N No Covers Supplied	A Normal B Pos. B C Pos. C D Pos. D See page E-2	Overall Length In Inches 12 Inch Min.

Dimensions in Inches (millimeters) are subject to change without notice.