


# ISO cylinder CRDSNU-B-20-200-PPS-A-MG-A1

Part number: 8073972

**FESTO**



## Data sheet

| Feature                                  | Value                                                              |
|------------------------------------------|--------------------------------------------------------------------|
| Maritime classification                  | See certificate                                                    |
| Stroke                                   | 200 mm                                                             |
| Piston diameter                          | 20 mm                                                              |
| Type code                                | CRDSNU-B                                                           |
| Based on norm                            | ISO 6432                                                           |
| Cushioning                               | Self-adjusting pneumatic end-position cushioning                   |
| Mounting position                        | Any                                                                |
| Design                                   | Piston<br>Piston rod<br>Cylinder barrel                            |
| Position sensing                         | For proximity sensor                                               |
| Symbol                                   | 00992970                                                           |
| Operating pressure                       | 1 bar ... 10 bar                                                   |
| Mode of operation                        | Double-acting                                                      |
| Operating medium                         | Compressed air as per ISO 8573-1:2010 [7:4:4]                      |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)         | 4 - Particularly high corrosion stress                             |
| For use in the food industry             | See supplementary material information                             |
| Ambient temperature                      | 0 °C ... 80 °C                                                     |
| Theoretical force at 6 bar, retracting   | 158 N                                                              |
| Theoretical force at 6 bar, advancing    | 188 N                                                              |
| Moving mass at 0 mm stroke               | 42.1 g                                                             |
| Additional weight per 10 mm stroke       | 7.2 g                                                              |
| Basic weight with 0 mm stroke            | 310 g                                                              |
| Additional moving mass per 10 mm stroke  | 3.9 g                                                              |
| Type of mounting                         | With accessories                                                   |
| Pneumatic connection                     | G1/8                                                               |
| Note on materials                        | RoHS-compliant                                                     |
| Cover material                           | High-alloy stainless steel                                         |
| Piston rod material                      | High-alloy stainless steel                                         |
| Material of cylinder barrel              | High-alloy stainless steel                                         |