Bulletin I25201 rev. B 03/03

International
IOR Rectifier

80RIA SERIES

PHASE CONTROL THYRISTORS **Stud Version**


80A

Features

- Hermetic glass-metal seal
- International standard case TO-209AC (TO-94)

Typical Applications

- DC motor controls
- Controlled DC power supplies
- AC controllers



case style
TO-209AC (TO-94)

Major Ratings and Characteristics

Parameters		80RIA	Unit
$I_{T(AV)}$		80	A
	@ T_C	85	°C
$I_{T(RMS)}$		125	A
I_{TSM}	@ 50Hz	1900	A
	@ 60Hz	1990	A
I^2t	@ 50Hz	18	KA^2s
	@ 60Hz	16	KA^2s
V_{DRM}/V_{RRM}		400 to 1200	V
t_q	typical	110	µs
T_J		- 40 to 125	°C

ELECTRICAL SPECIFICATIONS

Voltage Ratings

Type number	Voltage Code	V_{DRM}/V_{RRM}, max. repetitive peak and off-state voltage V	V_{RSM}, maximum non-repetitive peak voltage V	I_{DRM}/I_{RRM} max. @ T_J = 125°C mA
80RIA	40	400	500	15
	80	800	900	
	120	1200	1300	

On-state Conduction

	Parameter	80RIA	Units	Conditions		
$I_{T(AV)}$	Max. average on-state current	80	A	180° conduction, half sine wave		
	@ Case temperature	85	°C			
$I_{T(RMS)}$	Max. RMS on-state current	125	A	DC @ 75°C case temperature		
I_{TSM}	Max. peak, one-cycle	1900	A	t = 10ms	No voltage	Sinusoidal half wave, Initial $T_J = T_J$ max.
	non-repetitive surge current	1990		t = 8.3ms	reapplied	
		1600		t = 10ms	100% V_{RRM}	
		1675		t = 8.3ms	reapplied	
I^2t	Maximum I^2t for fusing	18	KA^2s	t = 10ms	No voltage	
		16		t = 8.3ms	reapplied	
		12.7		t = 10ms	100% V_{RRM}	
		11.7		t = 8.3ms	reapplied	
$I^2\sqrt{t}$	Maximum $I^2\sqrt{t}$ for fusing	180.5	$KA^2\sqrt{s}$	t = 0.1 to 10ms, no voltage reapplied		
$V_{T(TO)1}$	Low level value of threshold voltage	0.99	V	(16.7% x π x $I_{T(AV)}$ < I < π x $I_{T(AV)}$), $T_J = T_J$ max.		
$V_{T(TO)2}$	High level value of threshold voltage	1.13		(I > π x $I_{T(AV)}$), $T_J = T_J$ max.		
r_{t1}	Low level value of on-state slope resistance	2.29	mΩ	(16.7% x π x $I_{T(AV)}$ < I < π x $I_{T(AV)}$), $T_J = T_J$ max.		
r_{t2}	High level value of on-state slope resistance	1.84		(I > π x $I_{T(AV)}$), $T_J = T_J$ max.		
V_{TM}	Max. on-state voltage	1.60	V	I_{pk}= 250A, T_J = 25°C t_p = 10ms sine pulse		
I_H	Maximum holding current	200	mA	T_J = 25°C, anode supply 12V resistive load		
I_L	Typical latching current	400				

Switching

	Parameter	80RIA	Units	Conditions
di/dt	Max. non-repetitive rate of rise of turned-on current	300	A/µs	T_J = 125°C, V_d = rated V_{DRM}, I_{TM} = 2xdi/dt snubber 0.2µF, 15Ω, Gate pulse: 20V, 65Ω, t_p = 6µs, t_r= 0.5µs Per JEDEC Standard RS-397, 5.2.2.6.
t_d	Typical delay time	1	µs	Gate pulse: 10V, 15Ω source, t_p = 6µs, t_r = 0.1µs, V_d = rated V_{DRM}, I_{TM} = 50Adc, T_J = 25°C.
t_q	Typical turn-off time	110		I_{TM} = 50A, T_J = T_J max, di/dt = -5A/µs min., V_R = 50V, dv/dt = 20V/µs, Gate bias: 0V 25Ω, t_p = 500µs

Blocking

	Parameter	80RIA	Units	Conditions
dv/dt	Maximum critical rate of rise of off-state voltage	500	V/µs	T_J = 125°C exponential to 67% rated V_{DRM}
I_{RRM} I_{DRM}	Max. peak reverse and off-state leakage current	15	mA	T_J = 125°C rated V_{DRM}/V_{RRM} applied

Triggering

	Parameter	80RIA	Units	Conditions
P_{GM}	Maximum peak gate power	12	W	T_J = T_J max, $t_p \leq$ 5ms
$P_{G(AV)}$	Maximum average gate power	3		T_J = T_J max, f = 50Hz, d% = 50
I_{GM}	Max. peak positive gate current	3	A	T_J = T_J max, $t_p \leq$ 5ms
$+V_{GM}$	Maximum peak positive gate voltage	20	V	T_J = T_J max, $t_p \leq$ 5ms
$-V_{GM}$	Maximum peak negative gate voltage	10		
I_{GT}	Max. DC gate current required to trigger	270 120 60	mA	T_J = - 40°C T_J = 25°C T_J = 125°C Max. required gate trigger/ current/ voltage are the lowest value which will trigger all units 6V anode-to-cathode applied
V_{GT}	Max. DC gate voltage required to trigger	3.5 2.5 1.5	V	T_J = - 40°C T_J = 25°C T_J = 125°C
I_{GD}	DC gate current not to trigger	6	mA	T_J = T_J max Max. gate current/ voltage not to trigger is the max. value which will not trigger any unit with rated V_{DRM} anode-to-cathode applied
V_{GD}	DC gate voltage not to trigger	0.25	V	

Thermal and Mechanical Specification

	Parameter	80RIA	Units	Conditions
T_J	Max. operating temperature range	-40 to 125	°C	
T_{stg}	Max. storage temperature range	-40 to 150		
R_{thJC}	Max. thermal resistance, junction to case	0.30	K/W	DC operation
R_{thCS}	Max. thermal resistance, case to heatsink	0.1		Mounting surface, smooth, flat and greased
T	Mounting torque, ± 10%	15.5 (137)	Nm (lbf-in)	Non lubricated threads
		14 (120)		Lubricated threads
wt	Approximate weight	130	g	
	Case style	TO-209AC(TO-94)		See Outline Table


ΔR_{thJ-C} Conduction

(The following table shows the increment of thermal resistence R_{thJ-C} when devices operate at different conduction angles than DC)

Conduction angle	Sinusoidal conduction	Rectangular conduction	Units	Conditions
180°	0.042	0.030	K/W	$T_J = T_J$ max.
120°	0.050	0.052		
90°	0.064	0.070		
60°	0.095	0.100		
30°	0.164	0.165		

Ordering Information Table

Device Code



1 - I_{TAV} x 10A

2 - 0 = Eyelet terminals (Gate and Auxiliary Cathode Leads)
1 = Fast - on terminals (Gate and Auxiliary Cathode Leads)


3 - RIA = Essential part number

4 - Voltage code: Code x 10 = V_{RRM} (See Voltage Rating Table)

5 - None = Stud base 1/2"-20UNF- 2A threads

NOTE: For Metric Device M12 x 1.75 E6 Contact factory

Outline Table






Fig. 1 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 3 - On-state Power Loss Characteristics




Fig. 4 - On-state Power Loss Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 6 - Maximum Non-Repetitive Surge Current




Fig. 7 - On-state Voltage Drop Characteristics




Fig. 8 - Thermal Impedance Z_{thJC} Characteristics




Fig. 9 - Gate Characteristics

Data and specifications subject to change without notice.
This product has been designed and qualified for Industrial Level.
Qualification Standards can be found on IR's Web site.

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7309
Visit us at www.irf.com for sales contact information. 03/03