Specification for release

Customer :

Ordercode: **824001**

Description: **TVS Diode Array WE-TVS**

Package: **SOT23-6L**

compliant RoHS WÜRTH ELEKTRONIK

WÜRTH ELEKTRONIK

DATUM / DATE : 2010-01-27


A Features:

- ESD Protection for 4 high-speed I/O channels and VDD
- Provide ESD protection for each channel to
  IEC 61000-4-2 (ESD) ±15kV (air), ±8kV (contact)
  IEC 61000-4-4 (EFT) (5/50ns) 20A (I/O), 40A (VDD)
  IEC 61000-4-5 (Lightning) 4A (8/20µs)
- Below 5V operating voltage: 2.5 - 3.3 - 4.2 - 5.0V
- Ultra Low capacitance: 1pF typical

Mechanical Characteristics:

- JEDEC SOT23-6L Package
- Molding compound flamability rating: UL94V-0
- Packaging: Tape & Reel

B Schematic and Pin Configuration:




C Absolute Maximum Ratings:

	Symbol	Rating	Unit
Peak Pulse Current (tp = 8/20µs)	I_{PP}	5	A
Operating Supply Voltage, VDD to GND	V_{DC}	6	V
DC Voltage at any I/O Pin	V_{IO}	(GND -0.5) to (VDD +0.5)	V
ESD per IEC 61000-4-2 (Air / Contact), I/O to GND	$V_{ESD,IO}$	15 / 8	kV
ESD per IEC 61000-4-2 (Air / Contact), VDD to GND	$V_{ESD,VDD}$	15 / 8	kV
Operating Temperature	T_{Op}	-55 to +85	℃
Storage Temperature	T_{Sto}	-20 to +60	℃


D Electrical Characterisitcs:

Properties	Test Conditions	Value min	Value typ	Value max	Unit
V_{RWM}	Pin 5 to Pin 2			5	V
V_{BV}	I_{BV}=1mA, Pin 5 to Pin 2	6.2			V
I_R	V_{Pin5}=5V, Pin 5 to Pin 2			2	µA
V_F	I_F = 15mA, Pin 2 to Pin 5		0.8	1.2	V
v_C	I_{PP}=5A, tp=8/20µs, I/O to GND		9	10	V
$v_{Cl,IO}$	I_{TLP} = 17A, I/O to GND		14		V
C_{IO}	V_{Pin5}=5V, V_{Pin2}=0V, V_{IO}=2.5V, f=1MHz, I/O to GND		1.0	1.5	pF
C_X	V_{Pin5}=5V, V_{Pin2}=0V, V_{IO}=2.5V f=1MHz, between I/O pins		0.1	0.2	pF


E Typical Characteristics:



Power Derating Curve




Clamping Voltage vs. Peak Pulse Current




Variation of C_{IO} vs. V_{IO}

E Typical Characteristic:




Transmission Line Pulsing (TLP) Measurement




Transmission Line Pulsing System

F Recommended Land Layout:



A	0.60	mm
B	1.10	mm
C	0.95	mm
D	2.50	mm
E	1.40	mm
F	3.60	mm

G Body Marking:




W01: Device Code

X: Date Code

Y: Control Code

H Dimensions:



Scale - 10:1


Specification for release

Customer :
Ordercode: **824001**
Description : **TVS Diode Array WE-TVS**

compliant RoHS WÜRTH ELEKTRONIK


WÜRTH ELEKTRONIK

I Tape:




A	**4.00 ± 0.10**	mm
B	**4.00 ± 0.10**	mm
C	**8.00 ± 0.20**	mm
D	**1.55 ± 0.05**	mm
E	**4.00 ± 0.10**	mm
F	**2.00 ± 0.05**	mm
G	**1.75 ± 0.10**	mm
H	**3.50 ± 0.05**	mm
I	**3.25 ± 0.15**	mm
J	**1.35 ± 0.15**	mm
K	**0.25 ± 0.02**	mm

J Reel:



a	**178.0 ± 2.0**	mm
b	**13.0 ± 0.8**	mm
c	**10.0 ± 1.5**	mm
d	**12.5 ± 2.0**	mm



Quantity per Reel:	3000

General Release:	**Customer**
Date	Signature
	Würth Elektronik
Checked	Approved

JB	Version 3	2010-01-27
JB	Version 2	2010-01-05
JB	Version 1	2008-10-13
Name	**Modification**	Date

This electronic component has been designed and developed for usage in general electronic equipment. Before incorporating this component into any equipment where higher safety and reliability is especially required or if there is the possibility of direct damage or injury to human body, for example in the range of aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc, Würth Elektronik eiSos GmbH must be informed before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 · Germany · Phone (+49) (0) 7942 - 945 - 0 · Fax (+49) (0) 7942 - 945 - 400
http://www.we-online.com