



"UNIVERSAL" FOR T-1 & T-1 3/4



- Unique design separates leads and retains Tri-Lead and Bi-Lead components.
- Designed for PC board mounting of Tri-Lead and Bi-Lead T-1 and T-1 3/4 LEDs
- Provides height control, lead retention and stability.
- Also suitable for mounting lamps, resistors, transistors, diodes, capacitors, etc.

MATERIAL: Black PVC, UL Rated 94V-0





FOR T-1 3/4 and T-1			
CAT. NO.	L LENGTH	CAT. NO.	L LENGTH
8900	.120 (3.0)	8916	.400 (10.2)
8901	.140 (3.6)	8917	.420 (10.7)
8902	.160 (4.1)	8918	.440 (11.2)
8903	.180 (4.6)	8919	.450 (11.4)
8904	.200 (5.1)	8920	.460 (11.7)
8905	.220 (5.6)	8921	.480 (12.2)
8906	.240 (6.1)	8922	.500 (12.7)
8907	.250 (6.4)	8923	.550 (14.0)
8908	.260 (6.6)	8924	.600 (15.2)
8909	.280 (7.1)	8925	.650 (16.5)
8910	.300 (7.6)	8926	.700 (17.8)
8911	.320 (8.1)	8927	.750 (19.1)
8912	.340 (8.6)	8928	.800 (20.3)
8913	.350 (8.9)	8929	.850 (21.6)
8914	.360 (9.1)	8930	.900 (22.9)
8915	.380 (9.7)	8931	.925 (23.5)

"SELF-ALIGNING" FOR BI-LEAD T-1 & T-1 3/4

KEY FEATURES

- Positive self-alignment of leads on .100 (.25) centers.
- No special tools required

MATERIAL: Natural Nylon, UL Rated 94V-2




- This features an internally tapered barrier which guides the leads and eliminates crimping or shorting.
- The bottom bosses serve the dual purpose of heat dissipation and easy post soldering cleanup.

T-1 3/4	T-1	L LENGTH	A REF.	T-1 3/4	T-1	L LENGTH	A REF.
8311	7351	.120 (3.0)	.075 (1.9)	8327	7367	.400 (10.2)	.325 (8.3)
8312	7352	.140 (3.6)		8328	7368	.420 (10.7)	
8313	7353	.160 (4.1)		8329	7369	.440 (11.2)	
8314	7354	.180 (4.6)		8330	7370	.450 (11.4)	
8315	7355	.200 (5.1)		8331	7371	.460 (11.7)	
8316	7356	.220 (5.6)	.190 (4.8)	8332	7372	.480 (12.2)	.450 (11.4)
8317	7357	.240 (6.1)		8333	7373	.500 (12.7)	
8318	7358	.250 (6.4)		8334	7374	.550 (14.0)	
8319	7359	.260 (6.6)		8335	7375	.600 (15.2)	
8320	7360	.280 (7.1)		8336	7376	.650 (16.5)	
8321	7361	.300 (7.6)	.200 (5.1)	8337	7377	.700 (17.8)	.575 (14.6)
8322	7362	.320 (8.1)		8338	7378	.750 (19.1)	
8323	7363	.340 (8.6)		8339	7379	.800 (20.3)	
8324	7364	.350 (8.9)		8340	7380	.850 (21.6)	
8325	7365	.360 (9.1)		8341	7381	.900 (22.9)	
8326	7366	.380 (9.7)	.325 (8.3)	8342	7382	.925 (23.5)	.690 (17.5)

"SELF-RETAINING" FOR T-1

KEY FEATURES

- Features internal retention "teeth" which secure LED leads onto spacers.
- This features an internally tapered barrier which guides the leads and eliminates crimping or shorting.
- The bottom bosses serve the dual purpose of heat dissipation and easy post soldering cleanup.
- Internal design eliminates crimping or shorting of leads
- Self alignment of leads on .100 [.25] centers.
- Spacer will stay gripped to LED leads during assembly
- No special tools required



T-1	CAT. NO.	L LENGTH	A REF.	T-1	CAT. NO.	L LENGTH	A REF.
7030	.120 (3.0)	.060 (1.5)	.310 (7.9)	7046	.400 (10.2)	.435 (11.0)	.690 (17.5)
7031	.140 (3.6)			7047	.420 (10.7)		
7032	.160 (4.1)			7048	.440 (11.2)		
7033	.180 (4.6)			7049	.450 (11.4)		
7034	.200 (5.1)			7050	.460 (11.7)		
7035	.220 (5.6)	.185 (4.7)	.650 (14.2)	7051	.480 (12.2)	.850 (21.6)	.925 (23.5)
7036	.240 (6.1)			7052	.500 (12.7)		
7037	.250 (6.4)			7053	.550 (14.0)		
7038	.260 (6.6)			7054	.600 (15.2)		
7039	.280 (7.1)			7055	.650 (16.5)		
7040	.300 (7.6)	.310 (7.9)	.925 (23.5)	7056	.700 (17.8)	.900 (22.9)	.925 (23.5)
7041	.320 (8.1)			7057	.750 (19.1)		
7042	.340 (8.6)			7058	.800 (20.3)		
7043	.350 (8.9)			7059	.850 (21.6)		
7044	.360 (9.1)			7060	.900 (22.9)		
7045	.380 (9.7)			7061	.925 (23.5)		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Keystone Electronics:

7358	8323	8326	8332	8315	8322	8340	8319	8318	8339	8336	8327	8341	8338	8312	8333	8334	8342
8335	8316	8329	8331	8330	8317	8314	8328	8325	8313	8321	8324	8320	8311	8337	8900	8905	8924
8906	8926	8904	8916	8913	8910	8903	8902	8919	8925	8918	8911	8901	8927	8907	8921	8917	8928
8929	8912	8922	8908	8915	8923	8909	8914	8920	7377	7352	7373	7356	7357	7354	7359	7355	7353
7375	7371	7351	7370	7372	7374	7376	7379	7378	7368	7367	7363	7381	7364	7382	7361	7362	7369
7365	7366	7380	7360	8930	8931	7030	7031	7032	7033								