




**Data Sheet**

Product Category: IF SAW Filter

Part Number
835-IF70.0M-DAPackage
35.0 x 12.8 Thru HoleApplication
Base Station & RepeaterLast Modified
May 24 2003**TYPE :**70.0 MHz Bandpass Filter
26.25 MHz Bandwidth**PART NUMBER :****835-IF70.0M-DA****OPERATING CONDITIONS / ELECTRICAL CHARACTERISTICS**

PARAMETERS	Minimum	Typical	Maximum	Units
Center Frequency	69.93	70.00	70.07	MHz
Insertion Loss	-	24.2	25	dB
1dB Bandwidth	25.5	25.65	-	MHz
3dB Bandwidth	26.1	26.25	-	MHz
40dB Bandwidth	-	28.45	28.7	MHz
Passband Ripple	-	0.70	1.0	dB
Group Delay Variation	-	42	70	nsec
Absolute Delay	-	1.876	-	µsec
Ultimate Rejection	50	55	-	dB
Substrate Material	-	128° LN	-	-
Ambient Temperature	-	25	-	°C

* Custom SAW IF Filters available. Contact Oscilent for assistance.

PACKAGE OUTLINE (mm)**TEST FIXTURE**

L1 = 56nH L4 = 33nH
 L2 = 120nH L5 = 180nH
 L3 = 56nH
 Source/Load Impedance = 50 ohms

Part No.: 835-IF70.0M-DA

Oscilent Corporation - CALL **949.252.0522**

17962 Sky Park Circle , Building D , Irvine , CA 92614 , USA
Fax: 949.252.0599 , E-Mail: Sales@Oscilent.com

[Crystal Oscillators](#) | [Quartz Crystal](#) | [TCXO](#) | [VCXO](#) | [IF SAW Filter](#) | [RF SAW Filter](#) | [Ceramic Resonator](#)
[Crystal Filter](#) | [Ceramic Filter](#) | [SAW Filter / SAW Devices](#) | [Site Map](#)