

PRODUCT NO.

SEE TABLE

6.30 [0.248]

3.81 [0.150]

THE MYLAR
ONLY FOR 87547-XXX1C/XXX1CLF

SEE NOTE 7

14.1 [0.555]

10.84 [0.427]

15.09 [0.594]

// .127 [0.005] B

1.29 [0.051]
REF2.18 [0.086]
TYP

14.1 [0.555]

SEE DETAIL C

15罐P2X
2X

ϕ 1.90 [0.075]
+0.00 [0.000]
-0.10 [0.004]

1.40 [0.055]
2X

5.72 [0.225]

Δ .10 [0.004]
ALL EIGHT TERMINALS
MEASURED AT HEELS

DETAIL C

NOTE 3

↑ REF.

2.64 [0.104]

18.57 [0.731]

15.49 [0.610]


7.75 [0.305]

17.50 [0.689]

1.22 [0.048]
REF

11.43 [0.450]

15.24 [0.600]

2.66 [0.105]
2X3.73 [0.147]
2X

VIEW A-A

1.27 [0.050] 7X
NON-CUMULATIVE

8.89 [0.350] REF

.40 [0.016] 8X

POS #1

9.22 [0.363]
8X7.16 [0.282]
2X

mat'l. code				tolerances unless otherwise specified		CUSTOMER COPY		FCI	
ltr	ecn no	dr	date						
S	N08-0194	SH	09/08/08	linear	.XX±.3/.XX±.01	projection	title		
K	V12666	LP	1/10/02		.XX±.13/.XXX±.005		A-SMT ASSEMBLY		
L	V21834	LP	12/2/02	angles	.XXX±.051/.XXX±.0020		VERT 8 POS		
M	V04-0861	DAI	08/30/04	dr	0° ±2°	MM/INCH	product family	MOD JACK	code
N	N05-0035	YS	02/18/05	enrg	L.POTTEIGER 12/2/02	scale	size	dwg no	213
P	N05-0142	ZC	6/2/05	chr	J.KONTOS 12/2/02	1:1	A4	87547	sheet
R	N07-0217	WG	09/07/07	appd	J.KONTOS 12/2/02				1 of 2
sheet index	revision	R	R						
	sheet	1	2						



PRODUCT NO.

87547-XXXX

87547-XXXXLF

CONTACT PLATING OPTIONS

1 = GXT .76μm [30μ"]
2 = GOLD 1.27μm [50μ"]
3 = PdNi .64μm [25μ"]
4 = GOLD .76μm [30μ"]

NOT TOOLED

TERMINAL LOADING OPTIONS


1 = FULLY LOADED 8 POSITION
2 = POS. 1,2,7,8 LOADED, 4 POS.
3 = POS. 3,4,5,6 LOADED, 4 POS

COLOR

1 = BLACK
2 = RED

PACKAGE OPTIONS

BLISTER PACKAGE (TAPE & REEL)	24" REEL
1 = LOADED FACE UP	
BLISTER PACKAGE (TAPE & REEL)	NOT TOOLED
2 = LOADED FACE DOWN	
3 = PACKAGED IN TUBES	NOT TOOLED
4 = PACKAGED IN TRAYS	
BLISTER PACKAGE (TAPE & REEL)	15" REEL
5 = LOADED FACE UP	



NOTES:

- MATERIAL: HOUSING - THERMOPLASTIC V-0
CONTACT - PHOSPHOR BRONZE
- PLATING: SOLDER TAILS - FOR 87547-XXXX : 2.54 μm [100 μin] MIN. TIN LEAD
OVER 2.54 μm [100 μin] NICKEL
FOR 87547-XXXXLF: 2 μm [80 μin] MIN. PURE MATTE
TIN OVER 1.27 μm [50 μin] MIN. NICKEL
HOLDDOWN - FOR 87547-XXXX: 2.54 μm [100 μin] MIN TIN LEAD
OVER 2.54 μm [100 μin] NICKEL
FOR 87547-XXXXLF: 2μm [80 μin] MIN. PURE TIN
OVER 1.27 μm [50 μin] MIN. NICKEL
CONTACT AREA PLATING - SEE CHART ON SHEET 2
- MAX "TOE UP" AT TIP = 0.127 [0.005]
- IF LF P/N PACKAGING MEETS GS-14-920 SPECIFICATION.
- THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 40 SECONDS IN A CONVECTION, INFRA-RED OR VAPOR PHASE REFLOW OVEN.
- IF LF P/N THE PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.
- APPLY THE MYLAR ON THE P/N 87547-XXX1 WITH SUFFIX "C" FOR PICKING UP.
FOR INSTANCE 87547-4111CLF .

mat'l. code				tolerances unless otherwise specified		CUSTOMER COPY		FCI	
ltr	ecn no	dr	date	linear	.X±.3/.XX±.01	projection	title	www.fciconnect.com	
S					.XX±.13/.XXX±.005	MM/INCH	A-SMT ASSEMBLY VERT 8 POS		
				angles	XXX±.051/.XXX±.0020	scale	product family MOD JACK	code	
				dr	0° ±2°	1:1	size	213	
				enr	L.POTTEIGER 12/2/02		87547	2 of	
				chr	J.KONTOS 12/2/02				
				appd	J.KONTOS 12/2/02				
sheet index	revision sheet								