

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
A1	-			SESSSESHEET 1 OF 2			
TER							

21	6	38.5	30	45	42.5	38.5	36.5	B (GROOVES) Nuten A-C		5-966140-6 A	4-966140-6 A	18.3g	4	7	TAB (43.4mm)	CuSn0.15/0.20	SEL. SILVER PLATED
													3	7	TAB (34.4mm)	CuSn0.15/0.20	SEL. SILVER PLATED
													2	7	TAB (25.4mm)	CuSn0.15/0.20	SEL. SILVER PLATED
										6-966140-6 C	3-966140-6 C	18.3g	5	1	21 POS. HOUSING	PA66-GF13	NATURAL/natur
													4	7	TAB (43.4mm)	CuSn4	SEL. SILVER PLATED
													3	7	TAB (34.4mm)	CuSn4	SEL. SILVER PLATED
18	5	33.5	25	40	37.5	33.5	31.5	A (GROOVES B-C) Nuten B_C		6-966140-1 C	3-966140-1 C	16.0g	2	7	TAB (25.4mm)	CuSn4	SEL. SILVER PLATED
													1	1	21 POS. HOUSING	PA66-GF13	BLACK/schwarz
													4	6	TAB (43.4mm)	CuSn4	SEL. SILVER PLATED
										6-966140-2 C	3-966140-2 C	13.6g	3	6	TAB (34.4mm)	CuSn4	SEL. SILVER PLATED
													2	6	TAB (25.4mm)	CuSn4	SEL. SILVER PLATED
													1	1	18 POS. HOUSING	PA66-GF13	BLACK/schwarz
15	4	28.5	20	35	32.5	28.5	26.5	A (GROOVES B-C) Nuten B_C		6-966140-2 C	3-966140-2 C	13.6g	4	5	TAB (43.4mm)	CuSn4	SEL. SILVER PLATED
													3	5	TAB (34.4mm)	CuSn4	SEL. SILVER PLATED
													2	5	TAB (25.4mm)	CuSn4	SEL. SILVER PLATED
										6-966140-3 C	3-966140-3 C	11.2g	1	1	15 POS. HOUSING	PA66-GF13	BLACK/schwarz
													4	4	TAB (43.4mm)	CuSn4	SEL. SILVER PLATED
													3	4	TAB (34.4mm)	CuSn4	SEL. SILVER PLATED
12	3	23.5	15	30	27.5	23.5	21.5	A (GROOVES B-C) Nuten B_C		6-966140-3 C	3-966140-3 C	11.2g	2	4	TAB (25.4mm)	CuSn4	SEL. SILVER PLATED
													5	1	12 POS. HOUSING	PA66-GF13	NATURAL/natur
													4	3	TAB (43.4mm)	CuSn4	SEL. SILVER PLATED
										6-966140-4 C	3-966140-4 C	8.9g	3	3	TAB (34.4mm)	CuSn4	SEL. SILVER PLATED
													2	3	TAB (25.4mm)	CuSn4	SEL. SILVER PLATED
													1	1	9 POS. HOUSING	PA66-GF13	BLACK/schwarz
9	2	18.5	10	25	22.5	18.5	16.5	A (GROOVES B-C) Nuten B_C		6-966140-4 C	3-966140-4 C	8.9g	4	2	TAB (43.4mm)	CuSn4	SEL. SILVER PLATED
													3	2	TAB (34.4mm)	CuSn4	SEL. SILVER PLATED
													2	2	TAB (25.4mm)	CuSn4	SEL. SILVER PLATED
										6-966140-5 C	3-966140-5 C	6.6g	1	1	6 POS. HOUSING	PA66-GF13	BLACK/schwarz
																	SURFACE/Oberflaeche
																	COLOUR/ Farbe
POSITIONS Polzahl	n	a±0.2	b	c	d _{0.2}	e _{0.25}	f	CODING Kodierung	CAVITY NUMBERING Kammerbezeichnung	ORDER NO. REV. Bestell-Nr.	ORDER NO. REV. Bestell-Nr.	WEIGHT Gewicht	POS.	QTY Stueck	DESCRIPTION Benennung Einzelteil	MATERIAL Werkstoff	

21	6	38.5	30	45	42.5	38.5	36.5	B (GROOVES) Nuten A-C A (GROOVES B-C) (Nuten B_C)		8-966140-6 A	1-966140-6 A	18.3g	4	7	TAB (43.4mm)	CuSn4	TINNED/verzinkt
													3	7	TAB (34.4mm)	CuSn4	TINNED/verzinkt
													2	7	TAB (25.4mm)	CuSn4	TINNED/verzinkt
18	5	33.5	25	40	37.5	33.5	31.5			9-966140-6 F	966140-6 F	18.3g	5	1	21 POS. HOUSING	PA66-GF13	NATURAL/natur
													4	7	TAB (43.4mm)	CuSn4	TINNED/verzinkt
													3	7	TAB (34.4mm)	CuSn4	TINNED/verzinkt
15	4	28.5	20	35	32.5	28.5	26.5			9-966140-1 F	966140-1 F	16.0g	2	7	TAB (25.4mm)	CuSn4	TINNED/verzinkt
													1	1	21 POS. HOUSING	PA66-GF13	BLACK/schwarz
													4	6	TAB (43.4mm)	CuSn4	TINNED/verzinkt
									9-966140-2 F	966140-2 F	13.6g	3	6	TAB (34.4mm)	CuSn4	TINNED/verzinkt	
												2	6	TAB (25.4mm)	CuSn4	TINNED/verzinkt	
												1	1	18 POS. HOUSING	PA66-GF13	BLACK/schwarz	
12	3	23.5	15	30	27.5	23.5	21.5	B (GROOVES) Nuten A-C A (GROOVES B-C) (Nuten B_C)		8-966140-3 A	1-966140-3 A	11.2g	4	4	TAB (43.4mm)	CuSn4	TINNED/verzinkt
													3	4	TAB (34.4mm)	CuSn4	TINNED/verzinkt
													2	4	TAB (25.4mm)	CuSn4	TINNED/verzinkt
9	2	18.5	10	25	22.5	18.5	16.5			9-966140-3 F	966140-3 F	11.2g	5	1	12 POS. HOUSING	PA66-GF13	NATURAL/natur
													4	4	TAB (43.4mm)	CuSn4	TINNED/verzinkt
													3	4	TAB (34.4mm)	CuSn4	TINNED/verzinkt
6	1	13.5	5	20	17.5	13.5	11.5			9-966140-4 F	966140-4 F	8.9g	2	4	TAB (25.4mm)	CuSn4	TINNED/verzinkt
													1	1	12 POS. HOUSING	PA66-GF13	BLACK/schwarz
													4	3	TAB (43.4mm)	CuSn4	TINNED/verzinkt
									9-966140-5 F	966140-5 F	6.6g	3	3	TAB (34.4mm)	CuSn4	TINNED/verzinkt	
												2	3	TAB (25.4mm)	CuSn4	TINNED/verzinkt	
												1	1	9 POS. HOUSING	PA66-GF13	BLACK/schwarz	
POSITIONS Polzahl	n	a±0.2	b	c	d _{0.2}	e _{0.25}	f	CODING Kodierung	CAVITY NUMBERING Kammerbezeichnung	ORDER NO. REV. Bestell-Nr.	ORDER NO. REV. Bestell-Nr.	WEIGHT Gewicht	POS.	QTY Stueck	DESCRIPTION Benennung Einzelteil	MATERIAL Werkstoff	SURFACE/Oberflaeche
																	COLOUR/ Farbe