

NOTES
Bemerkungen

- 1 SUITABLE FOR PIN CONTACT SEE DRAWING:
Passend zu Stiftkontakt:
TE: 1355933
- 2 FOR FLR-CONDUCTOR ACCORDING TO DIN 72551, PART 6 ONLY
Nur fuer FLR-Leitungen nach DIN 72551, Teil 6
- 3 DETAILS OF DESIGN ARE LEFT TO MANUFACTURER
Einheiten der Ausfuehrung bleiben dem Hersteller ueberlassen

4 MIN. 0.8µm Au OVER MIN. 1.2µm Ni
Min. 0.8µm Au ueber min. 1.2µm Ni


5 2-4 µm ELECTROPLATED SILVER
2-4 µm galvanisch Silber

6 MIN. 0.8µm PdNi OVER MIN. 1.2µm Ni
Min. 0.8µm PdNi ueber min. 1.2µm Ni

7 FOR INSPECTION PURPOSES ONLY
Nur fuer Pruefzwecke

1:1

1:1

THIS DRAWING IS A CONTROLLED DOCUMENT.				DWN S. Garcia 22MAY2000	 TE Connectivity						
				CHN R. Jetter 22MAY2000							
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± n. ISO 8015 1 PLC ± n. ISO 2768- 2 PLC ± mm -E 3 PLC ± n. DIN 16901 4 PLC ANGLES FINISH			APVD -	NAME MICRO POWER QUADLOK BUCHSENKONTAKT Tabellenzeichnung Buchsenkontakt TABLE SOCKET CONTACT	SIZE A 1	CAGE CODE 00779	DRAWING NO. C=1355934	RESTRICTED TO -	
					PRODUCT SPEC 108-18476-1						
MATERIAL -					APPLICATION SPEC 114-18141-1						
					WEIGHT -						
Customer Drawing						SCALE 5:1	SHEET 1	OF 1	REV B		