

HANDLAMPS



WOODHEAD® OFFERS THE MOST EXTENSIVE LINE OF PORTABLE HANDLAMPS FOR USE IN WET, INDUSTRIAL AND COMMERCIAL ENVIRONMENTS

Task lighting in industrial environments can be a challenge for any process. Woodhead handlamps feature the most rugged, longest-lasting enclosures for use in all harsh environments: wet location, industrial duty, commercial duty and general duty.

FEATURES AND BENEFITS

Wide variety of light sources

Fixtures can be selected based on the actual type and amount of light needed for the application

Wide variety of enclosure ratings

Fixtures can be selected based on the application requirements for material, moisture, ruggedness

The most rugged high-performance enclosures

Products can be used for extended periods in the most harsh environments

APPLICATIONS

- Electrical cabinets
- General task lighting
- Spray and washdown areas
- Vaults and inspection areas

Handlamps Watertite® Wet Location Incandescent 75W, 100W



Features and Benefits

- Wet location rated handlamps meet and exceed OSHA requirements for wet location use
- Options on guards and globe types ensure the correct configuration for the application

Reference Information

UL File No.: E59251 (only grounded guards and 1220)
E59049 (1223, 1225 only)
CSA File No.: LR85374 (except polycarbonate globe)



Electrical

Voltage: 120V AC

Physical

Bulb Size: A21

Switch: No

Handle Construction:

Rubber for 1203 and 1207 series

Thermoset polyester for 1220 series

Environmental

NEMA Rating: NEMA 4X

A

Portable Lighting

Grounded Guard	Quick Open Guard	Reflector	Insulated Guard	Guard Material	Globe Material	Cord Type	NEMA Configuration	Cord Length	Lamp Wattage (max.)	Woodhead No.	Order No.
				#8 Gauge Zinc-plated Steel	Tempered glass				100W	1203	130103-0014
Yes				#8 Gauge Zinc-plated Steel	Tempered glass	16/3 SOOW	NEMA 5-15	7.62m (25.00')	100W	1203A163	130103-0015
Yes				#8 Gauge Zinc-plated Steel	Tempered glass	16/3 SOOW	NEMA 5-15	15.24m (50.00')	100W	1203B163	130103-0016
Yes				#8 Gauge Zinc-plated Steel	Tempered glass	16/3 SOOW	NEMA 5-15	30.48m (100.00')	100W	1203D163	130103-0017
Yes				#8 Gauge Zinc-plated Steel	Tempered glass				100W	1203GC	130103-0018
Yes				#8 Gauge Zinc-plated Steel	Tempered glass	16/3 SOOW	NEMA 5-15	7.62m (25.00')	100W	1203GCA163	130103-0019
Yes				#8 Gauge Zinc-plated Steel	Tempered glass	16/3 SOOW	NEMA 5-15	15.24m (50.00')	100W	1203GCB163	130103-0020
			Yes	#8 Gauge Zinc-plated Steel	Tempered glass				100W	1203I	130103-0021
Yes			Yes	#8 Gauge Zinc-plated Steel	Tempered glass	16/3 SOOW	NEMA 5-15	7.62m (25.00')	100W	1203IA163	130103-0022
Yes			Yes	#8 Gauge Zinc-plated Steel	Tempered glass	16/3 SOOW	NEMA 5-15	15.24m (50.00')	100W	1203IB163	130103-0024
Yes			Yes	#8 Gauge Zinc-plated Steel	Clear polycarbonate	16/3 SOOW	NEMA 5-15	15.24m (50.00')	75W	1203IB163P	130103-0025
Yes			Yes	#8 Gauge Zinc-plated Steel	Tempered glass	16/3 SOOW	NEMA 5-15	30.48m (100.00')	100W	1203ID163	130103-0026
Yes			Yes	#8 Gauge Zinc-plated Steel	Tempered glass				100W	1203IGC	130103-0027
				#8 Gauge Zinc-plated Steel	Clear polycarbonate				75W	1203P	130103-0029
Yes	Yes			#8 Gauge Zinc-plated Steel	Clear polycarbonate	16/3 SOOW	NEMA 5-15	7.62m (25.00')	75W	1203PQOA163	130103-0030
		Yes	Yes	#8 Gauge Zinc-plated Steel	Clear polycarbonate				75W	1203PRI	130103-0034
	Yes			#8 Gauge Zinc-plated Steel	Tempered glass				100W	1203QO	130103-0035
Yes	Yes			#8 Gauge Zinc-plated Steel	Tempered glass	16/3 SOOW	NEMA 5-15	7.62m (25.00')	100W	1203QOA163	130103-0036
Yes	Yes			#8 Gauge Zinc-plated Steel	Tempered glass	16/3 SOOW	NEMA 5-15	15.24m (50.00')	100W	1203QOB163	130103-0037
Yes	Yes			#8 Gauge Zinc-plated Steel	Tempered glass				100W	1203QOGC	130103-0038
		Yes		#8 Gauge Zinc-plated Steel	Tempered glass				100W	1203R	130103-0041
Yes		Yes		#8 Gauge Zinc-plated Steel	Tempered glass	16/3 SOOW	NEMA 5-15	7.62m (25.00')	100W	1203RA163	130103-0042
Yes		Yes		#8 Gauge Zinc-plated Steel	Clear polycarbonate	16/3 SOOW	NEMA 5-15	7.62m (25.00')	75W	1203RA163P	130103-0043
Yes		Yes		#8 Gauge Zinc-plated Steel	Tempered glass	16/3 SOOW	NEMA 5-15	15.24m (50.00')	100W	1203RB163	130103-0044
Yes		Yes		#8 Gauge Zinc-plated Steel	Clear polycarbonate	16/3 SOOW	NEMA 5-15	15.24m (50.00')	75W	1203RB163P	130103-0045
Yes		Yes		#8 Gauge Zinc-plated Steel	Tempered glass				100W	1203RGC	130103-0048
		Yes	Yes	#8 Gauge Zinc-plated Steel	Tempered glass				100W	1203RI	130103-0049
Yes		Yes	Yes	#8 Gauge Zinc-plated Steel	Tempered glass	16/3 SOOW	NEMA 5-15	7.62m (25.00')	100W	1203RIA163	130103-0050
Yes		Yes	Yes	#8 Gauge Zinc-plated Steel	Tempered glass	16/3 SOOW	NEMA 5-15	15.24m (50.00')	100W	1203RIB163	130103-0052
Yes		Yes	Yes	#8 Gauge Zinc-plated Steel	Tempered glass	16/3 SOOW	NEMA 5-15	30.48m (100.00')	100W	1203RID163	130103-0054
				Cast Aluminum	Tempered glass				100W	1207	130103-0055
Yes				Cast Aluminum	Tempered glass	16/3 SOOW	NEMA 5-15	7.62m (25.00')	100W	1207A163	130103-0056
Yes				Cast Aluminum	Tempered glass	16/3 SOOW	NEMA 5-15	15.24m (50.00')	100W	1207B163	130103-0057
Yes				Cast Aluminum	Tempered glass				100W	1207GC	130103-0058
		Yes		Cast Aluminum	Tempered glass				100W	1207R	130103-0060
Yes		Yes		Cast Aluminum	Tempered glass	16/3 SOOW	NEMA 5-15	7.62m (25.00')	100W	1207RA163	130103-0061
Yes		Yes		Cast Aluminum	Tempered glass	16/3 SOOW	NEMA 5-15	15.24m (50.00')	100W	1207RB163	130103-0062
Yes		Yes		Cast Aluminum	Tempered glass				100W	1207RGC	130103-0063
				N/A	PTFE				100W	1220	130103-0064
				N/A	PTFE	16/2 SOOW	NEMA 1-15	7.62m (25.00')	100W	1223	130103-0065
				N/A	PTFE	16/2 SOOW	NEMA 1-15	15.24m (50.00')	100W	1225	130103-0066

Replacement Parts

Description	Woodhead No.	Order No.
#8 Gauge Zinc-plated Steel Guard	1255	130112-0111
#8 Gauge Zinc-plated Steel Guard, with Reflector	1255R	130112-0114
#8 Gauge Zinc-plated Steel Guard, Quick-Open	1259	130112-0119
Glass Globe	1253	130191-0086
Polycarbonate Globe	41-6762	130112-0186
Teflon Globe with Hook	1229	130112-0110

Handlamps

Wet Location

Watertite®

Fluorescent

13W, 26W , 40W



Features and Benefits

- Wet location rated handlamps meet and exceed OSHA requirements for wet location use.
- Fluorescent handlamps offer bright, diffused illumination but remain cool to the touch
- Fluorescent bulbs and rubber design provide added durability and safety

Reference Information

CSA File No.: LR85374



Electrical

Voltage: 120V AC, 60Hz

NEMA Configuration: NEMA 5-15 Watertite plug

Physical

Switch: Yes

Cord Type: 16/3 SJT00W

Environmental

NEMA Rating: NEMA 4X

Lamp Wattage	Cord Length	Lumens	Lamp Type	Woodhead No.	Order No.
13W	7.62m (25.0')	900	PL13/41	19135A	130108-0170
13W	15.24m (50.0')	900	PL13/41	19135B	130108-0173
26W	7.62m (25.0')	1800	PL-C 26/41/4P	19265A	130108-0179
26W	15.24m (50.0')	1800	PL-C 26/41/4P	19265B	130108-0181
40W	7.62m (25.0')	3150	PL-L 40/41	19405A	130108-0183

Handlamps Super-Safeway™ Industrial Duty Incandescent 100W Max.



Features and Benefits

- The Super-Safeway line of handlamps offer heavy-duty construction and long operating life in the most demanding operating applications
- Rubber handles and 8-gauge Steel guards provide maximum protection for bulbs and electrical components
- Ergonomically designed fencer's flange handle helps protect users from accidentally touching a hot guard
- Available with or without a switch, outlet, quick-open or insulated guard ensuring the correct configuration for the application

Reference Information

UL File No.: E59251

CSA File No.: LR85374



Electrical

NEMA Configuration,

Product with Plug or Outlet: NEMA 5-15

Voltage: 240V max.

Physical

Bulb Size: A21

Handle Construction: Rubber

Guard Material: 8-gauge Zinc-plated Steel

Guard Style: Closed end, 75–100W with reflector

A

Portable Lighting

Handle Assembly				Guard				Complete Light			
Outlet	Switch	Replacement Handle Assembly		Guard Style	Insulated Guard	Replacement Guard		Cord Type	Cord Length	Woodhead Number	Order No.
		Woodhead Number	Order No.			Woodhead Number	Order No.				
None	Yes	1174	130102-0207	Quick Open		1166	130112-0105			1055	130102-0083
		1174	130102-0207	Quick Open		1166	130112-0105	16/3 S00W	7.62m (25.00')	1055A163	130102-0084
		1174	130102-0207	Quick Open		1166	130112-0105	16/3 S00W	15.24m (50.00')	1055B163	130102-0085
		1174	130102-0207	Screw Release		1156	130112-0085			1065	130102-0101
		1174	130102-0207	Screw Release		1156	130112-0085	16/3 S00W	7.62m (25.00')	1065A163	130102-0102
		1174	130102-0207	Screw Release		1156	130112-0085	16/3 S00W	15.24m (50.00')	1065B163	130102-0103
		1174	130102-0207	Screw Release	Yes	1156IG	130112-0087			1065I	130102-0106
		1174	130102-0207	Screw Release	Yes	1156IG	130112-0087	16/3 S00W	15.24m (50.00')	1065IB163	130102-0107
	No	1173	130102-0204	Quick Open		1166	130112-0105			105	130102-0080
		1173	130102-0204	Quick Open		1166	130112-0105	16/3 S00W	7.62m (25.00')	105A163	130102-0081
		1173	130102-0204	Quick Open		1166	130112-0105	16/3 S00W	15.24m (50.00')	105B163	130102-0082
		1173	130102-0204	Screw Release		1156	130112-0085			106	130102-0095
		1173	130102-0204	Screw Release		1156	130112-0085	16/3 S00W	7.62m (25.00')	106A163	130102-0096
		1173	130102-0204	Screw Release		1156	130112-0085	16/3 S00W	15.24m (50.00')	106B163	130102-0097
		1173	130102-0204	Screw Release	Yes	1156IG	130112-0087			106I	130102-0098
Side	Yes	1175US	130102-0211	Quick Open		1166	130112-0105			105US	130102-0090
		1175US	130102-0211	Quick Open		1166	130112-0105	16/3 S00W	7.62m (25.00')	105USA163	130102-0091
		1175US	130102-0211	Quick Open		1166	130112-0105	16/3 S00W	15.24m (50.00')	105USB163	130102-0093
		1175US	130102-0211	Screw Release		1156	130112-0085			106US	130102-0114
		1175US	130102-0211	Screw Release		1156	130112-0085	16/3 S00W	7.62m (25.00')	106USA163	130102-0117
		1175US	130102-0211	Screw Release	Yes	1156IG	130112-0087			106USI	130102-0123
		1175US	130102-0211	Screw Release	Yes	1156IG	130112-0087	16/3 S00W	7.62m (25.00')	106USIA163	130102-0124
	No	1175US	130102-0211	Screw Release	Yes	1156IG	130112-0087	16/3 S00W	15.24m (50.00')	106USIB163	130102-0125
		1175U	130102-0210	Quick Open		1166	130112-0105			105U	130102-0086
		1175U	130102-0210	Quick Open		1166	130112-0105	16/3 S00W	7.62m (25.00')	105UA163	130102-0087
		1175U	130102-0210	Quick Open		1166	130112-0105	16/3 S00W	15.24m (50.00')	105UB163	130102-0088
		1175U	130102-0210	Screw Release		1156	130112-0085			106U	130102-0108
		1175U	130102-0210	Screw Release		1156	130112-0085	16/3 S00W	7.62m (25.00')	106UA163	130102-0109
		1175U	130102-0210	Screw Release		1156	130112-0085	16/3 S00W	15.24m (50.00')	106UB163	130102-0110
		1175U	130102-0210	Screw Release	Yes	1156IG	130112-0087			106UI	130102-0111
		1175U	130102-0210	Screw Release	Yes	1156IG	130112-0087	16/3 S00W	7.62m (25.00')	106UIA163	130102-0112
		1175U	130102-0210	Screw Release	Yes	1156IG	130112-0087	16/3 S00W	15.24m (50.00')	106UIB163	130102-0113

Handlamps

Super-Safeway™

Industrial Duty

Incandescent, 100W Max.



Features and Benefits

- The Super-Safeway line of handlamps offer heavy-duty construction and long operating life in the most demanding operating applications
- Unique quick-open nylon guard runs cooler than standard metal guards
- Available with or without switch or outlet ensuring the correct configuration for the application

Reference Information

UL File No.: E59251

CSA File No.: LR85374



Electrical

NEMA Configuration,

Product with Plug or Outlet: NEMA 5-15

Voltage: 240V max.

Physical

Bulb Size: A21

Handle Construction: Rubber

Guard Material: Nylon

Guard Style: Closed end, 75–100W, quick open

Outlet	Switch	Replacement Handle Assembly		Replacement Guard		Complete Light			
		Woodhead Number	Order No.	Woodhead Number	Order No.	Cord Type	Cord Length	Woodhead Number	Order No.
None	No	1173	130102-0204	1168	130112-0106			118	130102-0212
		1173	130102-0204	1168	130112-0106	16/3 SOOW	7.62m (25.00')	118A163	130102-0213
		1173	130102-0204	1168	130112-0106	16/3 SOOW	15.24m (50.00')	118B163	130102-0214
	Yes	1174	130102-0207	1168	130112-0106			118S	130102-0215
		1174	130102-0207	1168	130112-0106	16/3 SOOW	7.62m (25.00')	118SA163	130102-0216
		1174	130102-0207	1168	130112-0106	16/3 SOOW	15.24m (50.00')	118SB163	130102-0217
Side	No	1175U	130102-0210	1168	130112-0106	16/3 SOOW	15.24m (50.00')	118UB163	130102-0221
	Yes	1175US	130102-0211	1168	130112-0106			118US	130102-0222
		1175US	130102-0211	1168	130112-0106	16/3 SOOW	7.62m (25.00')	118USA163	130102-0223
		1175US	130102-0211	1168	130112-0106	16/3 SOOW	15.24m (50.00')	118USB163	130102-0224
		1175US	130102-0211	1168	130112-0106	16/3 SOOW	15.24m (50.00')	118USB163	130102-0224

Handlamps

Super-Safeway™

Industrial Duty

Incandescent, 100W Max.



Features and Benefits

- The Super-Safeway line of handlamps offer heavy-duty construction and long operating life in the most demanding operating applications
- Rubber handles and 8-gauge Steel guards provide maximum protection for bulbs and electrical components
- Ergonomically designed fencer's flange handle helps protect users from accidentally touching a hot guard
- Available with or without a switch, outlet, reflector or insulated guard ensuring the correct configuration for the application

Reference Information

CSA File No.: LR85374



Electrical

NEMA Configuration,

Product with Plug or Outlet: NEMA 5-15

Voltage: 240V max.

Physical

Bulb Size: A21

Handle Construction: Rubber

Guard Material: 8-gauge Zinc-plated Steel

Guard Style: Open end, 75–100W

Handle Assembly				Guard				Complete Light			
Outlet	Switch	Replacement Handle Assembly		Reflector	Insulated Guard	Replacement Guard		Cord Type	Cord Length	Woodhead Number	Order No.
		Woodhead Number	Order No.			Woodhead Number	Order No.				
None	No	1173	130102-0204			1160	130112-0092			110	130102-0138
		1173	130102-0204	Yes		1164	130112-0099			114	130102-0167
		1173	130102-0204	Yes		1164	130112-0099	16/3 SOOW	7.62m (25.00')	114A163	130102-0168
		1173	130102-0204	Yes		1164	130112-0099	16/3 SOOW	15.24m (50.00')	114B163	130102-0169
Side	No	1175U	130102-0210			1160	130112-0092			110U	130102-0140
		1175U	130102-0210			1160	130112-0092	16/3 SOOW	7.62m (25.00')	110UA163	130102-0141
		1175U	130102-0210			1160	130112-0092	16/3 SOOW	15.24m (50.00')	110UB163	130102-0142
		1175U	130102-0210	Yes		1164	130112-0099			114U	130102-0171
		1175U	130102-0210	Yes		1164	130112-0099	16/3 SOOW	7.62m (25.00')	114UA163	130102-0172
		1175U	130102-0210	Yes		1164	130112-0099	16/3 SOOW	15.24m (50.00')	114UB163	130102-0173
		1175U	130102-0210	Yes	Yes	1164IG	130112-0101			114UI	130102-0176
		1175US	130102-0211			1160	130112-0092			110US	130102-0143
	Yes	1175US	130102-0211	Yes		1164	130112-0099			114US	130102-0177
		1175US	130102-0211	Yes		1164	130112-0099	16/3 SOOW	7.62m (25.00')	114USA163	130102-0178
		1175US	130102-0211	Yes	Yes	1164IG	130112-0101	16/3 SOOW	7.62m (25.00')	114USIA163	130102-0183
		1175US	130102-0211	Yes		1164	130112-0099	16/3 SOOW	15.24m (50.00')	114USB163	130102-0180
		1175US	130102-0211	Yes	Yes	1164IG	130112-0101	16/3 SOOW	15.24m (50.00')	114USIB163	130102-0184
		1175US	130102-0211	Yes		1164	130112-0099	16/3 SOOW	15.24m (50.00')	114USIB163	130102-0184
		1175US	130102-0211	Yes		1164	130112-0099	16/3 SOOW	15.24m (50.00')	114USIB163	130102-0184
		1175US	130102-0211	Yes		1164	130112-0099	16/3 SOOW	15.24m (50.00')	114USIB163	130102-0184

Hand Lamps Super-Safeway™ Industrial Duty Incandescent 100W Max.



Features and Benefits

- The Super-Safeway line of handlamps offer heavy-duty construction and long operating life in the most demanding operating applications
- Rubber handles and 8-gauge Steel guards provide maximum protection for bulbs and electrical components
- Ergonomically designed fencer's flange handle helps protect users from accidentally touching a hot guard
- Available with or without switch, outlet, reflector or insulated guard ensuring the correct configuration for the application

Reference Information

CSA File No.: LR85374



Electrical

NEMA Configuration,

Product with Plug or Outlet: NEMA 5-15
Voltage: 240V max.

Physical

Bulb Size: A23

Handle Construction: Rubber

Guard Material: 8-gauge Zinc-plated Steel

Guard Style: Open end, 200–300W

A

Portable Lighting

Handle Assembly				Guard				Complete Light			
Outlet	Switch	Replacement Handle Assembly		Reflector	Insulated Guard	Replacement Guard		Cord Type	Cord Length	Woodhead Number	Order No.
		Woodhead Number	Order No.			Woodhead Number	Order No.				
None	No	1173	130102-0204			1161	130112-0095			111	130102-0145
		1173	130102-0204			1161	130112-0095	16/3 S00W	7.62m (25.00')	111A163	130102-0146
		1173	130102-0204			1161	130112-0095	16/3 S00W	15.24m (50.00')	111B163	130102-0148
		1173	130102-0204		Yes	1161IG	130112-0097	16/3 S00W	15.24m (50.00')	111B163	130102-0152
		1173	130102-0204	Yes		1165	130112-0102			115	130102-0185
		1173	130102-0204	Yes	Yes	1165IG	130112-0104			115I	130102-0189
		1173	130102-0204	Yes		1165	130112-0102	16/3 S00W	15.24m (50.00')	115B163	130102-0188
		1173	130102-0204	Yes	Yes	1165IG	130112-0104	16/3 S00W	15.24m (50.00')	115B163	130102-0190
	Yes	1174	130102-0207			1161	130112-0095			111S	130102-0153
Side	No	1175U	130102-0210			1161	130112-0095			111U	130102-0158
		1175U	130102-0210			1161	130112-0095	16/3 S00W	7.62m (25.00')	111UA163	130102-0159
		1175U	130102-0210			1161	130112-0095	16/3 S00W	15.24m (50.00')	111UB163	130102-0160
		1175U	130102-0210			1161	130112-0095	16/3 S00W	15.24m (50.00')	111UB163	130102-0163
		1175U	130102-0210	Yes		1165	130112-0102			115U	130102-0192
		1175U	130102-0210	Yes		1165	130112-0102			115UI	130102-0196
		1175U	130102-0210	Yes		1165	130112-0102	16/3 S00W	7.62m (25.00')	115UA163	130102-0193
		1175U	130102-0210	Yes	Yes	1165IG	130112-0104	16/3 S00W	15.24m (50.00')	115UB163	130102-0194
	Yes	1175US	130102-0211			1161	130112-0095			111US	130102-0164
		1175US	130102-0211			1161	130112-0095	16/3 S00W	7.62m (25.00')	111USA163	130102-0165
		1175US	130102-0211	Yes		1165	130112-0102			115US	130102-0198
		1175US	130102-0211	Yes		1165	130112-0102			115USI	130102-0201
		1175US	130102-0211	Yes		1165	130112-0102	16/3 S00W	7.62m (25.00')	115USA163	130102-0199
		1175US	130102-0211	Yes	Yes	1165IG	130112-0104	16/3 S00W	7.62m (25.00')	115USIA163	130102-0202
		1175US	130102-0211	Yes		1165	130112-0102	16/3 S00W	15.24m (50.00')	115USB163	130102-0200
		1175US	130102-0211	Yes	Yes	1165IG	130112-0104	16/3 S00W	15.24m (50.00')	115USIB163	130102-0203

Hand Lamps

Super-Safeway™

Industrial Duty Incandescent PAR38 Bulb



Features and Benefits

- The Super-Safeway line of hand lamps offer heavy-duty construction and long operating life in the most demanding operating applications
- Rubber handles and 8-gauge Steel guards provide maximum protection for bulbs and electrical components
- Ergonomically designed fender's flange handle helps protect users from accidentally touching a hot guard
- Available with or without a switch or outlet ensuring the correct configuration for the application

Electrical

NEMA Configuration,
Product with Plug or Outlet: NEMA 5-15
Voltage: 240V max.

Physical

Bulb Size: PAR38
Handle Construction: Rubber
Guard Material: 8-gauge Zinc-plated Steel
Guard Style: Open end, PAR38

Handle Assembly				Guard		Complete Light			
Outlet	Switch	Replacement Handle Assembly		Replacement Guard		Cord Type	Cord Length	Woodhead Number	Order No.
		Woodhead Number	Order No.	Woodhead Number	Order No.				
None	No	1173	130102-0204	1181	130112-0108			119	130102-0226
		1173	130102-0204	1181	130112-0108	16/3 SOOW	7.62m (25.00')	119A163	130102-0227
		1173	130102-0204	1181	130112-0108	16/3 SOOW	15.24m (50.00')	119B163	130102-0228
	Yes	1174	130102-0207	1181	130112-0108			119S	130102-0229
		1174	130102-0207	1181	130112-0108	16/3 SOOW	7.62m (25.00')	119SA163	130102-0230
Side	Yes	1175US	130102-0211	1181	130112-0108			119US	130102-0234
		1175US	130102-0211	1181	130112-0108	16/3 SOOW	7.62m (25.00')	119USA163	130102-0235
	No	1175U	130102-0210	1181	130112-0108	16/3 SOOW	15.24m (50.00')	119UB163	130102-0233

Hand Lamps Super-Safeway™ Industrial Duty Fluorescent 4W, 8W, 15W, 30W



Features and Benefits

- Fluorescent hand lamps offer bright, diffused illumination but remain cool to the touch
- Fluorescent bulbs and rubber design provide added durability and safety
- Dual hooks provide additional options for mounting

Reference Information

UL File No.: E59049 (except 1013-3, 1015-3)
CSA File No.: LR85374



Electrical

NEMA Configuration: NEMA 5-15
Voltage: 120V 60Hz

Physical

Handle Construction: Rubber
Cord Type: 18/3 SJTW

Switch	Lamp Wattage	Ballast Location	Cord Length	Lumens	Lamp Type	Woodhead No.	Order No.
No	4W	Cord	5.49m (18.00')	95	F4/T5	1045	130108-0091
	8W	Cord	5.49m (18.00')	300	F8/T5	1049	130108-0092
Yes	15W	Handle	7.62m (25.00')	910	F15/T8	1003-3	130108-0078
		Handle	15.24m (50.00')	910	F15/T8	1005-3	130108-0083
	30W	Cord	7.62m (25.00')	2000	F30/T8	1013-3	130108-0085
		Cord	15.24m (50.00')	2000	F30/T8	1015-3	130108-0088

Hand Lamps Super-Safeway™ Industrial Duty Fluorescent 13W, 27W, 40W



Features and Benefits

- Fluorescent handlamps offer bright, diffused illumination but remain cool to the touch
- Fluorescent bulbs and rubber design provide added durability and safety
- Models available for European & Asian electrical requirements

Reference Information

UL File No.: E59049 (only 120V AC 60Hz with switch and ballast in handle)
CSA File No.: LR85374



Physical

Handle Construction: Rubber
Guard Material: Butyrate

Switch	Fixture Voltage	Lamp Wattage	Cord Type	Ballast Location	NEMA Configuration	Cord Length	Lumens	Lamp Type	Woodhead No.	Order No.		
No	120V AC 60 Hz	13W	16/3 SJTOW	Handle	NEMA 5-15	7.62m (25.00')	900	PL13/41	1086-3NS	130108-0134		
			18/3 SJTOOW	Cord	NEMA 5-15	7.62m (25.00')			1083-3NS	130108-0122		
Yes	120V AC 60 Hz		16/3 SJTOW	Handle	NEMA 5-15	7.62m (25.00')			1086-3	130108-0128		
			18/3 SJTOOW	Cord	NEMA 5-15	15.24m (50.00')			1087-3	130108-0136		
					NEMA 5-15	7.62m (25.00')			1083-3	130108-0106		
					NEMA 5-15	15.24m (50.00')			1085-3	130108-0125		
						7.62m (25.00')			1083-3-P	130108-0123		
						15.24m (50.00')			1085-3-P	130108-0126		
	230V AC 50 Hz				27W	NEMA 5-15			7.62m (25.00')	1800	PL-L27/41	1093-3
			NEMA 5-15	15.24m (50.00')		1095-3			130108-0143			
		120V AC 60 Hz	40W	NEMA 5-15		7.62m (25.00')	3150	PL-L40/41	1097-3			130108-0144
				NEMA 5-15		15.24m (50.00')			1099-3			130108-0149

Replacement Parts

Description	Woodhead No.	Order No.
13W Replacement Lamp	34-0350	130191-0021
27W Replacement Lamp	34-0130	130191-0036
40W Replacement Lamp	34-0120	130191-0035
1083-3 with Switch, Head Only	1083-3HON	130112-0068
1086-3 with Switch & Ballast, Head Only	1086-3HO	130108-0133
Shield Assembly for 13W Lights	40-1040	130112-0176

Hand Lamps

Safeway®

Commercial Duty Incandescent 100W Max.



Features and Benefits

- Phenolic handle and 8-gauge Steel guard provide rugged protection for bulb and electrical components
- Available with or without a switch, outlet or quick-open guard ensuring the correct configuration for the application

Reference Information

UL File No.: E59251
CSA File No.: LR85374



Electrical

NEMA Configuration,
Product with Plug or Outlet: NEMA 5-15
Voltage: 240V max.

Physical

Bulb Size: A21
Handle Construction: Phenolic
Guard Material: 8-gauge Zinc-plated Steel
Guard Style: Closed end, 75–100W with reflector

Handle Assembly				Guard			Complete Light			
Outlet	Switch	Replacement Handle Assembly		Guard Style	Replacement Guard		Cord Type	Cord Length	Woodhead No.	Order No.
		Woodhead No.	Order No.		Woodhead No.	Order No.				
None	Yes	270-1	130102-0245	Quick Open	1166	130112-0105			276S	130102-0266
		270-1	130102-0245		1166	130112-0105	16/3 SJTOW	15.24m (50.0')	276SB163	130102-0268
		270-1	130102-0245	Screw Release	1156	130112-0085			271S	130102-0252
		270-1	130102-0245		1156	130112-0085	16/3 SJTOW	7.62m (25.0')	271SA163	130102-0253
		270-1	130102-0245		1156	130112-0085	16/3 SJTOW	15.24m (50.0')	271SB163	130102-0254
Side	No	270-2	130102-0246	Quick Open	1166	130112-0105			276U	130102-0269
		270-2	130102-0246		1166	130112-0105	16/3 SJTOW	7.62m (25.0')	276UA163	130102-0270
		270-2	130102-0246		1166	130112-0105	16/3 SJTOW	15.24m (50.0')	276UB163	130102-0271
		270-2	130102-0246	Screw Release	1156	130112-0085			271U	130102-0256
		270-2	130102-0246		1156	130112-0085	16/3 SJTOW	7.62m (25.0')	271UA163	130102-0257
		270-2	130102-0246		1156	130112-0085	16/3 SJTOW	15.24m (50.0')	271UB163	130102-0258
	Yes	270-3	130102-0247	Quick Open	1166	130112-0105			276US	130102-0272
		270-3	130102-0247		1166	130112-0105	16/3 SJTOW	7.62m (25.0')	276USA163	130102-0273
		270-3	130102-0247		1166	130112-0105	16/3 SJTOW	15.24m (50.0')	276USB163	130102-0274
		270-3	130102-0247	Screw Release	1156	130112-0085			271US	130102-0259
		270-3	130102-0247		1156	130112-0085	16/3 SJTOW	7.62m (25.0')	271USA163	130102-0260
		270-3	130102-0247		1156	130112-0085	16/3 SJTOW	15.24m (50.0')	271USB163	130102-0261

Handlamps

Safeway®

Commercial Duty

Incandescent

100W Max.



- Features and Benefits**
- Nylon handle with switch and outlet provides convenience
 - Quick-open guard makes bulb changes quick and easy
- Reference Information**
- UL File No.: E59049
 CSA File No.: LR85374
- c  us 

- Electrical**
- NEMA Configuration: NEMA 5-15
 Voltage: 120V AC 60Hz
- Physical**
- Bulb Size: A21
 Handle Construction: Nylon
 Guard Material: 10-gauge Zinc-plated Steel
 Guard Style: Quick open with reflector
 Cord Type: 16/3 SJTOW
 Outlet: Yes
 Switch: Yes

Cord Length	Woodhead No.	Order No.
7.62m (25.0')	402	130109-0007
15.24m (50.0')	405	130109-0009

Handlamps Pro-Yellow® Commercial Duty Incandescent 150W Max.



Features and Benefits

- Rating of 150W allows for maximum light output for demanding applications
- Elastomeric grips on handle improve comfort during use

Reference Information

UL File No.: E59049



Electrical

NEMA Configuration: NEMA 5-15

Voltage: 120V AC 60Hz

Physical

Bulb Size: A21

Handle Construction: Nylon

Guard Material: 10-gauge Zinc-plated Steel

Guard Style: Quick open with reflector

Cord Type: 16/3 SJTW

Outlet: Yes

Switch: Yes

Cord Length	Woodhead No.	Order No.
7.62m (25.0')	WT6C-25	130109-0026
15.24m (50.0')	WT6C-50	130109-0027

Handlamps Pro-Yellow® General Duty Incandescent 100W Max.



Features and Benefits

- Hide-away guard rotates for easy bulb changes
- All plastic guard will run cooler than metal guards
- Elastomeric grips on handle improve comfort during use

Reference Information

UL File No.: E59049



Electrical

NEMA Configuration: NEMA 5-15

Voltage: 120V AC 60Hz

Physical

Bulb Size: A21

Handle Construction: Nylon

Guard Material: Polypropylene

Guard Style: Hide away

Cord Type: 18/3 SJTW

Outlet: No

Switch: Yes

Cord Length	Woodhead No.	Order No.
6.10m (20.0')	WT3C-20	130109-0017

Handlamps Pro-Yellow® Commercial Duty Fluorescent 26W



Features and Benefits

- Fluorescent handlamps run cooler and are more durable than incandescent
- The 26W lamp provides maximum light output in a compact size
- Elastomeric grips on handle improve comfort during use

Reference Information

UL File No.: E59049



Electrical

NEMA Configuration: NEMA 5-15

Voltage: 120V AC 60Hz

Physical

Bulb Size: PL-C26/41/4P

Handle Construction: Nylon

Guard Material: Polycarbonate

Cord Type: 18/3 SJTW

Outlet: No

Switch: Yes

Cord Length	Lumens	Woodhead No.	Order No.
7.62m (25.0')	1800	WT6F-25	130109-0028
15.24m (50.0')	1800	WT6F-50	130109-0029

Handlamps Pro-Yellow® General Duty Fluorescent 13W



Features and Benefits

- Fluorescent handlamps run cooler and are more durable than incandescent
- The 13W lamp provides adequate light for most general duty tasks
- Elastomeric grips on handle improve comfort during use

Reference Information

UL File No.: E59049



Electrical

NEMA Configuration: NEMA 5-15

Voltage: 120V AC 60Hz

Physical

Bulb Size: PL13/41

Handle Construction: Nylon

Guard Material: Polycarbonate

Cord Type: 18/3 SJTW

Outlet: No

Switch: Yes

Cord Length	Lumens	Woodhead No.	Order No.
6.10m (20.0')	900	WT3F-20	130109-0020

A

Portable Lighting