

	1	2	3	4	5	6	7																																																																									
A	1,02 0,56 13,46 A 16,30 3,5±0,30 15,88 2,54 8,89 6,5 31°±0,5° SECTION A-A C 6,35 1,27 R0,30 18° R0,50 3,10 3,40 0,50 1,85 2,53 3,88 Detail C 2:1 PC Board Layout Component Side Shown NOTES: Mechanical: 1. Housing material : Glass Filled Polyester UL94V-0 , Color: Black 2. Contact material: Phosphor Bronze t=0.35mm 3. Contact plating: Contact area---Selective gold plating Tails---Tin plated all over 50u" Nickel 4. Operating Life: 750 Cycles min. 5. PCB Retention Pre-solder: 1 LB min. 6. PCB Retention Post-solder: 10 LBS min. Electrical: 1. Voltage Rating: 125VAC. 2. Current Rating: 1.5AMP. 3. Contact Resistance: 30mΩ max. 4. Insulation Resistance: 1000MΩ min. @ 500 VDC 5. Dielectric Strength: 750 VAC 50Hz, 1 min. Environmental: 1. Storage: -40°C To +85°C 2. Operation: -40°C~+85°C 3. Wave Soldering Temp: 200~220°C(5~10S) Packing: 100pcs/Tray, 3200pcs/Carton Order code: A-2014-1-X-N-T Contact plating: 1: selective 15u" gold 2: selective 30u" gold 3: selective 50u" gold 4: selective 6u" gold <td>A</td>							A																																																																								
B								B																																																																								
C								C																																																																								
D								D																																																																								
E								E																																																																								
F								F																																																																								
G	RoHS compliant Unit:mm <table><tr><td>Scale</td><td>Free</td><td></td><td></td><td></td><td></td><td>Date</td><td>Name</td><td>Customer-No.</td></tr><tr><td>TOLERANCE</td><td></td><td></td><td></td><td></td><td></td><td>Drawn</td><td>27.05.2013</td><td>Amy</td></tr><tr><td>X.X</td><td>±0.20</td><td></td><td></td><td></td><td></td><td>Approved</td><td>27.05.2013</td><td>Amy</td></tr><tr><td>X.XX</td><td>±0.15</td><td></td><td></td><td></td><td></td><td></td><td></td><td>ASSMANN WSW-No.</td></tr><tr><td>X.XXX</td><td>±0.10</td><td></td><td></td><td></td><td></td><td></td><td></td><td>A-2014-1-X-N-T</td></tr><tr><td>DIM</td><td>TOL</td><td></td><td></td><td></td><td></td><td colspan="3">Drawing-No.</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td colspan="3">ASS 5702 CO</td></tr><tr><td>Angle</td><td>±5°</td><td>Id.</td><td>Modification</td><td>Date</td><td>Name</td><td colspan="3">Replace</td></tr></table> <td>G</td>							Scale	Free					Date	Name	Customer-No.	TOLERANCE						Drawn	27.05.2013	Amy	X.X	±0.20					Approved	27.05.2013	Amy	X.XX	±0.15							ASSMANN WSW-No.	X.XXX	±0.10							A-2014-1-X-N-T	DIM	TOL					Drawing-No.									ASS 5702 CO			Angle	±5°	Id.	Modification	Date	Name	Replace			G
Scale	Free					Date	Name	Customer-No.																																																																								
TOLERANCE						Drawn	27.05.2013	Amy																																																																								
X.X	±0.20					Approved	27.05.2013	Amy																																																																								
X.XX	±0.15							ASSMANN WSW-No.																																																																								
X.XXX	±0.10							A-2014-1-X-N-T																																																																								
DIM	TOL					Drawing-No.																																																																										
						ASS 5702 CO																																																																										
Angle	±5°	Id.	Modification	Date	Name	Replace																																																																										
H								H																																																																								
	1	2	3	4	5	6	7																																																																									