


|          |         |
|----------|---------|
| orange 1 | green 2 |
| white    | white   |
| blue 3   | brown 4 |
| white    | white   |

#### Material:

- Plug: YUS-06 8P8C 50μ"
- Conductor:
  - Wire: Cat.6 PIMF STR 26AWG
  - Bare Copper 26AWG 7/0.16±0.015MM
- Insulator:
  - Thickness Min. at any point: 0.2MM
  - Thickness Max. Avg.: 0.35MM
  - Diameter: 1.05±0.06MM
- Jacket PVC:
  - Thickness Min. at any point: 0.50MM
  - Thickness Max. Avg.: 0.60MM
  - Diameter: 6.1±0.02MM

| PA/R | PINOUT    |      |           |
|------|-----------|------|-----------|
|      | P1(T568B) | WIRE | P2(T568B) |
| 1    | 1         | WHT  | 1         |
|      | 2         | ORG  | 2         |
| 2    | 3         | WHT  | 3         |
|      | 6         | GRN  | 6         |
| 3    | 4         | BLU  | 4         |
|      | 5         | WHT  | 5         |
| 4    | 7         | WHT  | 7         |
|      | 8         | PPN  | 8         |

⊕ = Assmann logo

**RoHS**  
Compliant

ITEM NO.

**A-MCSSP60200/G-R**

TITLE

Cat.6 SFTP Patch Cable - 8P8C 50μ", Green, 20 Meters

**ASSMANN**  
Electronics, Inc.

1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283  
Toll Free: 1-877-277-6266 • Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED  
©Copyright 2010 by Assmann Electronic Components  
All International Rights Reserved