

	1	2	3	4	5	6	7																																																																																							
A								A																																																																																						
B								B																																																																																						
C								C																																																																																						
D	SPECIFICATIONS <table><tr><td>HOUSING</td><td>POLY CARBONATE (PC) UL94V2</td></tr><tr><td>CONTACT BLADE</td><td>HIGH STRENGTH COPPER ALLOY</td></tr><tr><td>MATERIAL</td><td>100 MICRON NICKEL UNDERPLATED</td></tr><tr><td>PLATING TYPE</td><td>8% PHOSPHOR BRONZE</td></tr><tr><td>PLATING THICKNESS:</td><td>GOLD PLATED 6U"</td></tr><tr><td>OPERATING TEMP</td><td>-40° C TO 125° C</td></tr><tr><td>CURRENT RATING</td><td>250V AC MAX AT 2A</td></tr><tr><td>DIELECTRIC</td><td>500V AC</td></tr><tr><td>INSULATION RES</td><td>500MGAOHMS</td></tr></table> COMPLIES WITH FCC68/F							HOUSING	POLY CARBONATE (PC) UL94V2	CONTACT BLADE	HIGH STRENGTH COPPER ALLOY	MATERIAL	100 MICRON NICKEL UNDERPLATED	PLATING TYPE	8% PHOSPHOR BRONZE	PLATING THICKNESS:	GOLD PLATED 6U"	OPERATING TEMP	-40° C TO 125° C	CURRENT RATING	250V AC MAX AT 2A	DIELECTRIC	500V AC	INSULATION RES	500MGAOHMS	D																																																																				
HOUSING	POLY CARBONATE (PC) UL94V2																																																																																													
CONTACT BLADE	HIGH STRENGTH COPPER ALLOY																																																																																													
MATERIAL	100 MICRON NICKEL UNDERPLATED																																																																																													
PLATING TYPE	8% PHOSPHOR BRONZE																																																																																													
PLATING THICKNESS:	GOLD PLATED 6U"																																																																																													
OPERATING TEMP	-40° C TO 125° C																																																																																													
CURRENT RATING	250V AC MAX AT 2A																																																																																													
DIELECTRIC	500V AC																																																																																													
INSULATION RES	500MGAOHMS																																																																																													
E								E																																																																																						
F								F																																																																																						
G	RoHS compliant Unit: mm <table><tr><td>Scale</td><td>Free</td><td></td><td></td><td></td><td></td><td></td><td>Date</td><td>Name</td><td>Customer-No.</td></tr><tr><td colspan="2">TOLERANCE</td><td></td><td></td><td></td><td></td><td>Drawn</td><td>04.06.2014</td><td>Joanna</td><td></td></tr><tr><td>X.</td><td></td><td></td><td></td><td></td><td></td><td>Approved</td><td>04.06.2014</td><td>Joanna</td><td>ASSMANN WSW-No.</td></tr><tr><td>X.X</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>A-MO-8/8-SR</td></tr><tr><td>X.XX</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>DIM</td><td>TOL</td><td></td><td></td><td></td><td></td><td colspan="3" rowspan="3"></td><td>Drawing-No.</td></tr><tr><td>X.°</td><td>±3°</td><td></td><td></td><td></td><td></td><td>ASS 6402 CO</td><td>rev00</td></tr><tr><td>X.X°</td><td>±1.0°</td><td>①</td><td>Drawn</td><td>04.06.2014</td><td>Joanna</td><td></td><td></td></tr><tr><td>Angle</td><td>TOL</td><td>Id.</td><td>Modification</td><td>Date</td><td>Name</td><td>Replace</td><td>Sheet</td><td></td><td></td></tr></table>							Scale	Free						Date	Name	Customer-No.	TOLERANCE						Drawn	04.06.2014	Joanna		X.						Approved	04.06.2014	Joanna	ASSMANN WSW-No.	X.X									A-MO-8/8-SR	X.XX										DIM	TOL								Drawing-No.	X.°	±3°					ASS 6402 CO	rev00	X.X°	±1.0°	①	Drawn	04.06.2014	Joanna			Angle	TOL	Id.	Modification	Date	Name	Replace	Sheet			G
Scale	Free						Date	Name	Customer-No.																																																																																					
TOLERANCE						Drawn	04.06.2014	Joanna																																																																																						
X.						Approved	04.06.2014	Joanna	ASSMANN WSW-No.																																																																																					
X.X									A-MO-8/8-SR																																																																																					
X.XX																																																																																														
DIM	TOL								Drawing-No.																																																																																					
X.°	±3°								ASS 6402 CO	rev00																																																																																				
X.X°	±1.0°	①	Drawn	04.06.2014	Joanna																																																																																									
Angle	TOL	Id.	Modification	Date	Name	Replace	Sheet																																																																																							
H	<table><tr><td>1</td><td>2</td><td>3</td><td>4</td><td>5</td><td>6</td><td>7</td></tr></table>							1	2	3	4	5	6	7	H																																																																															
1	2	3	4	5	6	7																																																																																								