

A21 THRU A27

SINGLE PHASE 2.0AMP SURFACE MOUNT GLASS PASSIVATED RECTIFIER


Features

- Glass passivated die construction
- Ideal for surface mouted applications
- Low reverse leakage
- Metallurgically bonded construction
- High temperature soldering guaranteed:
260℃/10 seconds,0.375"(9.5mm) lead length,
5 lbs. (2.3kg) tension
- Plastic material-UL flammability 94V-0

Mechanical Data

- Case: SOD-123FL, molded plastic
- Terminals: plated leads solderable per
MIL-STD-750, Method 2026
- Polarity: Color band denotes cathode end
- Mounting position: Any

SOD-123FL



Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

Rating at 25℃ ambient temperature unless otherwise specified.

Single Phase, half wave, 60Hz, resistive or inductive load.





For capacitive load, derate current by 20%.

TYPE NUMBER	SYMBOL	A21	A22	A23	A24	A25	A26	A27	UNITS
Peak Repetitive Reverse Voltage	V_{RRM}								
Working Peak Reverse Voltage	V_{RWM}	50	100	200	400	600	800	1000	V
DC Blocking Voltage	V_{DC}								
RMS Reverse Voltage	V_{RMS}	35	70	140	280	420	560	700	V
Average Rectified Output Current @ $T_L = 75^\circ C$	I_O	2.0							A
Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	50							A
Forward Voltage per element @ $I_F = 2.0A$	V_{FM}	1.1							V
Peak Reverse Current @ $T_A = 25^\circ C$ At Rated DC Blocking Voltage @ $T_A = 100^\circ C$	I_R	5.0 100							μA
Typical thermal resistance (NOTE 1)	$R_{\theta JA}$	180							$^\circ C/W$
Typical junction capacitance (NOTE 2)	C_J	4							pF
Operating and Storage Temperature Range	T_J, T_{STG}	-55to+150							$^\circ C$

Note:1. Thermal resistance from junction to ambient at 0.375" (9.5mm) lead length, P.C.B. mounted

2. Measured at 1.0 MHz and applied reverse voltage of 4.0V D.C.

A21 THRU A27

FIG. 1- FORWARD CURRENT DERATING CURVE

FIG. 2-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS

FIG. 3-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT

FIG. 4-TYPICAL JUNCTION CAPACITANCE

FIG. 5 TYPICAL REVERSE CHARACTERISTICS
