Automotive Signal Common Mode Chokes



ACMS-Q4528

Request Samples Check Inventory

4.5 x 3.2 x 2.8 mm
RoHS/RoHS II Compliant
MSL Level = 1

Features

- AEC-Q200 compliant
- PPAP ready and supported
- Manufactured in TS/IATF 16949 production lines
- Excellent impedance characteristics
- Inductance values from 11 µH to 100 µH

Applications

- Differential signal line common mode noise suppression.
- Multimedia devices
- Automotive applications such as ADAS, Infotainment, Sensing, TCU

Electrical Specifications

Part Number	Impedance (Ω) @10MHz		Inductance (µH) (+50/-30%)	DCR (mΩ)	Rated Current (A)	Rated Voltage (Vdc)	Insulation Resistance (MΩ)
	Min	Typ.		Max	Max	Max	Min
ACMS-Q4528-110	300	600	11	600	0.36	50	10
ACMS-Q4528-220	500	1200	22	1000	0.31	50	10
ACMS-Q4528-510	1000	2800	51	1000	0.23	50	10
ACMS-Q4528-101	2000	5800	100	2000	0.20	50	10

Rated Current is based on an Irms temperature rise of 40°C
Inductance Test Conditions: 0.1V, 100KHz
ACMS-Q4528 is AEC-Q200 Automotive certified
ACMS-Q4528 Series is RoHS Compliant and Pb free
Operating Temperature: -55°C to +150°C (Including self-heating)
Storage Temperature (on PCB): -55°C to +150°C
Storage (in original packaging): <40°C, <60% RH

ABRACON

5101 Hidden Creek Ln, Spicewood TX 78669
Phone: 512-371-6159 Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISION Initial Release
3/31/2022

ABRACON IS
ISO9001-2015
CERTIFIED

Automotive Signal Common Mode Chokes



ACMS-Q4528


Request Samples

Check Inventory


4.5 x 3.2 x 2.8 mm
RoHS/RoHS II Compliant
MSL Level = 1

Electrical Specifications


ACMS-Q4528-601




ACMS-Q4528-122



ACMS-Q4528-282



ACMS-Q4528-582



ABRACON

5101 Hidden Creek Ln, Spicewood TX 78669
Phone: 512-371-6159 Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISION Initial Release
3/31/2022

ABRACON IS
ISO9001-2015
CERTIFIED

Automotive Signal Common Mode Chokes





ACMS-Q4528

Request Samples | Check Inventory


4.5 x 3.2 x 2.8 mm
RoHS/RoHS II Compliant
MSL Level = 1

Mechanical Specifications





A	B	C	D	E
4.5 ±0.2	3.2 ±0.2	2.8 ±0.2	0.75 ±0.2	0.85 ±0.2



Recommended Layout

Dimensions: mm

ABRACON

5101 Hidden Creek Ln, Spicewood TX 78669
Phone: 512-371-6159 Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISION Initial Release
3/31/2022

ABRACON IS
ISO9001-2015
CERTIFIED

Automotive Signal Common Mode Chokes




ACMS-Q4528


Request Samples | Check Inventory

4.5 x 3.2 x 2.8 mm
RoHS/RoHS II Compliant
MSL Level = 1

Schematic



Materials



	Description	Specification
a	Upper Plate	Ferrite
b	Core	Ferrite Core
c	Electrode	Ag/Ni/Sn
d	Wire	Enameled Copper Wire

Part Identification

ACMS - ☐ ☐ - ☐ - ☐

ACE-Q200
Q: Automotive Grade
Blank: Commercial grade

Package L x H (mm)
4528: 4.5mm x 2.8mm

Inductance (µH)
i.e. 110: 11µH

Packaging
T: Tape & Reel 500 pcs

ABRACON

5101 Hidden Creek Ln, Spicewood TX 78669
Phone: 512-371-6159 Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISION Initial Release
3/31/2022

ABRACON IS
ISO9001-2015
CERTIFIED

Automotive Signal Common Mode Chokes




ACMS-Q4528

Request Samples | Check Inventory

4.5 x 3.2 x 2.8 mm
RoHS/RoHS II Compliant
MSL Level = 1

Reflow Profile



Zone	Description	Temperature	Times
1	Preheat	T_{SMIN} ~ T_{SMAX} 150°C ~ 200°C	60 ~ 180 sec.
2	Reflow	T_L 217°C	60 ~ 150 sec.
3	Peak heat	T_P 250°C ±5°C	30 sec. MAX

ABRACON

5101 Hidden Creek Ln, Spicewood TX 78669
Phone: 512-371-6159 Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISION Initial Release
3/31/2022

ABRACON IS
ISO9001-2015
CERTIFIED

Automotive Signal Common Mode Chokes




ACMS-Q4528

Request Samples | Check Inventory


4.5 x 3.2 x 2.8 mm
RoHS/RoHS II Compliant
MSL Level = 1

Packaging

Tape & Reel: 500pcs/reel



Series	A	B	C	D
ACMS-Q4528	13.5 ±0.5	60.0 ±2.0	13.5 ±0.5	178 ±2.0



W	P	E	F	P0	P2	Bo	Ao	Ko	D	D1	t
12.0 ±0.10	8.0 ±0.10	1.75 ±0.10	5.5 ±0.10	4.0 ±0.10	2.0 ±0.10	4.9 ±0.10	3.6 ±0.10	3.0 ±0.10	1.5 +0.10/-0	1.5 ±0.10	0.26 ±0.05

Dimensions: mm

ATTENTION: Abracon LLC's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependent Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon LLC is required. Please contact Abracon LLC for more information.

ABRACON

5101 Hidden Creek Ln, Spicewood TX 78669
Phone: 512-371-6159 Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISION Initial Release
3/31/2022

ABRACON IS
ISO9001-2015
CERTIFIED