DATEL Innovation & Excellence

DATEL | 120 Forbes Blvd., Suite 125 Mansfield, MA 02048 | Phone: +1-508-964-5131 | www.datel.com



Image is for illustration purposes only

Part Number ADS-917G-C/883, Sampling A/D Converters

14 Bit, 1MHz (1MSPS), Sampling Analog to Digital (A/D) Converter, 0 to +10V Input range, no pipeline delay, -55°C to +125°C temperature range, High Reliability 883 Screening, RoHS Compliant.

Specifications

Resolution	14 Bit
Number of Channels	1
Sampling Rate	1 MHz
Acquisition Time	570 ns
Power Consumption	1.9 W
Differential Non-Linearity Error/Other	0.75 LSB
Integral Non-Linearity Error/Other	1.5 LSB
Package Type	SMT
Input Range 1st (min)	0 V
Input Range 1st (max)	10 V
Input Range 2nd (min)	-5 V
Input Range 2nd (max)	5 V
Required Supply Voltage 1st	5 V
Required Supply Voltage 3rd	15 V
Required Supply Voltage 4th	-15 V
Total Harmonic Distortion	-84 dB
Signal to Noise Ratio	77 dB
Analog Bandwidth	7 MHz
Operating Temp. Range (min)	-55 ºC
Operating Temp. Range (max)	+125 ºC
RoHS	Yes
Status	Recommended for new design

© DATEL is a registered trademark of DATEL, Inc.