


## AEO/ALO Series

66/120 Watts

**Total Power:** Up to 120 Watts  
**Input Voltage:** 48V  
**# of Outputs:** Single



### Special Features

- 2.3" x 0.9" Industry Standard 8th brick outline
- Baseplate or Openframe construction
- Low Ripple and Noise
- Regulation to zero load
- High Capacitive load start-up
- Fixed Frequency Switching for EMI predictability
- Industry Standard features: Input UVLO with hysteresis, Enable, OVP, OCP, OTP, Output, VoltageTrim, Differential Remote Sense
- Meets Basic Insulation
- EU Directive 2002/95/EC compliant for RoHS

## Electrical Specifications

| Input                         |                                                                           |
|-------------------------------|---------------------------------------------------------------------------|
| Input range:                  | 36 - 75VDC                                                                |
| Input surge:                  | 100V / 100ms                                                              |
| Input UVLO:                   | 33-36 V (UVLO ON)<br>31-31 V (UVLO OFF)                                   |
| Efficiency <sup>2</sup> :     | 93% @ 5V (typical)                                                        |
| Output                        |                                                                           |
| Line / Load Regulation:       | <0.1% $V_O$ (typical)                                                     |
| Load Current:                 | Up to 25A for $V_O \leq 1.8V$                                             |
| Noise / Ripple <sup>1</sup> : | 20mV <sub>PK-PK</sub> (typical for $V_O \leq 2.5V$ )                      |
| Transient Response:           | 2% typical deviation (50% to 75% Step Load)<br><100us settling time (typ) |
| Over Voltage Protection:      | 130% $V_O$ typ (autorecovery)                                             |
| Over Current Protection:      | 130% $I_{O,max}$ typ (autorecovery)                                       |
| Over Temperature Protection:  | 115°C average PCB temperature (autorecovery)                              |
| Switching Frequency:          | Fixed Frequency                                                           |
| Isolation Voltage:            | 1500Vdc                                                                   |
| Control                       |                                                                           |
| Output Voltage Trim:          | $\pm 10\% V_{O,NOM}$                                                      |
| Enable:                       | TTL compatible (Positive or Negative logic)                               |

### Safety

UL, cUL 60950-1 Recognized  
TUV EN60950-1 Licensed



## Environmental Specifications

|                               |                          |
|-------------------------------|--------------------------|
| Operating ambient temperature |                          |
| Openframe:                    | -40 °C to +85 °C Ambient |
| Baseplate:                    | -40 °C to +100 °C Case   |
| Storage temperature:          | -55 °C to +125 °C        |
| MTBF:                         | >1 Million hours         |

| Ordering Information |                |            |              |                                                 |
|----------------------|----------------|------------|--------------|-------------------------------------------------|
| 120W Series          |                |            |              |                                                 |
| Output Voltage       | Output Voltage | Efficiency | Model Number |                                                 |
| 12.0 V               | 10.0 A         | 93.0%      | ALO10B48N-L  |                                                 |
| 5.0 V                | 20.0 A         | 92.0%      | ALO20A48N-L  |                                                 |
| 3.3 V                | 30.0 A         | 91.0%      | ALO30F48N-L  |                                                 |
| 2.5 V                | 35.0 A         | 89.5%      | ALO35G48N-L  | Not for New Designs - Please check LES A Series |
| 1.8 V                | 40.0 A         | 88.0%      | ALO40Y48N-L  |                                                 |
| 1.5 V                | 40.0 A         | 86.0%      | ALO40M48N-L  |                                                 |
| 1.2 V                | 40.0 A         | 85.0%      | ALO40K48N-L  | Not for New Designs - Please check LES A Series |
| 66W Series           |                |            |              |                                                 |
| Output Voltage       | Output Voltage | Efficiency | Model Number |                                                 |
| 12.0 V               | 4.0 A          | 93.0%      | ALO4B48N-L   | Not for New Designs - Please check LES B Series |
| 5.0 V                | 12.0 A         | 92.0%      | ALO12A48N-L  | Not for New Designs - Please check LES B Series |
| 3.3 V                | 20.0 A         | 91.0%      | ALO20F48N-L  | Not for New Designs - Please check LES B Series |
| 2.5 V                | 20.0 A         | 90.0%      | ALO20G48N-L  | Not for New Designs - Please check LES B Series |
| 1.8 V                | 25.0 A         | 88.5%      | ALO25Y48N-L  | Not for New Designs - Please check LES B Series |
| 1.5 V                | 25.0 A         | 86.5%      | ALO25M48N-L  | Not for New Designs - Please check LES B Series |
| 1.2 V                | 25.0 A         | 85.5%      | ALO25K48N-L  | Not for New Designs - Please check LES B Series |

## Options


|          | Construction                                   | Size          | Output Current                                                               | Output Voltage                                                                    | Input Voltage               | Remote ON/OFF Logic              |          | PIN Length O/P Termination                                                                                                            | RoHS Designation                 |
|----------|------------------------------------------------|---------------|------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------|----------------------------------|----------|---------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|
| <b>A</b> | <b>L</b>                                       | <b>O</b>      | <b>10</b>                                                                    | <b>B</b>                                                                          | <b>48</b>                   | <b>N</b>                         | <b>-</b> | <b>6</b>                                                                                                                              | <b>L</b>                         |
|          | L = Low Profile;<br>Openframe<br>E = Baseplate | O = 8th Brick | 10 = 10 Amps<br>20 = 20 Amps<br>30 = 30 Amps<br>35 = 35 Amps<br>40 = 40 Amps | B = 12.0V<br>A = 5.0V<br>F = 3.3V<br>G = 2.5V<br>Y = 1.8V<br>M = 1.5V<br>K = 1.2V | 48 = 48V<br>(36-75 V Range) | N = Negative<br>Blank = Positive |          | Through Hole:<br>6 = 3.6mm<br>Blank = 5mm<br><br>S = Surface Mount*<br>*Available for Low<br>Profile; Openframe<br>(ALO) Version only | L = RoHS 6/6<br>Blank = RoHS 5/6 |

## Mechanical Drawing

### OPEN FRAME THROUGH HOLE

Rev. 09.30.08\_100  
AEO/ALO25 Series  
3 of 4

#### ALO SERIES THRU HOLE PIN




PIN SIDE DOWN

PIN SIDE UP

SIDE VIEW

### BASEPLATE THROUGH HOLE

#### AEO SERIES THRU HOLE PIN



PIN SIDE DOWN

PIN SIDE UP

SIDE VIEW

## Pin Assignments

### Single Output

1. +Vin
2. Enable (On/off)
3. -Vin
4. -VOUT
5. -Sense
6. Trim
7. +Sense
8. +VOUT

### Notes:

1. Measured at 20 MHz bandwidth with external 10  $\mu$ F tant. capacitor in parallel with 0.1  $\mu$ F ceramic capacitor connected across +Vout and -Vout; 220  $\mu$ F e-cap or equivalent connected across +Vin and -Vin.
2. Efficiency measurements are typical values taken at full load, nominal line and  $T_A = 25^\circ\text{C}$ .
3. All specifications are typical at nominal line, full load and  $T_A = 25^\circ\text{C}$  unless otherwise noted.
4. All specifications subject to change without notice.
5. Mechanical drawings are for reference only. Dimensions are in inches [mm]. Pin placement tolerance  $\pm 0.005$  [0.127]. Mechanical Tolerance  $\pm 0.02$  [0.5], recommended surface mount pads (min: 0.080 x 0.112 [2.03 x 2.84] / max: 0.092 x 0.124 [2.34 x 3.15]); through hole pin diameter (Pins 4 & 8)  $\phi = 0.062$  [1.57], others  $\phi = 0.04$  [1.0] (6X).
6. Technical Reference Notes should be consulted for detailed information when available.
8. Warranty 2yrs.

| PIN LENGTH      | A                                  |
|-----------------|------------------------------------|
| Std Pin Length: | 0.189 [4.8] MIN<br>0.205 [5.2] MAX |
| "-6" Option:    | 0.137 [3.5] MIN<br>0.152 [3.9] MAX |


## Mechanical Drawing

### OPEN FRAME SURFACE MOUNT

#### ALO OPEN FRAME SMT PIN



#### PIN SIDE DOWN



#### PIN SIDE UP

#### SIDE VIEW

### Americas

5810 Van Allen Way  
Carlsbad, CA 92008  
USA  
Telephone: +1 760 930 4600  
Facsimile: +1 760 930 0698

### Europe (UK)

Waterfront Business Park  
Merry Hill, Dudley  
West Midlands, DY5 1LX  
United Kingdom  
Telephone: +44 (0) 1384 842 211  
Facsimile: +44 (0) 1384 843 355

### Asia (HK)

14/F, Lu Plaza  
2 Wing Yip Street  
Kwun Tong, Kowloon  
Hong Kong  
Telephone: +852 2176 3333  
Facsimile: +852 2176 3888

For global contact, visit:

[www.powerconversion.com](http://www.powerconversion.com)

[techsupport.embeddedpower@emerson.com](mailto:techsupport.embeddedpower@emerson.com)

While every precaution has been taken to ensure accuracy and completeness in this literature, Emerson Network Power assumes no responsibility, and disclaims all liability for damages resulting from use of this information or for any errors or omissions.

**Emerson Network Power.**  
The global leader in enabling  
business-critical continuity.

- AC Power
- Connectivity
- DC Power
- Embedded Computing
- Embedded Power**
- Monitoring
- Outside Plant
- Power Switching & Controls
- Precision Cooling
- Racks & Integrated Cabinets
- Services
- Surge Protection

**EmersonNetworkPower.com**

Emerson Network Power and the Emerson Network Power logo are trademarks and service marks of Emerson Electric Co.  
©2008 Emerson Electric Co.