

### Quick Jump:

## Heavy-duty, industrial quality, continuous duty heat blower

- 3 models produce 300°F, 500°F or 750°F. High temperatures accommodate many heating, drying & shrinking applications
- High air flow rating - 47 CFM at 2200 FPM means jobs get done fast
- Brushless induction type motor for quiet continuous duty operation
- Rubber backed stand, permits 90° non-slip adjustability. Use in any position or mount on equipment
- Comfort balanced handle for carrying or portable use
- Use to bend plastics, dry materials, parts and ink, heat materials, mount over conveyor lines and on machinery and more



### ORDERING INFORMATION

#### 120V MODELS (UL Listed)

| MODEL NO. | ITEM NO. | DESCRIPTION |       |      |       |        |       |
|-----------|----------|-------------|-------|------|-------|--------|-------|
| AH-301    | 10151    | 300°F       | 150°C | 120V | 10.0A | 1200 W | 60 Hz |
| AH-501    | 10153    | 500°F       | 260°C | 120V | 14.0A | 1680 W | 60 Hz |
| AH-751 *  | 10156    | 750°F       | 400°C | 120V | 18.0A | 2160 W | 60 Hz |

#### CANADIAN MODELS (CSA Certified)

| MODEL NO.  | ITEM NO. | DESCRIPTION |       |      |       |        |       |
|------------|----------|-------------|-------|------|-------|--------|-------|
| AH-301     | 10151    | 300°F       | 150°C | 120V | 10.0A | 1200 W | 60 Hz |
| AH-501-C * | 10154    | 500°F       | 260°C | 120V | 14.0A | 1680 W | 60 Hz |
| AH-751 *   | 10156    | 750°F       | 400°C | 120V | 18.0A | 2160 W | 60 Hz |

#### 230V MODELS

| MODEL NO. | ITEM NO. | DESCRIPTION |       |      |      |        |          |
|-----------|----------|-------------|-------|------|------|--------|----------|
| AH-302    | 10152    | 300°F       | 150°C | 230V | 5.2A | 1200 W | 50/60 Hz |

|        |       |       |       |      |      |        |          |
|--------|-------|-------|-------|------|------|--------|----------|
| AH-502 | 10155 | 500°F | 260°C | 230V | 7.3A | 1680 W | 50/60 Hz |
| AH-752 | 10157 | 750°F | 400°C | 230V | 9.4A | 2160 W | 50/60 Hz |

*All 120 volt models meet NOM requirements in Mexico.*

*\*Comes standard with NEMA plug type-5-20P*

## SPECIFICATIONS

|                                                                             |                                   |
|-----------------------------------------------------------------------------|-----------------------------------|
| ■ Ave. Air Volume: 47 CFM                                                   | ■ Nozzle O.D.: 2.6"               |
| ■ Ave. Air Velocity: 2200 FPM                                               | ■ Nozzle Opening: 1.8"            |
| ■ Motor: Induction                                                          | ■ Cordset: 6 ft., 3-wire grounded |
| ■ Base Size: 6" x 6"                                                        | ■ Net Weight: 6 lbs.              |
| ■ Dimensions: 12" L x 6" W x 9" H,<br>(AH-301 & AH-302, 9" L x 6" W x 9" H) | ■ Shipping Weight: 8 lbs.         |

*Many international voltages/cordsets available upon request.*

*Contact our Sales Department for appropriate Model Numbers.*

## View Replacement Parts List

*Users should independently evaluate the suitability of the product for their application.*

---

[HOME](#)   [BACK TO PRODUCT LISTING](#)